

SET-UP SHEET

XRAY GTXE'22 SET-UP VER. 01 ©XRAY

XRAY GTXE'22 C-HUB

RACE	FRENCH CHAMPIONSHIP ROUND 1		
TRACK	BOURG EN BRESSE		
NAME	Michaël DERDERIAN	DATE	13/06/2021

TEMPERATURE AIR	30	TEMPERATURE TRACK	2
-----------------	----	-------------------	---

LAPS	FINAL POSITION	BEST LAPTIME	RACE LENGTH
	2	17.2 /sec	7 /min

TRACKS			
CONDITION	<input type="checkbox"/> SMOOTH	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY
	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	<input type="checkbox"/> FAST

TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH
----------	------------------------------	--	-------------------------------

FRONT	DIFFERENTIAL		REAR
	CASE MATERIAL		
500 000	OIL		
13T <input checked="" type="checkbox"/> 14T	BEVEL DRIVE GEAR	13T <input type="checkbox"/> 14T	
46	CROWN GEAR	46	

MOTOR PINION	GEARING	SPUR GEAR
20 /T		45 /T
	STANDARD <input checked="" type="checkbox"/> GRAPHITE	

FRONT	SHOCKS		REAR
2 dots	SPRINGS	2 dots	
800 /cSt	OIL	800 /cSt	
standard	MEMBRANE	standard	
	REBOUND		
<input checked="" type="checkbox"/> 6 HOLES	PISTONS	<input checked="" type="checkbox"/> 6 HOLES	
<input type="checkbox"/> 8 HOLES	1.1 mm	<input type="checkbox"/> 8 HOLES	
<input type="checkbox"/> 10 HOLES	1.2 mm	<input type="checkbox"/> 10 HOLES	
	1.3 mm		
	1.4 mm		
	OTHER PISTONS		

FRONT	ANTI-ROLL BAR	REAR
2.5 /mm	THICKNESS	2.8 /mm

FRONT	TIRES		REAR
	TIRES TYPE:	PMT	
	Q5	← COMPOUND →	Q3
	Q5	← COMPOUND →	Q3

ELECTRONICS	
MOTOR	HOBBYWING 2800 KV
SPEEDO	HOBBYWING PRO G2
BATTERY TYPE	IP 10000 mah

BODY	WEIGHT
TYPE ZONDA GT5	TOTAL 3800 /g

COMMENTS

FRONT	C-HUB		FRONT ARM	REAR	
	COMPOSITE <input type="checkbox"/>	ALU <input checked="" type="checkbox"/>	SOFT <input type="checkbox"/>	REAR ARMS	
	CASTER		MEDIUM <input checked="" type="checkbox"/>	HARD <input checked="" type="checkbox"/>	X-HARD <input type="checkbox"/>
	16° <input type="checkbox"/>		HARD <input type="checkbox"/>	GRAPHITE <input type="checkbox"/>	
	6° <input type="checkbox"/>		GRAPHITE <input type="checkbox"/>		
	2° <input checked="" type="checkbox"/>				
OFFSET					
0 <input type="checkbox"/> +1 <input checked="" type="checkbox"/> +2 <input type="checkbox"/>					
CASTER BUSHINGS					
+2° <input type="checkbox"/>					
+1° <input type="checkbox"/>					
0° <input checked="" type="checkbox"/>					
-1° <input type="checkbox"/>					
-2° <input type="checkbox"/>					
FRONT DROOP					
27					
MEASURE UNDER WHEEL AXLE		#107717 GAUGE			

FRONT	SHOCKS		REAR
	WING HIGH		
	GRAPHITE BRACE		
	WITHOUT <input checked="" type="checkbox"/>		
	1-PIECE <input type="checkbox"/>		
	2-PIECES <input type="checkbox"/>		
	REAR DIFFUSOR		
	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>		
	WHEELBASE SHIM POSITION		
	0 mm <input checked="" type="checkbox"/> 2 mm <input type="checkbox"/>		
	SHIMS BEHIND FRONT ARM		
	WHEELBASE SHIM POSITION		
	2 mm <input type="checkbox"/> 4 mm <input checked="" type="checkbox"/>		
	SHIMS IN FRONT OF REAR ARM		
	LOWER ROLL CENTER		
	ECCENTRIC BUSHINGS		

FRONT	SERVO SAVER		REAR
	TIGHTEN	MATERIAL	
	TIGHT <input checked="" type="checkbox"/>	MEDIUM <input checked="" type="checkbox"/>	
	MEDIUM <input type="checkbox"/>	GRAPHITE <input type="checkbox"/>	
	SOFT <input type="checkbox"/>		
	WHEELBASE		
	0 mm <input type="checkbox"/> 1 mm <input type="checkbox"/> 2 mm <input checked="" type="checkbox"/> 3 mm <input type="checkbox"/> 4 mm <input type="checkbox"/>		
	SHIMS IN FRONT OF UPRIGHT		
	STANDARD BATTERY		
	BATTERY SETTING		
	FRONT <input type="checkbox"/> REAR <input type="checkbox"/>		
	SHORT BATTERY <input type="checkbox"/>		

FRONT	CAMBER		REAR
	2	FRONT CAMBER	
	REAR CAMBER	2	
	LENGTH		
	RIDE HEIGHT		
	8 /mm		
	10 /mm		