

XRAY XB4'21

FRONT

APPLIED ☒ NOT APPLIED ☐

STEERING BLOCK

MEDIUM ☐
HARD ☐
GRAPHITE ☒

LONGER BUSHINGS

UP ☒
DOWN ☐

SHIM mm

DRIVE SHAFT

CVD ☐ ECS ☒
Length 83 /mm

ROLL ENTER

LOWER SHOCK POSITION

#107711 GAUGE mm **DOWNSTOP**

REAR UPRIGHT

DRIVE SHAFT

Length 75 /mm

SHIM 2 mm

SHIMS 2 /mm

HARD ☐
GRAPHITE ☐
ALU ☒

#325341 ADJ. DRIVE AXLE
1 2 3 4

1° ☒ 0.5° ☐

#107711 GAUGE

CASTER

6° ☐
9° ☐
12° ☒

CASTER BLOCK

MEDIUM ☐
HARD ☐
GRAPHITE ☐
ALU ☒

WING CUTTING LINE

1 2 3 4 5

WING SIDE LINE

HIGHER ☒
LOWER ☐

WING POSITION

UP ☒
MIDDLE ☐
DOWN ☐

WING THICKNESS

0.75 ☐ 1 ☒ 1.5 ☐

TYPE 323511

OFFSET 3

BUMP STEER

SHIM 4 mm

IN FRONT OF ARM

FF

FR

RR

1° ☒ 0.5° ☐
1° ☒ 0.5° ☐

ROLL CENTER ECCENTRIC BUSHINGS

1° ☒ 0.5° ☐
1° ☒ 0.5° ☐

UP ☒ DOWN ☐

FRONT TOE

OUT 1

STEER. PLATE

HARD ☐
GRAPHITE ☒
ALU ☐

BUMP STEER

SHIM 2 mm

SERVO SAVER

SOFT ☐
MEDIUM ☐
TIGHT ☒

MATERIAL

STANDARD ☐
GRAPHITE ☒

ARM SHIM mm

REAR TOE

IN 3

GRAPHITE FOR REAR BRACE

YES ☒
NO ☐

REAR BRACE

MEDIUM ☐
HARD ☒

ARM SHIM 2 mm

FRONT CAMBER 2

DOWNSTOP

SHIM mm

LENGTH 23 mm

UPSTOP

SHIM mm

COLLAR

STANDARD ☒ -2mm ☐

FRONT DIFF HEIGHT

RIDE HEIGHT 16 mm

REAR DIFF HEIGHT

RIDE HEIGHT 16 mm

REAR CAMBER 2

DOWNSTOP

SHIM mm

LENGTH 29 mm

UPSTOP

SHIM mm

COLLAR

STANDARD ☒ -2mm ☐

FRONT ARMS

LONG ☐
SHORT ☒
MEDIUM ☐
HARD ☒
GRAPHITE ☐

T-BRACE

CHASSIS

STANDARD ☒
2.5mm ☐

REAR ARMS

LONG ☒
SHORT ☐
MEDIUM ☐
HARD ☒
GRAPHITE ☐

CHASSIS FLEX

SCREW USED ☒
SCREW NOT USED ☐

SIDE GUARDS

MEDIUM ☐
HARD ☐
carbon ☒

FRONT BALANCE 20 g

REAR BALANCE 35 g

XRAY 35g

FRONT BALANCE 20 g

REAR BALANCE 35 g