

# SET-UP SHEET

VER.01 ©XRAY

# XRAY X4'22

RACE			
TRACK	P&F hobbies		
NAME	Raymond McCoy	DATE	

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME
	2	2	10.0 /sec	/	

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
SOLID AXLE	<input checked="" type="checkbox"/> YES	
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL 8000 /cSt
PINION 28 /T	SPUR GEAR 110 /T	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
400	OIL /cSt	400
	REBOUND %	
<input type="checkbox"/> YES <input type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input type="checkbox"/> NO

PISTONS	
<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS	<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS
1.0mm	1.1mm
1.2mm	

SHOCK LENGTH FRONT	8.7 /mm	SHOCK LENGTH REAR	8.7 /mm
--------------------	---------	-------------------	---------

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.3
V8's	TIRES	V8's		
Sxt	ADDITIVE	Sxt		
6	ADDITIVE TIMING	6		

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT	1322 /g	WEIGHT BALANCE	FRONT %	REAR %
MOTOR	Trinity 4.0	TIMING		
ESC	Trinity MX10 Pro	BATTERIES	Trinity 6200	
BODY	OG twister .4	WING	Std.	

68 /mm	Dimension from body post to window bottom line	BODY POSITION
WING SIDE PLATE	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	
Dimension from edge to surface		

COMMENTS  
1.6 rc-maker split top decks  
High bite concrete epoxy coated surface.

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
<input checked="" type="checkbox"/> 5° <input type="checkbox"/> 4° <input type="checkbox"/> 3° Adjust with eccentric bushings	BUMP STEER 3 /mm HEIGHT 19 /mm SHIM 4 /mm	<input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> 1.5° <input type="checkbox"/> 2.5° <input type="checkbox"/> 3.5° <input type="checkbox"/> 4.5° <input type="checkbox"/> 5.5° Adjust with eccentric bushings
2 /mm FF <input checked="" type="checkbox"/> RIDE HEIGHT 5 /mm <input type="checkbox"/> SERVO SAVER <input checked="" type="checkbox"/> SERVO HORN		2.5 /mm RF <input checked="" type="checkbox"/> RIDE HEIGHT 5.4 /mm <input type="checkbox"/> RR 2.5 /mm

FRONT	FRONT SUSPENSION	FRONT HUB
1.5 /deg. CAMBER Left = Right	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm <input type="checkbox"/> NO <input type="checkbox"/> DRIVE SHAFT 58mm <input checked="" type="checkbox"/> 59mm <input type="checkbox"/> STD. BEARING <input checked="" type="checkbox"/>	SHIM 2 /mm SHIM 3 /mm FRONT SHOCK POSITION 1 2 3 4 SHIM .5 /mm
	#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 6.0 /mm DOWNSTOP	

REAR	REAR SUSPENSION	REAR HUB
1.25 /deg. CAMBER Left = Right	BODY POST VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/> REAR SHOCK POSITION 1 2 3 4 DRIVE SHAFT 52mm <input checked="" type="checkbox"/> 54mm <input type="checkbox"/> STD. BEARING <input checked="" type="checkbox"/>	SHIM 3 /mm SHIM 3 /mm SHIM 1.5 /mm
	#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4.6 /mm DOWNSTOP	

FRONT TOP VIEW	REAR
1 TOE OUT Left = Right ACKERMANN SHIM /mm DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> UPPER ARM STANDARD <input checked="" type="checkbox"/> OFFSET STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> SHIM /mm	3 TOE IN Left = Right SHIM /mm DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> UPPER ARM STANDARD <input checked="" type="checkbox"/> OFFSET STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> SHIM /mm
TOP DECK TOP DECK FLEX NONE <input checked="" type="checkbox"/> BEARING <input type="checkbox"/> TOP DECK 1.6mm <input checked="" type="checkbox"/> 2.0mm <input type="checkbox"/> TOP DECK CUTTING	

FRONT BOTTOM VIEW	REAR
STEER. LOCK 27 /deg. STEER. SHIM SIZE /mm FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> FR SERVO HOLDER CHASSIS GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU FLEX <input type="checkbox"/> FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/> MOTOR MOUNT CHASSIS T-BRACE REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>