

SET-UP SHEET

VER.01 ©XRAY

XRAY X4'22

RACE	EWS Round 4	
TRACK	EWS	
NAME	Kyle Branson	DATE 13/02/2022

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
20	1	1	13.9 /sec	/	

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
SOLID AXLE	<input checked="" type="checkbox"/> YES	
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL 6000 /cSt
PINION 29 /T	SPUR GEAR 110 /T	FINAL DRIVE RATIO 7.2

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.6
350	OIL /cSt	350
	REBOUND %	
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input type="checkbox"/> 3 HOLES	<input type="checkbox"/> 1.0mm	<input type="checkbox"/> 3 HOLES
<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS

SHOCK LENGTH FRONT 9 /mm	SHOCK LENGTH REAR 9 /mm
--------------------------	-------------------------

1.3 THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm 1.2
RUSH	TIRES	RUSH
MR33	ADDITIVE	MR33
15	ADDITIVE TIMING	15

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT 1325 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
MOTOR	HW 5.0	TIMING	
ESC	HW	BATTERIES	Ip4200
BODY	Speciale	WING	Std

65 /mm	Dimension from body post to window bottom line	BODY POSITION
WING SIDE PLATE	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	
Dimension from edge to surface		

COMMENTS

FRONT CASTER	BUMP STEER	HEIGHT	SHIM	FRONT & REAR SUSPENSION	REAR CASTER	TOE GAIN
Adjust with eccentric bushings	3 /mm	19 /mm	8 /mm		Adjust with eccentric bushings	5 /mm
2 /mm FF	5.2 /mm	FR 2 /mm	<input type="checkbox"/> SERVO SAVER		2.5 /mm RF	5.4 /mm
<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> SERVO HORN		<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT

FRONT CAMBER	BODY STOP	FRONT SUSPENSION	FRONT HUB
2 /deg. Left=Right	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> 16.5 /mm	FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm NO <input type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
		SHIM 0.5 /mm	
DRIVE SHAFT 58mm 59mm STD. BEARING		#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge	DOWNSTOP 6.2 /mm

REAR CAMBER	BODY POST	REAR SUSPENSION	REAR HUB
2 /deg. Left=Right	VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>	SHIM 0.5 /mm 2.5 /mm	COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
		SHIM 1.5 /mm	
DRIVE SHAFT 52mm 54mm STD. BEARING		#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge	DOWNSTOP 4 /mm

FRONT TOP VIEW	REAR TOP VIEW
TOE OUT 1 /mm Left=Right	TOE IN 2.75 /mm Left=Right
ACKERMANN SHIM 0.5 /mm	SHIM /mm
DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>
UPPER ARM STANDARD <input checked="" type="checkbox"/>	UPPER ARM STANDARD <input checked="" type="checkbox"/>
STEERING BRIDGE YES <input type="checkbox"/> NO <input type="checkbox"/>	TOP DECK FLEX NONE <input checked="" type="checkbox"/> BEARING <input type="checkbox"/>
TOP DECK STANDARD <input checked="" type="checkbox"/> SPLITTED <input type="checkbox"/>	TOP DECK 1.6mm <input checked="" type="checkbox"/> 2.0mm <input type="checkbox"/>
OFFSET STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm	OFFSET STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm

FRONT BOTTOM VIEW	REAR BOTTOM VIEW
STEER. LOCK 27.5 /deg.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
STEER. SHIM SIZE 7.5 /mm	MOTOR MOUNT
FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	CHASSIS T-BRACE
FR SERVO HOLDER	CHASSIS
FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>
STEER. PLATE STANDARD <input checked="" type="checkbox"/> +1mm <input type="checkbox"/>	GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input checked="" type="checkbox"/>