

# SET-UP SHEET

XRAY GTX8'22 SET-UP VER. 01 ©XRAY

# XRAY GTX8'22 C-HUB

RACE	National GT championship		
TRACK	New Taipei Metropolitan Park Circuit		
NAME	Sheng-Zhong Wang	DATE	13/03/22

TEMPERATURE AIR	25	TEMPERATURE TRACK	1
LAPS	160	FINAL POS.	1
BEST LAPTIME	7.78 <sub>750C</sub>	RACE LENGTH	50 /min

TRACKS			
CONDITION	<input type="checkbox"/> SMOOTH	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY
	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	<input checked="" type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH

1ST		GEARING		2ND	
<input type="checkbox"/> 15T	<input type="checkbox"/> 16T	<input type="checkbox"/> 17T	<input type="checkbox"/> 18T	<input checked="" type="checkbox"/> 19T	<input type="checkbox"/> 20T
<input type="checkbox"/> 48T	<input type="checkbox"/> 49T	<input checked="" type="checkbox"/> 50T	STANDARD	<input checked="" type="checkbox"/> GRAPHITE	<input type="checkbox"/> 45T
<input type="checkbox"/> 46T	<input type="checkbox"/> 47T				

CLUTCH	
CLUTCH	STANDARD <input type="checkbox"/> OTHER <input type="checkbox"/>
SHOE	#348541
	SPRINGS TIGHTEN 0.2
	SPRING

FRONT DIFFERENTIAL		REAR	
STD	CASE MATERIAL	STD	
500k	OIL	80k	
13T <input checked="" type="checkbox"/> 14T	BEVEL DRIVE GEAR	13T <input checked="" type="checkbox"/> 14T	
46	CROWN GEAR	46	

FRONT SHOCKS		REAR	
#358194	SPRINGS	#358196	
800 /cSt	OIL	800 /cSt	
STD	MEMBRANE	STD	
0 /%	REBOUND	0 /%	
<input checked="" type="checkbox"/> 6 HOLES	PISTONS	<input checked="" type="checkbox"/> 6 HOLES	
<input type="checkbox"/> 8 HOLES	1.1 mm	<input type="checkbox"/> 8 HOLES	
<input type="checkbox"/> 10 HOLES	1.2 mm	<input type="checkbox"/> 10 HOLES	
	1.3 mm		
	1.4 mm		
	OTHER PISTONS		

FRONT ANTI-ROLL BAR		REAR	
2.4 /mm	THICKNESS	3.0 /mm	

FRONT TIRES		REAR	
TIRES TYPE: PMT			
Q5	← COMPOUND →	Q3	
Q5	← COMPOUND →	Q3	

ENGINE	
TYPE	
MUFFLER	
MANIFOLD	
PLUG	
FUEL	

BODY TYPE	TOTAL WEIGHT
Blitz GT5	/g

COMMENTS
1st pinion gear: 14T

FRONT		REAR	
STEERING BLOCK	C-HUB	FRONT ARM	REAR ARMS
COMPOSITE <input checked="" type="checkbox"/>	COMPOSITE <input type="checkbox"/>	SOFT <input type="checkbox"/>	MEDIUM <input type="checkbox"/>
ALU <input type="checkbox"/>	ALU <input checked="" type="checkbox"/>	MEDIUM <input type="checkbox"/>	HARD <input type="checkbox"/>
	CASTER	HARD <input checked="" type="checkbox"/>	X-HARD <input checked="" type="checkbox"/>
	16° <input type="checkbox"/>	GRAPHITE <input type="checkbox"/>	GRAPHITE <input type="checkbox"/>
	6° <input checked="" type="checkbox"/>		
	2° <input type="checkbox"/>		
OFFSET		UPPER SHOCK POSITION	UPRIGHT ROLL CENTER
0 <input checked="" type="checkbox"/>			
+1 <input type="checkbox"/>			
+2 <input type="checkbox"/>			
CASTER BUSHINGS			
+2° <input type="checkbox"/>			
+1° <input type="checkbox"/>			
0° <input checked="" type="checkbox"/>			
-1° <input type="checkbox"/>			
-2° <input type="checkbox"/>			
FRONT DROOP			
27			
MEASURE UNDER WHEEL AXLE	#10717 GAUGE		

FRONT		REAR	
BUMP STEER SHIM	GRAPHITE BRACE	REAR DIFFUSOR	
STEERING BLOCK 0 /mm	WITHOUT <input type="checkbox"/>	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	
STEERING PLATE 6 /mm	1-PIECE <input checked="" type="checkbox"/>		
SHIMS PLACE ALWAYS UNDER	2-PIECES <input type="checkbox"/>		
WHEELBASE SHIM POSITION	WHEELBASE SHIM POSITION		
0 mm <input checked="" type="checkbox"/> 2 mm	2 mm <input checked="" type="checkbox"/> 4 mm		
SHIMS BEHIND FRONT ARM	SHIMS IN FRONT OF REAR ARM		
FF 1° <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/>	FR 1° <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/>		
FR 1° <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/>	RR 1° <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/>		
	LOWER ROLL CENTER		
	ECCENTRIC BUSHINGS		

1.5 FRONT TOE OUT	3.0 REAR TOE IN
TIGHTEN SERVO SAVER MATERIAL	UPPER PLATE
TIGHT <input checked="" type="checkbox"/>	COMPOSITE <input type="checkbox"/>
MEDIUM <input type="checkbox"/>	GRAPHITE <input type="checkbox"/>
SOFT <input type="checkbox"/>	
WHEELBASE	
0 mm <input type="checkbox"/> 1 mm <input checked="" type="checkbox"/> 2 mm <input type="checkbox"/> 3 mm <input type="checkbox"/> 4 mm	
SHIMS IN FRONT OF UPRIGHT	
ACKERMANN POSITION	
3 2 1	
TOP DECK	
COMPOSITE <input checked="" type="checkbox"/>	
GRAPHITE <input type="checkbox"/>	
ENGINE MOUNT	
STANDARD <input checked="" type="checkbox"/>	
MONOBLOCK <input type="checkbox"/>	

2.2 FRONT CAMBER	REAR CAMBER 4
LENGTH STD mm	LENGTH STD mm
RISE HEIGHT 8 /mm	RISE HEIGHT 9.5 /mm