

SET-UP SHEET

VER.01 ©XRAY

XRAY X4'22

RACE	Lux Championship R3		
TRACK	RCCM Mertzig		
NAME	Jacques Libar	DATE	19/20.03.2022

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
23	1	1	6.6 /sec	/	

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input checked="" type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input type="checkbox"/> FAST

TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH
----------	---

FRONT	TRANSMISSION	REAR
SOLID AXLE	<input checked="" type="checkbox"/> YES	
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL 8K /cSt
PINION 37 /T	SPUR GEAR 104 /T	FINAL DRIVE RATIO 5.3

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
425	OIL /cSt	425
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input type="checkbox"/> 3 HOLES	PISTONS	3 HOLES <input type="checkbox"/>
<input type="checkbox"/> 4 HOLES	1.0mm	4 HOLES <input type="checkbox"/>
<input checked="" type="checkbox"/> PSS	1.1mm	<input type="checkbox"/> PSS
	1.2mm	<input checked="" type="checkbox"/>
2x0.8		2x0.8

SHOCK LENGTH FRONT	SHOCK LENGTH REAR
9 /mm	9 /mm

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

volante 28	TIRES	volante 28
MXLR	ADDITIVE	MXLR
15 min	ADDITIVE TIMING	15 min

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT 1334 /g	WEIGHT BALANCE	FRONT 49 %	REAR 51 %
----------------------	----------------	------------	-----------

MOTOR team Zombie 13.5	TIMING
------------------------	--------

ESC Nosram	BATTERIES Team Zombie 6250
------------	----------------------------

BODY Wolverine	WING	std
----------------	------	-----

<p>Dimension from body post to window bottom line</p>	BODY POSITION
<p>Dimension from body post to upper holder</p>	WING SIDE PLATE YES <input type="checkbox"/> NO <input type="checkbox"/>
<p>Dimension from edge to surface</p>	

COMMENTS

FRONT & REAR SUSPENSION	
FRONT CASTER <input checked="" type="checkbox"/> 5° <input type="checkbox"/> 4° <input type="checkbox"/> 3° Adjust with eccentric bushings	REAR CASTER <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/> 1.5° <input type="checkbox"/> 2.5° <input type="checkbox"/> 3.5° <input type="checkbox"/> 4.5° <input type="checkbox"/> 5.5° Adjust with eccentric bushings
BUMP STEER 4 /mm HEIGHT 19 /mm SHIM 4 /mm	TOE GAIN 4 /mm RIDE HEIGHT 3.0 /mm RF <input checked="" type="checkbox"/> 5.4 /mm RR <input checked="" type="checkbox"/> 3.0 /mm
RIDE HEIGHT 5.2 /mm SERVO SAVER <input type="checkbox"/> SERVO HORN <input checked="" type="checkbox"/>	

2 /deg. CAMBER Left = Right	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> /mm	FRONT SUSPENSION FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm NO <input type="checkbox"/> DRIVE SHAFT 58mm <input checked="" type="checkbox"/> 59mm <input type="checkbox"/> STD. BEARING <input checked="" type="checkbox"/>	2 /mm SHIM 2 /mm FRONT SHOCK POSITION 1 2 3 4 FRONT HUB COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> SHIM 0.5 /mm
#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 6.6 /mm DOWNSTOP			

2 /deg. CAMBER Left = Right	BODY POST VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>	REAR SUSPENSION REAR SHOCK POSITION 1 2 3 4 REAR HUB COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> SHIM 1 /mm
DRIVE SHAFT 52mm <input checked="" type="checkbox"/> 54mm <input type="checkbox"/> STD. BEARING <input checked="" type="checkbox"/> #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4.0 /mm DOWNSTOP		

0.5 TOE OUT Left = Right	ACKERMANN SHIM 0. /mm	2.0 TOE IN Left = Right
DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	SHIM 0 /mm BRASS WEIGHT FOR MOTOR MOUNT	DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>
UPPER ARM STANDARD <input checked="" type="checkbox"/>	STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	UPPER ARM STANDARD <input checked="" type="checkbox"/>
OFFSET STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm	TOP DECK FLEX NONE <input checked="" type="checkbox"/> BEARING <input type="checkbox"/> TOP DECK 1.6mm <input type="checkbox"/> 2.0mm <input checked="" type="checkbox"/>	OFFSET STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm
TOP DECK CUTTING		

FRONT BOTTOM VIEW STEER. LOCK 24 /deg. STEER. SHIM SIZE /mm FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> SERVO HOLDER FR RE	REAR T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/> MOTOR MOUNT CHASSIS GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input checked="" type="checkbox"/> REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>
FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> STEER. PLATE STANDARD <input checked="" type="checkbox"/> +1mm <input type="checkbox"/>	