

SET-UP SHEET

VER.01 ©XRAY

XRAY X4'22

RACE	ETS Aigen Start		
TRACK	Aigen		
NAME	Kaufmann Marco	DATE	

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
			/sec	/	

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input checked="" type="checkbox"/> FAST
TRACTION	<input checked="" type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
SOLID AXLE	<input checked="" type="checkbox"/> YES	
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL 7k 151 /cSt
PINION 29 /T	SPUR GEAR 110 /T	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
375	OIL /Cst	375
	REBOUND %	
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input type="checkbox"/> 3 HOLES	<input type="checkbox"/> 1.0mm	<input type="checkbox"/> 3 HOLES
<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS

SHOCK LENGTH FRONT 9 /mm	SHOCK LENGTH REAR 9 /mm
---------------------------------	--------------------------------

1.2 THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm 1.2
TIRES Matrix		
ADDITIVE MR33 Asphalt		
ADDITIVE TIMING 2x 5min		

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT	/g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
--------------	----	----------------	-------------------	------------------

MOTOR	4,5T	TIMING
-------	-------------	--------

ESC	BATTERIES	Gensace
-----	-----------	----------------

BODY	Wolverine 0,5mm	WING	Std 0,5
------	------------------------	------	----------------

	BODY POSITION
	WING SIDE PLATE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>

COMMENTS
T-Brace 0.5mm up. Test ETS: RC Front 2.5mm, RC Rear 3mm, with Softer Shock Oil and Diff and Spool up.

FRONT CASTER	BUMP STEER	HEIGHT	SHIM	REAR CASTER	TOE GAIN
Adjust with eccentric bushings 5° 4° 3°	3.5 /mm	/mm	/mm	Adjust with eccentric bushings 0.5° 1.5° 2.5° 3.5° 4.5° 5.5°	5 /mm
2 /mm FF	5,2 /mm	2 /mm FR	<input type="checkbox"/> SERVO SAVER <input type="checkbox"/> SERVO HORN	2.5 /mm RF	5,6 /mm RR
2 /mm	2 /mm	2 /mm		2.5 /mm	2.5 /mm

FRONT CAMBER	BODY STOP	FRONT SUSPENSION	FRONT HUB
2 /deg. Left = Right	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> /mm	FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
		BULKHEAD SHIMS YES <input type="checkbox"/> 3mm <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SHIM 1 /mm
		DRIVE SHAFT <input checked="" type="checkbox"/> 58mm <input type="checkbox"/> 59mm <input type="checkbox"/> STD. BEARING	SHOCK POSITION 1 2 3 4
		#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge 5,8 /mm

REAR CAMBER	BODY POST	REAR SUSPENSION	REAR HUB
2 /deg. Left = Right	VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>	REAR BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
		BULKHEAD SHIMS YES <input type="checkbox"/> 3mm <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SHIM 1 /mm
		DRIVE SHAFT <input type="checkbox"/> 52mm <input checked="" type="checkbox"/> 54mm <input type="checkbox"/> STD. BEARING	SHOCK POSITION 1 2 3 4
		#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge 3,8 /mm

FRONT TOP VIEW	REAR TOP VIEW
TOE OUT 1 /mm Left = Right	TOE IN 3 /mm Left = Right
ACKERMANN SHIM 0.5 /mm	SHIM 1 /mm
DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>
UPPER ARM STANDARD <input checked="" type="checkbox"/>	UPPER ARM STANDARD <input checked="" type="checkbox"/>
STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	TOP DECK FLEX NONE <input type="checkbox"/> BEARING <input type="checkbox"/>
TOP DECK <input checked="" type="checkbox"/> SPLITTED	TOP DECK 1.6mm <input checked="" type="checkbox"/> 2.0mm
OFFSET STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm	OFFSET STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> SHIM/mm

FRONT BOTTOM VIEW	REAR BOTTOM VIEW
STEER. LOCK 26 /deg.	T-BRACE ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/>
STEER. SHIM SIZE 8 /mm	MOTOR MOUNT
FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	CHASSIS T-BRACE
FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>
STEER. PLATE STANDARD <input checked="" type="checkbox"/> +1mm <input type="checkbox"/>	CHASSIS GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input type="checkbox"/>