

SET-UP SHEET

XRAY GTX8'23 SET-UP VER. 01 ©XRAY

XRAY GTX8'23 C-HUB

RACE	Basic	
TRACK	Hudy Arena	
NAME	XRAY	DATE

TEMPERATURE AIR		TEMPERATURE TRACK	
LAPS		FINAL POS.	
BEST LAPTIME		/sec	
RACE LENGTH		/min	

TRACKS		
CONDITION	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM
	<input type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED
TRACTION	<input type="checkbox"/> LOW	<input type="checkbox"/> MEDIUM
	<input type="checkbox"/> BUMPY	<input type="checkbox"/> FAST
	<input type="checkbox"/> HIGH	

1ST	GEARING	2ND
<input type="checkbox"/> 13T	<input checked="" type="checkbox"/> 14T	<input type="checkbox"/> 17T
<input type="checkbox"/> 15T	<input type="checkbox"/> 16T	<input type="checkbox"/> 18T
<input type="checkbox"/> 17T	<input type="checkbox"/> 19T	<input type="checkbox"/> 20T
<input type="checkbox"/> 18T	<input type="checkbox"/> 21T	<input type="checkbox"/> 22T
SPUR GEARS		
<input type="checkbox"/> 48T	<input checked="" type="checkbox"/> 49T	<input type="checkbox"/> 50T
<input type="checkbox"/> STANDARD	<input checked="" type="checkbox"/> GRAPHITE	<input type="checkbox"/> 45T
<input type="checkbox"/> 46T	<input type="checkbox"/> 47T	<input type="checkbox"/> 48T

CLUTCH	
CLUTCH	STANDARD <input checked="" type="checkbox"/>
SHOE	Kit
	OTHER
	Kit
	SPRINGS TIGHTEN
	SPRING

FRONT	DIFFERENTIAL	REAR
Kit	CASE MATERIAL	Kit
300K	OIL	50K

FRONT	SHOCKS	REAR
Kit	SPRINGS	Kit
800	OIL	800
Cell soft	MEMBRANE	Cell soft
0	REBOUND	0
<input checked="" type="checkbox"/> 6 HOLES	PISTONS	<input checked="" type="checkbox"/> 6 HOLES
<input type="checkbox"/> 8 HOLES	1.1 mm	<input type="checkbox"/> 8 HOLES
<input type="checkbox"/> 10 HOLES	1.2 mm	<input type="checkbox"/> 10 HOLES
	1.3 mm	
	1.4 mm	
	OTHER PISTONS	

FRONT	ANTI-ROLL BAR	REAR
2.5	THICKNESS	2.8

FRONT	TIRES	REAR
TIRES TYPE:		
← COMPOUND →		
FR		
RR		

ENGINE	
TYPE	
MUFFLER	
MANIFOLD	
PLUG	
FUEL	

BODY TYPE	TOTAL WEIGHT
	/g

COMMENTS

FRONT	REAR
STEERING BLOCK	COMPOSITE <input checked="" type="checkbox"/>
ALU	ALU
C-HUB	COMPOSITE <input checked="" type="checkbox"/>
ALU	ALU
FRONT ARM	SOFT <input type="checkbox"/>
MEDIUM <input checked="" type="checkbox"/>	MEDIUM <input checked="" type="checkbox"/>
HARD <input type="checkbox"/>	HARD <input checked="" type="checkbox"/>
GRAPHITE <input type="checkbox"/>	GRAPHITE <input type="checkbox"/>
OFFSET	0 <input type="checkbox"/> +1 <input type="checkbox"/> +2 <input checked="" type="checkbox"/>
CASTER BUSHINGS	16° <input type="checkbox"/> 6° <input checked="" type="checkbox"/> 2° <input type="checkbox"/>
FRONT DROOP	MEASURE UNDER WHEEL AXLE #107717 GAUGE
UPPER SHOCK POSITION	UPRIGHT ROLL CENTER
REAR SHOCK PLATE POSITION	IN <input checked="" type="checkbox"/> OUT <input type="checkbox"/>
REAR SHOCK PLATE POSITION	LOWER ROLL CENTER
REAR DROOP	MEASURE UNDER WHEEL AXLE

FRONT	REAR
BUMP STEER SHIM /mm	WING HIGH /mm
STEERING BLOCK 0	GRAPHITE BRACE
STEERING PLATE 3	WITHOUT <input checked="" type="checkbox"/>
SHIMS PLACE ALWAYS UNDER	1-PIECE <input type="checkbox"/>
WHEELBASE SHIM POSITION	2-PIECES <input type="checkbox"/>
SHIMS BEHIND FRONT ARM	REAR DIFFUSOR
SHIMS IN FRONT OF REAR ARM	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
FF	RF
FR	RR
LOWER ROLL CENTER	REAR
ECCENTRIC BUSHINGS	

FRONT	REAR
1 FRONT TOE OUT	3 REAR TOE IN
TIGHTEN	SERVO SAVER MATERIAL
TIGHT <input type="checkbox"/>	MEDIUM <input type="checkbox"/>
MEDIUM <input checked="" type="checkbox"/>	GRAPHITE <input checked="" type="checkbox"/>
SOFT <input type="checkbox"/>	GRAPHITE <input type="checkbox"/>
UPPER PLATE	WHEELBASE
COMPOSITE <input checked="" type="checkbox"/>	0 mm 1 mm 2 mm 3 mm 4 mm
GRAPHITE <input checked="" type="checkbox"/>	SHIMS IN FRONT OF UPRIGHT
ENGINE MOUNT	
STANDARD <input checked="" type="checkbox"/>	
MONOBLOCK <input type="checkbox"/>	

FRONT	REAR
2 FRONT CAMBER	REAR CAMBER 2
REAR DIFF HEIGHT	UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>
LENGTH 22.3	LENGTH 22.3
RIDE HEIGHT 9	RIDE HEIGHT 10