

SET-UP SHEET

XB2'23 SET-UP SHEET VER. 1 ©XRAY 2022

XRAY XB2'23

RACE	Practice	
TRACK		
NAME	Max	DATE 2022-12-28

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION		FINAL POSITION	

TRACK			
SIZE	<input type="checkbox"/> OPEN	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> TIGHT
TRACTION			
SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY
TYPE	<input type="checkbox"/> CLAY	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASTRO
CONDITION	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> HARD PACKED	<input type="checkbox"/> DRY
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY	<input type="checkbox"/> WET

TRANSMISSION			
DIFFERENTIAL			
BALL DIFF	<input type="checkbox"/>	GEAR DIFF	<input type="checkbox"/>
		ACTIVE DIFF	<input checked="" type="checkbox"/>
	OIL 4k	cst	60° 90° 120°
SATELLITE GEARS	COMPOSITE	<input checked="" type="checkbox"/> STEEL	GEARS 2 <input checked="" type="checkbox"/> 4
SLIPPER	2 PAD	<input checked="" type="checkbox"/> 3 PAD	mm

GEARING	
PINION	23
SPUR GEAR	78

GEAR BOX	
FRONT LCG	<input checked="" type="checkbox"/>
REAR LCG	<input type="checkbox"/>

FRONT	SHOCKS	REAR
New 2dot	SPRINGS	New 2dot
cst 550	OIL	cst 500
<input checked="" type="checkbox"/> 2 HOLES	PISTONS	<input checked="" type="checkbox"/> 2 HOLES
<input type="checkbox"/> 3 HOLES	<input checked="" type="checkbox"/> ø1.6mm	<input type="checkbox"/> 3 HOLES
<input type="checkbox"/> 6 HOLES	<input type="checkbox"/> ø1.7mm	<input type="checkbox"/> 6 HOLES
	OTHER	
	ø mm 1.8 mm	
DOWNSTOP SHIM		DOWNSTOP SHIM
LENGTH 24 mm		LENGTH 30 mm
UPSTOP SHIM		UPSTOP SHIM
0 mm		3 mm
COLLAR STANDARD		COLLAR STANDARD
-2mm		-2mm
OTHER		OTHER
<input checked="" type="checkbox"/> KIT	BALL JOINT	<input checked="" type="checkbox"/> KIT

FRONT	SHOCK TOWER	REAR
ALU	<input checked="" type="checkbox"/> GRAPHITE	GRAPHITE
		ALU

FRONT	ANTI ROLL BAR	REAR
	THICKNESS	
	1,3 mm	

FRONT	TIRES	REAR
	BRAND	
	COMPOUND	
	INSERTS	
	WHEELS	

ELECTRONICS		
MOTOR	HW 6,5	HW G2S
MOTOR TIMING	30	Sunp. 3800
		BATTERY

BODY	
2CL	<input checked="" type="checkbox"/> LIGHT

COMMENT	

FRONT	APPLIED	APPLIED	REAR
STEERING BLOCK MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	LONGER BUSHINGS UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	SHIM 1 /mm	SHIM 2 /mm
CASTER BLOCK MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	FLAT ARM 2 1	SHIM 4 /mm	DRIVE SHAFT Length 75 /mm
LSM ARM 2 1	XB2D SUSP. ARM 1 2 3	SHIM 2 /mm	XB4 SUSP. ARM 1 2

FRONT	WING POSITION	SHOCK TOWER	WING CUTTING LINE / SIDE LINE	WING TYPE	WING POSITION
CASTER BUSHINGS 0° <input type="checkbox"/> 2.5° <input checked="" type="checkbox"/> 5° <input type="checkbox"/>	FRONT WING YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	<input checked="" type="checkbox"/> HIGHER <input type="checkbox"/> LOWER	SHOCK POSITION FRONT <input checked="" type="checkbox"/> REAR <input type="checkbox"/>	TEC CENTER FIN YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	UP <input type="checkbox"/> MIDDLE <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>
KICK-UP ° KIT 26° <input checked="" type="checkbox"/>	BUMP STEER SHIM 2 /mm				

FRONT TOE	EXTENSION	BATTERY PLACEMENT	REAR TOE	OFFSET	WHEELBASE	ROLL CENTER
0.5 °	0 SLOTS <input type="checkbox"/> 1 SLOT <input type="checkbox"/> 2 SLOTS <input checked="" type="checkbox"/> 3 SLOTS <input type="checkbox"/>	LONG SIDE FRONT <input type="checkbox"/> LONG SIDE REAR <input checked="" type="checkbox"/>	0.5 IN	6 /slots	SHIM 1 /mm	HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>
OFFSET 3 /slots	WHEELBASE SHIM 3 /mm	BATTERY SIZE STD. SHORT <input type="checkbox"/> LOW SHORT <input checked="" type="checkbox"/>	UPPER BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>			
ROLL CENTER HARD <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	SERVO HORNS SHIM 6 /mm	SERVO BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>				

STEERING ARMS	REAR ROLL CENTER HOLDERS
HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	RF 0.5° <input type="checkbox"/> 1° <input checked="" type="checkbox"/>
STEERING PLATE HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	RR 0.5° <input checked="" type="checkbox"/> 1° <input type="checkbox"/>

FRONT CAMBER	DIFF HEIGHT	REAR CAMBER
1,5 °	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	2 °
FRONT ARM MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	REAR ARM MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	
RIDE HEIGHT 14 /mm	RIDE HEIGHT 14 /mm	

ARM MOUNT	ECCENTRIC SHOCK BALL	ARM SHIM	CHASSIS	CHASSIS FLEX
COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/>	FRONT <input checked="" type="checkbox"/> REAR <input type="checkbox"/>	0 /mm	ALU MID (KIT) <input checked="" type="checkbox"/> ALU LONG <input type="checkbox"/> GRAPHITE MID <input type="checkbox"/>	<input checked="" type="checkbox"/> SCREW USED <input type="checkbox"/> SCREW NOT USED
CHASSIS BRACE MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	BALANCE 70 g			
SERVO WEIGHT STANDARD <input checked="" type="checkbox"/> LOW PROFILE <input type="checkbox"/>				