

SET-UP SHEET

VER.01 ©XRAY

XRAY X4'22

RACE	Pre Setup for HKRCSA Rd 3 at 08Jan2023		
TRACK	Trc		
NAME	Chan Ka lok Joey	DATE	20Dec2022

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME
			/sec	/	

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input checked="" type="checkbox"/> FAST

TRACTION	<input checked="" type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH
----------	---

FRONT	TRANSMISSION	REAR
SOLID AXLE	<input checked="" type="checkbox"/> YES	
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL 5000 /cSt
PINION 38 /T	SPUR GEAR 91 /T	FINAL DRIVE RATIO 4,55

FRONT	SHOCKS	REAR
Axon 2.7	XRAY SPRINGS	Axon 2.8
450	OIL /cSt	450
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input type="checkbox"/> 3 HOLES	<input type="checkbox"/> 1.0mm	<input type="checkbox"/> 3 HOLES
<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS

SHOCK LENGTH FRONT	9.5 /mm	SHOCK LENGTH REAR	9.5 /mm
--------------------	---------	-------------------	---------

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

Xpress 40S	TIRES	Xpress 40S
Red Spider	ADDITIVE	Red Spider
75C / 15mins	ADDITIVE TIMING	75C / 15mins

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT

TOTAL WEIGHT	1325 /g	WEIGHT BALANCE	FRONT 50 % REAR 50 %
--------------	---------	----------------	----------------------

MOTOR	HW 13.5	TIMING	
-------	---------	--------	--

ESC	HW Handout	BATTERIES	Coddar 150c
-----	------------	-----------	-------------

BODY	Brutale 0.5	WING	Std
------	-------------	------	-----

<p>Dimension from body post to window bottom line</p>	BODY POSITION
<p>Dimension from body post to upper holder</p>	WING SIDE PLATE YES <input type="checkbox"/> NO <input type="checkbox"/>
<p>Dimension from edge to surface</p>	

COMMENTS
 SpeeDome-RC chassis (wide type) , split top deck both
 Medium type.
 28g copper plate under Coddar 150C battery

FRONT CASTER	BUMP STEER	HEIGHT	SHIM	REAR CASTER	TOE GAIN
Adjust with eccentric bushings	4 /mm	19 /mm	/mm	Adjust with eccentric bushings	6 /mm
2 /mm FF	5.0 /mm	FR 2 /mm	<input type="checkbox"/> SERVO SAVER	2.5 /mm RF	5.4 /mm
<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> SERVO HORN		<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT

FRONT CAMBER	BODY STOP	FRONT SUSPENSION	FRONT HUB
2 /deg. Left=Right	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
	/mm	BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm <input type="checkbox"/> NO <input type="checkbox"/>	SHIM 0.5 /mm
		DRIVE SHAFT 58mm <input checked="" type="checkbox"/> 59mm <input type="checkbox"/> STD. BEARING <input checked="" type="checkbox"/>	
		#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5.4 /mm DOWNSTOP	

REAR CAMBER	BODY POST	REAR SUSPENSION	REAR HUB
2 /deg. Left=Right	VERTICAL <input checked="" type="checkbox"/> HORIZONTAL <input type="checkbox"/>	REAR BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
		BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm <input type="checkbox"/> NO <input type="checkbox"/>	SHIM /mm
		DRIVE SHAFT 52mm <input checked="" type="checkbox"/> 54mm <input type="checkbox"/> STD. BEARING <input checked="" type="checkbox"/>	
		#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4.8 /mm DOWNSTOP	

FRONT TOP VIEW	REAR TOP VIEW
TOE OUT 1 /deg. Left=Right	TOE IN 3 /deg. Left=Right
ACKERMANN SHIM 0 /mm	SHIM 2 /mm
DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>	DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>
UPPER ARM STANDARD <input checked="" type="checkbox"/>	UPPER ARM STANDARD <input checked="" type="checkbox"/>
STEERING BRIDGE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	TOP DECK FLEX NONE <input type="checkbox"/> BEARING <input type="checkbox"/>
TOP DECK STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm	TOP DECK 1.6mm <input type="checkbox"/> 2.0mm <input checked="" type="checkbox"/>
TOP DECK SPLITTED <input checked="" type="checkbox"/>	TOP DECK CUTTING <input type="checkbox"/>

FRONT BOTTOM VIEW	REAR BOTTOM VIEW
STEER. LOCK 25 /deg.	T-BRACE ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/>
STEER. SHIM SIZE 7 /mm	MOTOR MOUNT
FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	CHASSIS T-BRACE
FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>
STEER. PLATE STANDARD <input checked="" type="checkbox"/> +1mm <input type="checkbox"/>	CHASSIS GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input type="checkbox"/>