

# SET-UP SHEET

# XRAY XB4'23

RACE	EOS Daun	
TRACK	Daun	
NAME	Max	DATE

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION	12	FINAL POSITION	14

TRACK		
SIZE	<input type="checkbox"/> OPEN	<input checked="" type="checkbox"/> MEDIUM
TRACTION	<input type="checkbox"/> VERY-LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> VERY-HIGH	
SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM
TYPE	<input type="checkbox"/> CLAY	<input checked="" type="checkbox"/> CARPET
CONDITION	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> HARD PACKED
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY

DIFFERENTIAL TYPE		
FRONT ↓	MIDDLE ↓	REAR ↓
GEAR DIFF <input type="checkbox"/>	GEAR DIFF <input type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>
BALL DIFF <input type="checkbox"/>	SLIPPER <input checked="" type="checkbox"/>	BALL DIFF <input type="checkbox"/>
ACTIVE DIFF <input checked="" type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>
60° 90° 120°	60° 90° 120°	60° 90° 120°
OIL 20k cst	OIL cst	OIL 20k cst

SATELLITE GEARS		
COMPOSITE <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>
STEEL <input checked="" type="checkbox"/>	STEEL <input type="checkbox"/>	STEEL <input checked="" type="checkbox"/>
40T <input checked="" type="checkbox"/> 41T	CROWN GEAR	40T <input checked="" type="checkbox"/> 41T

CENTRAL SLIPPER & ONE-WAY SETTING	
	ONE-WAY TIGHTNESS
SLIPPING ADJUSTMENT	LOOSE
13 mm	1 CW TURN (BASIC SETUP)
	FULLY TIGHTEN

GEARING	
PINION 19 T	78 T CENTER DIFF SPUR

FRONT	SHOCKS	REAR
5dot	SPRINGS	4dot
cst 500	OIL	cst 375
% 0	REBOUND	% 0
<input type="checkbox"/> 2 HOLES <input checked="" type="checkbox"/> 3 HOLES <input type="checkbox"/> 6 HOLES	PISTONS <input type="checkbox"/> ø1.2mm <input type="checkbox"/> ø1.3mm <input checked="" type="checkbox"/> ø1.4mm <input type="checkbox"/> ø1.6mm <input checked="" type="checkbox"/> ø1.7mm CUSTOM PISTONS <input type="checkbox"/> +1 mm <input type="checkbox"/> +1 mm	<input type="checkbox"/> 2 HOLES <input checked="" type="checkbox"/> 3 HOLES <input type="checkbox"/> 6 HOLES

FRONT	ANTI ROLL BAR	REAR
2 mm	THICKNESS	2 mm

FRONT	TIRES	REAR
	BRAND	
	COMPOUND	
	INSERTS	
	WHEELS	

ELECTRONICS	
MOTOR 5,5	SPEEDO
MOTOR TIMING	3800Sunpadow BATTERY
BATTERY SIZE	
STD. SHORT	<input checked="" type="checkbox"/> LOW SHORT

BODY	
TYPE	Carpet
	STANDARD <input type="checkbox"/> LIGHT <input checked="" type="checkbox"/>

COMMENTS	

FRONT	APPLIED <input type="radio"/> <input checked="" type="checkbox"/> APPLIED	REAR
ALU C-HUB SHIM UP 2 /mm DOWN /mm LONGER BUSHINGS UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> DRIVE SHAFT CVD <input type="checkbox"/> ECS <input checked="" type="checkbox"/> Length 83 /mm SHIM 0 mm ALU <input checked="" type="checkbox"/> STEERING BLOCK MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> LOWER SHOCK POSITION #107711 GAUGE DOWNSTOP mm	REAR UPRIGHT DRIVE SHAFT Length 77 /mm SHIM mm SHIMS 2 /mm HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU HIGH <input checked="" type="checkbox"/> ALU LOW <input type="checkbox"/> #325341 ADJ. DRIVE AXLE 1 2 3 4 #107711 GAUGE DOWNSTOP mm 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>	

FRONT	CASTER	CASTER BLOCK	WING CUTTING LINE	WING SIDE LINE
CASTER 6° <input type="checkbox"/> 7° <input checked="" type="checkbox"/> 9° <input type="checkbox"/> 12° <input type="checkbox"/> OFFSET 2 /slots BUMP STEER SHIM 2 mm	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	1 2 3 4 5 OFFSET 4 /slots UPRIGHT WHEELBASE SHIM 2 /mm IN FRONT OF ARM	HIGHER <input type="checkbox"/> LOWER <input checked="" type="checkbox"/> WING POSITION UP <input checked="" type="checkbox"/> MIDDLE <input type="checkbox"/> DOWN <input type="checkbox"/> WING THICKNESS 0.75 <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 1.5 TYPE TEC	

FF	FR	ROLL CENTER	RF	RR 2°
<input checked="" type="checkbox"/> 1° <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/> 1° <input type="checkbox"/> 0.5°	<input checked="" type="checkbox"/> 1° <input type="checkbox"/> 0.5°	ECCENTRIC BUSHINGS <input checked="" type="checkbox"/> 1° <input type="checkbox"/> 0.5°	UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>	<input checked="" type="checkbox"/> 2°

FRONT TOE	STEER. PLATE	REAR TOE	GRAPHITE FOR REAR BRACE	REAR BRACE	ARM SHIM
1	HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> BUMP STEER SHIM 2 mm SHIM UNDER STEER. PLATE SERVO SAVER SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/> TIGHT <input checked="" type="checkbox"/> MATERIAL STANDARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	1	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	2 mm

FRONT CAMBER	FRONT DIFF HEIGHT	REAR DIFF HEIGHT	REAR CAMBER
1.5°	DOWNSTOP SHIM 3 mm LENGTH 20 mm UPSTOP SHIM 0 mm	DOWNSTOP SHIM 2 mm LENGTH 27.3 mm UPSTOP SHIM 0 mm	2
COLLAR	FRONT	REAR	COLLAR
STANDARD <input type="checkbox"/> -2mm	RIDE HEIGHT 13 mm #107720 GAUGE	RIDE HEIGHT 13 mm #107720 GAUGE	STANDARD <input type="checkbox"/> -2mm

FRONT ARMS	BALANCE	MOTOR MOUNT	BALANCE	REAR ARMS
LONG <input type="checkbox"/> SHORT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	g	FRONT <input checked="" type="checkbox"/> REAR <input type="checkbox"/>	g	LONG <input type="checkbox"/> SHORT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>
CHASSIS ALU <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>				
SIDE GUARDS HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>				