

**XRAY X4'23**

### FRONT & REAR SUSPENSION

#### FRONT CASTER

Adjust with eccentric bushings

5° ☐ 4° ☒ 3° ☐

UPPER CLAMP STD. ☒ ☐ -1.5mm

#### REAR CASTER

Adjust with eccentric bushings

0.5° ☐ 1.5° ☒ 2.5° ☐ 3.5° ☐ 4.5° ☐ 5.5° ☐

UPPER CLAMP STD. ☒ ☐ -1.5mm

BUMP STEER 3 /mm

HEIGHT /mm

SHIM 4 /mm

TOE GAIN 5.5 /mm

2 /mm RF

5.2 /mm RR

2 /mm FF

5.0 /mm

FR 2 /mm

☒ SERVO SAVER

☐ SERVO HORN

☒ RIDE HEIGHT

☐ RIDE HEIGHT

#### FRONT SUSPENSION

-1.5 /degr. CAMBER Left=Right

BODY STOP YES ☐ NO ☒ /mm

FRONT BRACE YES ☐ NO ☒

BULKHEAD SHIMS YES ☒ 3mm ☐ NO

FRONT SHOCK POSITION 1 2

SHIM 2 /mm

FRONT HUB HARD ☐ GRAPHITE ☒ ALU ☐

SHIM 1 /mm

DRIVE SHAFT ☒ 58mm ☐ 59mm ☒ BEARING ☐ BLADE

#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5.8 /mm DOWNSTOP

#### REAR SUSPENSION

-1.5 /degr. CAMBER Left=Right

BODY POST VERTICAL ☐ HORIZONTAL ☒

SHIM 2 /mm

REAR SHOCK POSITION 1 2

SHIM 2 /mm

REAR HUB HARD ☐ GRAPHITE ☒ ALU ☐

SHIM 1 /mm

DRIVE SHAFT ☐ 52mm ☒ 54mm ☒ BEARING ☐ BLADE

#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5.4 /mm DOWNSTOP

#### FRONT TOP VIEW

1 TOE OUT Left=Right

ACKERMANN SHIM 0.5 /mm

DIFF POSITION UP ☐ DOWN ☒

UPPER ARM SOFT ☐ MEDIUM STD. ☒

HUB OFFSET STD. ☒ -0.5mm ☐ +0.5mm SHIM/mm

STEERING BRIDGE YES ☐ NO ☒

STEERING PLATE 8.0mm ☒ STD. ☐ 7.5mm ☐

#### REAR TOP VIEW

2.5 TOE IN Left=Right

SHIM /mm

DIFF POSITION UP ☐ DOWN ☒

UPPER ARM SOFT ☐ MEDIUM STD. ☒

HUB OFFSET STD. ☒ -0.5mm ☐ +0.5mm SHIM/mm

#### FRONT BOTTOM VIEW

STEER. LOCK 25 /degr.

STEER. SHIM SIZE /mm

FRONT BRACE YES ☐ NO ☒

FRONT ARMS MEDIUM ☐ HARD ☒

#### REAR BOTTOM VIEW

T-BRACE ALU ☐ BRASS ☐

CHASSIS GRAPHITE ☐ ALU ☒ ALU FLEX ☐

REAR ARMS MEDIUM ☐ HARD ☒