

SET-UP SHEET

X4'23 SET-UP SHEET VER.1 ©XRAY

XRAY X4'23

RACE	ROAR Paved Nats 17.5			
TRACK	Coral Springs			
NAME	Mike Gee	DATE	5/28/23	

QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME
3	1	12.8 /sec	/	

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input checked="" type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL 5000 /cSt
PINION	SPUR GEAR	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
400	OIL /cSt	400
-	REBOUND %	-
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH	9 /mm	9 /mm	SHOCK LENGTH

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

Sweep D36	TIRES	
MG Yellow	ADDITIVE	Clean w/ buggy grip
10 mins	ADDITIVE TIMING	Heat 60C

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT	1330 /g	WEIGHT BALANCE	FRONT 50 % REAR 50 %
--------------	---------	----------------	----------------------

MOTOR	17.5	TIMING	
ESC	Orca OE1	BATTERIES	PCR 6600 (285g)
BODY	Speciale UL	WING	Speciale UL

BS 41 /mm	Dimension from body post to window bottom line	BODY POSITION
7 + 1 /mm	Dimension from body post to upper holder	WING SIDE PLATE
	Dimension from edge to surface	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>

X4'23	<input checked="" type="checkbox"/>	1.6mm	<input checked="" type="checkbox"/>	2.0mm	<input checked="" type="checkbox"/>	1.6mm
X4'22	<input type="checkbox"/>	2.0mm	<input type="checkbox"/>	2.0mm	<input type="checkbox"/>	1.6mm
X4'22	<input type="checkbox"/>	NONE	<input type="checkbox"/>	BEARING	<input type="checkbox"/>	

5g in front and behind motor mount
Battery forward

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
Adjust with eccentric bushings	BUMP STEER 2.5 /mm	Adjust with eccentric bushings
UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm	HEIGHT 18 /mm	UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm
SHIM 6 /mm	SERVO SAVER	SHIM 6 /mm
3 /mm FF	SERVO HORN	TOE GAIN 5.5 /mm
5.2 /mm		3.5 /mm RF
FR 3 /mm		5.4 /mm
		RR 3.5 /mm

2 /deg. CAMBER	FRONT SUSPENSION	FRONT HUB
Left = Right	FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	HARD <input type="checkbox"/>
BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	FRONT SHOCK POSITION	GRAPHITE <input checked="" type="checkbox"/>
	BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm NO <input type="checkbox"/>	ALU <input type="checkbox"/>
DRIVE SHAFT 58mm 59mm BEARING BLADE	HUBDY	SHIM 0.5 /mm
#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	DOWNSTOP 5.8 /mm

2 /deg. CAMBER	REAR SUSPENSION	REAR HUB
Left = Right	REAR BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	HARD <input type="checkbox"/>
BODY POST VERTICAL <input type="checkbox"/> HORIZONTAL <input type="checkbox"/>	REAR SHOCK POSITION	GRAPHITE <input checked="" type="checkbox"/>
		ALU <input type="checkbox"/>
DRIVE SHAFT 52mm 54mm BEARING BLADE	HUBDY	SHIM 0.5 /mm
#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	DOWNSTOP 4.8 /mm

1 TOE OUT	FRONT TOP VIEW	REAR	2.75 TOE IN
Left = Right	ACKERMANN SHIM 1 /mm	SHIM /mm	Left = Right
DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>	BRASS WEIGHT FOR MOTOR MOUNT		DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN
UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM STD. <input type="checkbox"/>	STEERING BRIDGE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	STEERING PLATE 8.0mm <input checked="" type="checkbox"/> STD. <input type="checkbox"/> 7.5mm	UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM STD. <input type="checkbox"/>
HUB OFFSET STD. <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> +0.5mm SHIM/mm		HUB OFFSET STD. <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> +0.5mm SHIM/mm	

FRONT BOTTOM VIEW	REAR
STEER. LOCK 25 /deg.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
STEER. SHIM SIZE Std /mm	MOTOR MOUNT
FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	CHASSIS GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input type="checkbox"/>
SERVO HOLDER	REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>