

# SET-UP SHEET

X4'23 SET-UP SHEET VER.1 ©XRAY

# XRAY X4'23

RACE	Final Setup For HKRCSA Rd 2		
TRACK	TRC		
NAME	Chan Ka Lok Joey	DATE	31Jul2023

QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
P2	A2	16.427 /sec	18	5:01.387

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL 5000 /cSt
PINION 38 /T	SPUR GEAR 91 /T	FINAL DRIVE RATIO 4.55

FRONT	SHOCKS	REAR
2.7	XRAY SPRINGS	2.7
400	OIL /cSt	400
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH 8.5 /mm			SHOCK LENGTH 9 /mm

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

Solaris 40J	TIRES	Solaris 40J
V3 Black	ADDITIVE	V3 Black
65c / 10Mins	ADDITIVE TIMING	65c / 10Mins

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT 1320 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
----------------------	----------------	------------	-----------

MOTOR	Orca 13.5t Handout	TIMING	
ESC	Orca Totem Handout	BATTERIES	Coddar 6600mah
BODY	LensBodies Ghibli 0.5	WING	Std

	Dimension from body post to window bottom line	BODY POSITION
	Dimension from body post to upper holder	WING SIDE PLATE
	Dimension from edge to surface	

X4'23	<input checked="" type="checkbox"/> 1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input type="checkbox"/> 1.6mm
X4'22	<input type="checkbox"/> 2.0mm	<input type="checkbox"/> 2.0mm	<input type="checkbox"/> 1.6mm
X4'22	<input type="checkbox"/> 2.0mm	<input type="checkbox"/> 1.6mm	<input type="checkbox"/> NONE
			<input type="checkbox"/> BEARING

COMMENTS
Speedome-RC New Chassis Rear +1 type . Speedome-RC New split topdeck (soft at Front ,Medium at rear). 5g beside servo ,under front belt .

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
Adjust with eccentric bushings		Adjust with eccentric bushings
UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm		UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm
2.5 /mm FF	5.2 /mm	FR 2.5 /mm
<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> SERVO SAVER	<input checked="" type="checkbox"/> SERVO HORN
		TOE GAIN 6 /mm
		3 /mm RF
		5.4 /mm
		RR 3 /mm
		<input checked="" type="checkbox"/> RIDE HEIGHT

2 /deg. CAMBER	Left = Right	BODY STOP YES <input checked="" type="checkbox"/> NO
		FRONT SUSPENSION
		FRONT BRACE YES <input checked="" type="checkbox"/> NO
		FRONT SHOCK POSITION
		BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm NO
		DRIVE SHAFT 58mm 59mm BEARING BLADE
		#107702 Chassis Droop Gauge Blocks
		#107712 Chassis Droop Gauge
		5.4 /mm DOWNSTOP

2 /deg. CAMBER	Left = Right	BODY POST VERTICAL <input checked="" type="checkbox"/> HORIZONTAL
		REAR SUSPENSION
		1.5 /mm SHIM 3 /mm
		REAR SHOCK POSITION
		REAR HUB HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
		SHIM 0.5 /mm
		DRIVE SHAFT 52mm 54mm BEARING BLADE
		#107702 Chassis Droop Gauge Blocks
		#107712 Chassis Droop Gauge
		4.6 /mm DOWNSTOP

FRONT TOP VIEW	REAR
1 TOE OUT Left = Right	3 TOE IN Left = Right
ACKERMANN SHIM 0 /mm	SHIM 2 /mm
DIFF POSITION UP <input checked="" type="checkbox"/> DOWN	DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN
UPPER ARM SOFT <input type="checkbox"/> MEDIUM STD. <input checked="" type="checkbox"/>	UPPER ARM SOFT <input type="checkbox"/> MEDIUM STD. <input checked="" type="checkbox"/>
STEERING BRIDGE YES <input type="checkbox"/> NO	STEERING PLATE 8.0mm <input checked="" type="checkbox"/> STD. 7.5mm
HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm	HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK 26 /deg.	T-BRACE ALU <input checked="" type="checkbox"/> BRASS
STEER. SHIM SIZE 7.5 /mm	MOTOR MOUNT
FRONT BRACE YES <input checked="" type="checkbox"/> NO	CHASSIS T-BRACE
FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD	CHASSIS GRAPHITE <input checked="" type="checkbox"/> ALU ALU FLEX
	REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD