

# SET-UP SHEET

VER.01 ©XRAY

# XRAY X4F'23

RACE	Dutch Nationals Round 6		
TRACK	M.A.C. De Baanbrekers		
NAME	Patrick Jongenelis	DATE	01-10-2023

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
23-36	1	1	19.158 /sec	22	7:12.840

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input checked="" type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH
FRONT	TRANSMISSION
GEAR DIFFERENTIAL - OIL	200K /cst

PINION / T	SPUR GEAR / T	FINAL DRIVE RATIO
43	91	4.02

FRONT	SHOCKS	REAR
2.8	XRAY SPRINGS	2.6
350	OIL /cst	350
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
<input type="checkbox"/> 3 HOLES <input type="checkbox"/> 4 HOLES <input checked="" type="checkbox"/> PSS	PISTONS 1.0mm <input type="checkbox"/> 1.1mm <input checked="" type="checkbox"/> 1.2mm <input type="checkbox"/>	<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS
SHOCK LENGTH FRONT		SHOCK LENGTH REAR
8.5 /mm		9 /mm

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.5
Ride ETS	TIRES	Ride ETS		
CS High grip	ADDITIVE	CS High grip		
15 Min	ADDITIVE TIMING	15 Min		

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT	1300 /g	WEIGHT BALANCE	FRONT 61 % REAR 39 %
--------------	---------	----------------	----------------------

MOTOR	HW 17.5T ETS	TIMING	
-------	--------------	--------	--

ESC	HW Juststock XR10	BATTERIES	LRP 4600
-----	-------------------	-----------	----------

BODY	Speed 3	WING	STD
------	---------	------	-----

<p>Dimension from body post to window bottom line</p> <p>WING SIDE PLATE YES <input type="checkbox"/> NO <input type="checkbox"/></p> <p>Dimension from body post to upper holder</p> <p>Dimension from edge to surface</p>	BODY POSITION
---	---------------

COMMENTS

All HUDY oils.

Preheat 20 mins.

FRONT CASTER		FRONT & REAR SUSPENSION		REAR CASTER	
<input checked="" type="checkbox"/> 5°	<input type="checkbox"/> 4°	BUMP STEER	HEIGHT	<input checked="" type="checkbox"/> 0.5°	<input type="checkbox"/> 1.5°
Adjust with eccentric bushings		2.5 /mm	19 /mm	Adjust with eccentric bushings	
		SHIM			
		7.5 /mm			
		TOE GAIN			
		8 /mm			
		2 /mm FF	5.6 /mm FR		
		2 /mm	2 /mm		
		<input type="checkbox"/> SERVO SAVER	<input checked="" type="checkbox"/> SERVO HORN		
		2 /mm RF	6 /mm RR		
		2 /mm	2 /mm		
		<input type="checkbox"/> SERVO SAVER	<input checked="" type="checkbox"/> SERVO HORN		
		2 /mm	2 /mm		
		<input type="checkbox"/> SERVO SAVER	<input checked="" type="checkbox"/> SERVO HORN		

FRONT CAMBER		BODY STOP		FRONT SUSPENSION		FRONT HUB	
2 /deg.	Left=Right	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	/mm	2 /mm SHIM	2 /mm	COMPOSITE <input checked="" type="checkbox"/>	ALU <input type="checkbox"/>
		FRONT BRACE		FRONT SHOCK POSITION			
		YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>		1 2 3 4			
		BULKHEAD SHIMS		SHIM			
		YES <input checked="" type="checkbox"/> 3mm	NO <input type="checkbox"/>	0.5 /mm			
		DRIVE SHAFT		HUDY			
		58mm 59mm	STD. BEARING	0 1 2 3 4 5 6 7 8 9 10			
		#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	5.6 /mm	DOWNSTOP		

REAR CAMBER		REAR SUSPENSION		REAR HUB	
2 /deg.	Left=Right	1 /mm SHIM	2 /mm	COMPOSITE <input type="checkbox"/>	ALU <input type="checkbox"/>
		REAR SHOCK POSITION			
		1 2 3 4			
		SHIM			
		1.5 /mm			
		HUDY			
		0 1 2 3 4 5 6 7 8 9 10			
		#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	4.6 /mm	DOWNSTOP

FRONT TOP VIEW		REAR TOP VIEW	
1 TOE OUT	Left=Right	1.8 TOE IN	Left=Right
ACKERMANN			
SHIM 0 /mm			
DIFF POSITION			
UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>			
UPPER ARM			
STANDARD <input checked="" type="checkbox"/>			
STEERING BRIDGE			
YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>			
OFFSET			
STANDARD <input type="checkbox"/>			
-0.5mm <input checked="" type="checkbox"/>			
SHIM/mm			
TOP DECK			
SPLITTED			
TOP DECK FLEX			
TOP DECK CUTTING			
UPPER ARM			
STANDARD <input checked="" type="checkbox"/>			
OFFSET			
STANDARD <input type="checkbox"/>			
-0.5mm <input checked="" type="checkbox"/>			
SHIM/mm			

FRONT BOTTOM VIEW		REAR BOTTOM VIEW	
STEER. LOCK	26 /deg.	T-BRACE	ALU <input checked="" type="checkbox"/>
STEER. SHIM	SIZE /mm	BRASS <input type="checkbox"/>	
FRONT BRACE	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	MOTOR MOUNT	
FRONT ARMS	MEDIUM <input checked="" type="checkbox"/>	CHASSIS T-BRACE	
HARD <input type="checkbox"/>		CHASSIS	GRAPHITE <input checked="" type="checkbox"/>
STEER. PLATE	STANDARD <input checked="" type="checkbox"/>	REAR ARMS	MEDIUM <input checked="" type="checkbox"/>
		HARD <input type="checkbox"/>	