# SET-UP SHEET

# XRAY XB4'23

| | |
|---|---|
| RACE | CZMS R1 |
| TRACK | CZMS |
| NAME | Max |
| DATE | 4.11.2023 |

| | | | |
|---|---|---|---|
| LAPS | | BEST LAP TIME | sec |
| QUALIFYING POSITION | 1 | FINAL POSITION | 1 |

## TRACK

| | | | |
|---|---|---|---|
| SIZE | ☐ OPEN | ☐ MEDIUM | ☒ TIGHT |
| TRACTION | ☐ ☐ ☐ ☐ ☐ ☐ ☒ ☐ ☐ | | |
| | VERY-LOW | MEDIUM | VERY-HIGH |
| SURFACE | ☐ SMOOTH | ☐ MEDIUM | ☐ BUMPY |
| TYPE | ☐ CLAY | ☒ CARPET | ☐ ASTRO |
| CONDITION | ☐ BLUE GROOVE | ☐ HARD PACKED | ☐ DRY |
| | ☐ DUSTY | ☐ LOAMY | ☐ WET |

## DIFFERENTIAL TYPE

| FRONT | MIDDLE | REAR |
|---|---|---|
| ☒ GEAR DIFF | ☐ GEAR DIFF | ☒ GEAR DIFF |
| ☐ BALL DIFF | ☒ SLIPPER | ☐ BALL DIFF |
| ☐ ACTIVE DIFF | ☐ ACTIVE DIFF | ☐ ACTIVE DIFF |
| 60° 90° 120° | 60° 90° 120° | 60° 90° 120° |
| OIL 15k cSt | OIL cSt | OIL 10k cSt |

### SATELLITE GEARS

| | | |
|---|---|---|
| ☐ COMPOSITE ☒ STEEL | ☐ COMPOSITE ☐ STEEL | ☐ COMPOSITE ☒ STEEL |
| ☒ 40T ☐ 41T | CROWN GEAR | ☒ 40T ☐ 41T |

## CENTRAL SLIPPER & ONE-WAY SETTING




## GEARING

| | | | |
|---|---|---|---|
| PINION | 18 T | 81 T | CENTER DIFF SPUR |

| FRONT | SHOCKS | REAR |
|---|---|---|
| 5 | SPRINGS | 4 |
| 400 cSt | OIL | 300 cSt |
| % | REBOUND | % |
| ☒ 2 HOLES | PISTONS | ☐ 2 HOLES ☒ |
| ☐ 3 HOLES | ☐ ø1.2mm ☐ ø1.3mm ☐ ø1.4mm ☒ ø1.6mm ☐ ø1.7mm | ☐ 3 HOLES |
| ☐ 6 HOLES | CUSTOM PISTONS | ☐ 6 HOLES |
| HOLES | ø mm ø 1,8 mm | HOLES |

| FRONT | ANTI ROLL BAR | REAR |
|---|---|---|
| 2 mm | THICKNESS | 2 mm |

| FRONT | TIRES | REAR |
|---|---|---|
| sch Fusion2 | BRAND | sch cactus |
| | COMPOUND | |
| | INSERTS | |
| XRAY HARD | WHEELS | XRAY HARD |

## ELECTRONICS

| | | | |
|---|---|---|---|
| MOTOR | 4,5T | Nitride | SPEEDO |
| MOTOR TIMING | 30 | LCG | BATTERY |

BATTERY SIZE: ☐ STD. SHORT ☒ LOW SHORT

## BODY

| | | | |
|---|---|---|---|
| TYPE | Gamma 4DL | STANDARD ☐ | ☒ LIGHT |

## COMMENTS