

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	Club RCCA				
TRACK	RCCA				
NAME	Chris Adams		DATE		
QUAL POSITION	1	FINAL POSITION	1	BEST LAPTIME	10.0 /sec
LAPS	/				

TRACK		
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL 8000 /cSt
PINION 29 /T	SPUR GEAR 110 /T	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
550	OIL /cSt	550
25	REBOUND %	25
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm	<input checked="" type="checkbox"/> PSS	<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm
SHOCK LENGTH 8.5 /mm		

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
gravity		TIRES		
sxt		ADDITIVE		
15		ADDITIVE TIMING		
		WIPE OFF TIME		
Timing:		Temp.:		
FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT	
TREATED AREA				

TOTAL WEIGHT	1322 /g	WEIGHT BALANCE	FRONT 50 % REAR 50 %
MOTOR	5.5	TIMING	30
ESC	hw	BATTERIES	ea 4200
BODY	twister	WING	speciale

67.5 /mm	Dimension from body post to window bottom line	BODY POSITION
7 +2 small oring	Dimension from body post to upper holder	WING SIDE PLATE
64 /mm	Dimension from edge to surface	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>

X4'23	1.6mm <input checked="" type="checkbox"/> 2.0mm <input type="checkbox"/> 1.6mm
X4'22	2.0mm <input type="checkbox"/> 1.6mm
X4'22	2.0mm <input type="checkbox"/> 1.6mm
NONE <input type="checkbox"/> BEARING <input type="checkbox"/>	

20g under rear belt, 15 g in front of motor mount

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
Adjust with eccentric bushings	BUMP STEER 2 /mm	Adjust with eccentric bushings
HEIGHT /mm	SHIM /mm	TOE GAIN 1.0 /mm
2 /mm FF	5.0 /mm FR	2.5 /mm RF
RIDE HEIGHT	2 /mm RR	5.2 /mm
<input checked="" type="checkbox"/> SERVO SAVER	<input checked="" type="checkbox"/> SERVO HORN	

FRONT	SHOCK HOLDERS	SHIM	FRONT HUB
-2.1 /deg. CAMBER	SHIM 4 /mm	2.5 /mm	MEDIUM <input type="checkbox"/>
Left = Right	SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	2 /mm	HARD <input type="checkbox"/>
BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	DRIVE SHAFT 58mm <input checked="" type="checkbox"/> 59mm <input type="checkbox"/>	SHIM .5 /mm	GRAPHITE <input checked="" type="checkbox"/>
BEARING BLADE	#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	ALU <input type="checkbox"/>
		5.6 /mm	DOWNSTOP

REAR	SHOCK HOLDERS	SHIM	REAR HUB
-2 /deg. CAMBER	SHIM 4 /mm	2 /mm	MEDIUM <input type="checkbox"/>
Left = Right	SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	2 /mm	HARD <input type="checkbox"/>
BODY POST VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>	DRIVE SHAFT 52mm <input checked="" type="checkbox"/> 54mm <input type="checkbox"/>	SHIM 1 /mm	GRAPHITE <input checked="" type="checkbox"/>
BEARING BLADE	#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	ALU <input type="checkbox"/>
		4.2 /mm	DOWNSTOP

FRONT TOP VIEW	REAR TOP VIEW
TOE OUT .8	TOE IN 2.8
Left = Right	Left = Right
ACKERMANN SHIM 1 /mm	SHORT LiPo BRASS WEIGHT YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm	BRASS WEIGHT FOR MOTOR MOUNT 10 40g 11 40g
UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>	SHIM 0 /mm
STEERING BRIDGE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	STEERING SHIM /mm
HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm	PLATE 8.0mm 7.5mm STD. <input checked="" type="checkbox"/>

FRONT BOTTOM VIEW	REAR BOTTOM VIEW
STEER. LOCK 26 /deg.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
SERVO HOLDER	CHASSIS T-BRACE
MOTOR MOUNT	FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>
CHASSIS GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU 1.5mm <input type="checkbox"/>	REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>