

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	Xrs Rd 3				
TRACK	Hudy Arena				
NAME	Jan Gehrig		DATE	16.12.23	
QUAL POSITION	5	FINAL POSITION	4	BEST LAPTIME	13,2 /sec
LAPS	/				

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL
PINION	38 /T	SPUR GEAR
	100 /T	FINAL DRIVE RATIO
		5

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.6
425	OIL /Cst	425
20	REBOUND %	20
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm	<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm	<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm
<input checked="" type="checkbox"/> PSS	<input checked="" type="checkbox"/> PSS	<input checked="" type="checkbox"/> PSS
0.8		0.8
SHOCK LENGTH	8.5 /mm	SHOCK LENGTH
	8.5 /mm	
1.3	THICKNESS/mm	1.2

Hudy 28	TIRES	
Hudy red	ADDITIVE	
15	ADDITIVE TIMING	
	WIPE OFF TIME	
	TIRE WARMERS	
Timing:	Temp.:	
FRONT LEFT	FRONT RIGHT	
REAR LEFT	REAR RIGHT	
TREATED AREA		

TOTAL WEIGHT	1300 /g	WEIGHT BALANCE	FRONT 50 % REAR 50 %
--------------	---------	----------------	----------------------

MOTOR	Hobbywing justock 13.5	TIMING	
ESC	Hobbywing xr10 stock	BATTERIES	LRP 5100
BODY	Wolverine	WING	Twister

65 /mm	Dimension from body post to window bottom line	BODY POSITION
27	Dimension from body post to upper holder	WING SIDE PLATE
	Dimension from edge to surface	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
1.6mm <input type="checkbox"/> 2.0mm <input checked="" type="checkbox"/> 1.6mm		
X4'23		
X4'22		
X4'22		
NONE <input type="checkbox"/> BEARING <input type="checkbox"/>		

Front tire round edge completely glued to the top

FRONT & REAR	SUSPENSION
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER	SHIM
3 /mm	6 /mm
HEIGHT	SHIM
17 /mm	6 /mm
2 /mm FF	TOE GAIN
5 /mm	1.5 /mm
FR 2 /mm	2.5 /mm RF
<input type="checkbox"/> SERVO SAVER	5.2 /mm
<input checked="" type="checkbox"/> SERVO HORN	RR 2.5 /mm

FRONT	SHOCK HOLDERS	SHIM	SHOCK LENGTH	SHOCK LENGTH
1 /deg. CAMBER	SHIM 4 /mm	3 /mm	2 /mm	
Left = Right	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>			
13 /mm				
DRIVE SHAFT	SUSPENSION FLEX			
58mm 59mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>			
BEARING BLADE	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>			

REAR	SHOCK HOLDERS	SHIM	SHOCK LENGTH	SHOCK LENGTH
1,5 /deg. CAMBER	SHIM 4 /mm	2 /mm	2 /mm	
Left = Right	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>			
4 /mm				
DRIVE SHAFT	SUSPENSION FLEX			
52mm 54mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>			
BEARING BLADE	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>			

FRONT TOP VIEW	REAR
TOE OUT	TOE IN
Left = Right	Left = Right
10	20
ACKERMANN	SHIM 0.5 /mm
SHIM 0.5 /mm	
SHORT LiPo BRASS WEIGHT	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	
BRASS WEIGHT FOR MOTOR MOUNT	40g
40g	
DIFF POSITION	DIFF POSITION
UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> +1mm	UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> +1mm
UPPER ARM	UPPER ARM
SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/>	SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/>
STEERING BRIDGE	STEERING
YES <input type="checkbox"/> NO <input type="checkbox"/>	SHIM /mm
	7.5
HUB OFFSET	PLATE
STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm 1	8.0mm 7.5mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK	T-BRACE
21 /deg.	ALU BRASS
MOTOR MOUNT	CHASSIS T-BRACE
SERVO HOLDER	
FRONT ARMS	REAR ARMS
MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>