

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	Snowbird Nationals 2024				
TRACK	Wyndham Resort				
NAME	Alexander Hagberg		DATE	04/02/2024	
QUAL POSITION	3	FINAL POSITION	3	BEST LAPTIME	9.4 /sec
LAPS	/				

TRACK		
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM
	<input type="checkbox"/> FAST	<input type="checkbox"/> HIGH

FRONT		TRANSMISSION		REAR	
GEAR DIFF OIL	/cSt	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL	7000	/cSt
PINION	28 /T	SPUR GEAR	110 /T	FINAL DRIVE RATIO	

FRONT		SHOCKS		REAR	
2.4-2.7		XRAY SPRINGS		2.6	
375		OIL /cSt		375	
0		REBOUND %		0	
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		FOAM INSERTS		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm
SHOCK LENGTH		8.5 /mm	SHOCK LENGTH	
1.2		THICKNESS/mm	1.2	

Jaco Blue	TIRES	Jaco Blue
HUDY Red	ADDITIVE	HUDY Red
8	ADDITIVE TIMING	8
2	WIPE OFF TIME	2
Timing:	Temp.:	Timing:
FRONT LEFT	FRONT RIGHT	REAR LEFT
REAR RIGHT	TREATED AREA	

TOTAL WEIGHT	1320 /g	WEIGHT BALANCE	FRONT 50 % REAR 50 %
--------------	---------	----------------	----------------------

MOTOR	HW G3 5.0T	TIMING	35
ESC	HW XR10 PRO G2S	BATTERIES	Nosram 4200
BODY	Speciale UL	WING	Speciale L

67 /mm	Dimension from body post to window bottom line	BODY POSITION
8th hole, 0	Dimension from body post to upper holder	WING SIDE PLATE
64.5 /mm	Dimension from edge to surface	

1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm
2.0mm	<input type="checkbox"/> 1.6mm	<input type="checkbox"/> 2.0mm
NONE	<input type="checkbox"/> BEARING	

2x HUDY 293011 used underneath battery pack. Tires cleaned with sauce.

FRONT & REAR SUSPENSION	
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER	SHIM
2.0 /mm	1.5 /mm
HEIGHT	TOE GAIN
19 /mm	1.0 /mm
SHIM	SHIM
3.0 /mm	3.0 /mm
FRIDE HEIGHT	FRIDE HEIGHT
5.2 /mm	5.4 /mm
FR 3.0 /mm	RR 3.0 /mm
<input checked="" type="checkbox"/> SERVO SAVER	<input checked="" type="checkbox"/> SERVO HORN

FRONT	
2.0 /mm	CAMBER
Left = Right	
SHOCK HOLDERS	SHIM
6.0 /mm	
SUSPENSION FLEX	YES <input checked="" type="checkbox"/> NO
DRIVE SHAFT	BEARING BLADE
58mm 59mm	
FRONT HUB	SHIM
MEDIUM <input type="checkbox"/>	0.5 /mm
HARD <input type="checkbox"/>	
GRAPHITE <input checked="" type="checkbox"/>	
ALU <input type="checkbox"/>	
SHOCK LENGTH	8.5 /mm
ANTI-ROLL BAR	THICKNESS/mm
1.2	

REAR	
2.0 /mm	CAMBER
Left = Right	
SHOCK HOLDERS	SHIM
6.0 /mm	
SUSPENSION FLEX	YES <input checked="" type="checkbox"/> NO
DRIVE SHAFT	BEARING BLADE
52mm 54mm	
REAR HUB	SHIM
MEDIUM <input type="checkbox"/>	1.5 /mm
HARD <input type="checkbox"/>	
GRAPHITE <input checked="" type="checkbox"/>	
ALU <input type="checkbox"/>	
SHOCK LENGTH	8.5 /mm
ANTI-ROLL BAR	THICKNESS/mm
1.2	

FRONT TOP VIEW		REAR	
1.25	TOE OUT	2.75	TOE IN
Left = Right		Left = Right	
ACKERMANN	SHIM	SHORT LiPo BRASS WEIGHT	YES <input checked="" type="checkbox"/> NO
1.5 /mm		BRASS WEIGHT FOR MOTOR MOUNT	40g
DIFF POSITION	<input checked="" type="checkbox"/> UP	DIFF POSITION	<input checked="" type="checkbox"/> UP
<input type="checkbox"/> DOWN		<input type="checkbox"/> DOWN	
<input type="checkbox"/> +1mm		<input type="checkbox"/> +1mm	
UPPER ARM	SOFT <input checked="" type="checkbox"/>	UPPER ARM	SOFT <input checked="" type="checkbox"/>
MEDIUM <input type="checkbox"/>		MEDIUM <input type="checkbox"/>	
STEERING BRIDGE	YES <input type="checkbox"/> NO	STEERING	SHIM
SHIM	7.5 /mm	0 /mm	
HUB OFFSET	STD. <input checked="" type="checkbox"/> -0.5mm	HUB OFFSET	STD. <input checked="" type="checkbox"/> -0.5mm
+0.5mm		+0.5mm	

FRONT BOTTOM VIEW		REAR	
STEER. LOCK	26 /deg.	T-BRACE	ALU BRASS
SERVO HOLDER	FR RE	CHASSIS T-BRACE	
FRONT ARMS	MEDIUM <input type="checkbox"/>	REAR ARMS	MEDIUM <input type="checkbox"/>
HARD <input checked="" type="checkbox"/>		HARD <input checked="" type="checkbox"/>	
CHASSIS	GRAPHITE <input type="checkbox"/>	CHASSIS	ALU 1.5mm
ALU <input checked="" type="checkbox"/>		ALU 1.5mm	