

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	Zerofive cup 24				
TRACK	PYC Hong Kong				
NAME	Bowie	DATE	31/03/2024		
QUAL POSITION	7th	FINAL POSITION	5th	BEST LAPTIME	/sec
LAPS	/				

TRACK		
TRACK SURFACE	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM
	<input type="checkbox"/> FAST	<input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	6000 /cst	<input checked="" type="checkbox"/> FRONT SOLID AXLE
PINION	29 /T	GEAR DIFF OIL
SPUR GEAR	110 /T	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.6
450	OIL /cst	450
15	REBOUND %	15
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
<input checked="" type="checkbox"/> 4 HOLES	1.1mm	1.1mm
<input type="checkbox"/> PSS	1.2mm	1.2mm
	SHOCK LENGTH	8.5 /mm
	SHOCK LENGTH	8.5 /mm

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

Solaris 40J	TIRES	
MG Yellow	ADDITIVE	
10 mins / 70deg	ADDITIVE TIMING	
	WIPE OFF TIME	
	TIRE WARMERS	
Timing:	Temp.:	
FRONT LEFT	FRONT RIGHT	
REAR LEFT	REAR RIGHT	

TOTAL WEIGHT	1308 /g	WEIGHT BALANCE	FRONT %	REAR %
--------------	---------	----------------	---------	--------

MOTOR	Zombie Evo 5.5T	TIMING	30
ESC	Zombie TZ-01	BATTERIES	Zombie 5850
BODY	Twister UL	WING	Twister UL

66 /mm	Dimension from body post to window bottom line	BODY POSITION
7+o ring	Dimension from body post to upper holder	
WING SIDE PLATE	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	
65 /mm	Dimension from edge to surface	

1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm
X4'23		
X4'22		
X4'22		
NONE	<input type="checkbox"/> BEARING	

COMMENTS

FRONT & REAR SUSPENSION
<div> FRONT CASTER <input type="checkbox"/> 5° <input checked="" type="checkbox"/> 4° <input type="checkbox"/> 3° Adjust with eccentric bushings </div> <div> BUMP STEER 1.5 /mm </div> <div> HEIGHT 20 /mm </div> <div> SHIM /mm </div>
<div> REAR CASTER <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/> 1.5° <input type="checkbox"/> 2.5° <input type="checkbox"/> 3.5° <input type="checkbox"/> 4.5° <input type="checkbox"/> 5.5° Adjust with eccentric bushings </div> <div> TOE GAIN 1 /mm </div> <div> 3 /mm FF 5.0 /mm FR 3 /mm SERVO SAVER RIDE HEIGHT SERVO HORN </div>
<div> 3 /mm RF 5.4 /mm RR 3 /mm RIDE HEIGHT </div>

FRONT
<div> 2 /deg. CAMBER Left = Right </div> <div> BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> 18 /mm </div> <div> SHOCK HOLDERS SHIM 3 /mm </div> <div> SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> </div> <div> DRIVE SHAFT <input checked="" type="checkbox"/> 58mm <input type="checkbox"/> 59mm <input checked="" type="checkbox"/> BEARING <input type="checkbox"/> BLADE </div> <div> SHIM 0.5 /mm </div> <div> FRONT HUB MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> </div>
<div> SHIM 0.5 /mm </div>

REAR
<div> 2 /deg. CAMBER Left = Right </div> <div> BODY POST VERTICAL <input checked="" type="checkbox"/> HORIZONTAL <input type="checkbox"/> </div> <div> SHOCK HOLDERS FIXED <input checked="" type="checkbox"/> ACTIVE <input type="checkbox"/> SHIM 2.5 /mm </div> <div> SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> </div> <div> DRIVE SHAFT <input type="checkbox"/> 52mm <input checked="" type="checkbox"/> 54mm <input checked="" type="checkbox"/> BEARING <input type="checkbox"/> BLADE </div> <div> SHIM 4.8 /mm </div> <div> REAR HUB MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> </div>
<div> SHIM 4.8 /mm </div>

FRONT TOP VIEW	REAR
<div> 1 TOE OUT Left = Right </div> <div> ACKERMANN SHIM 1 /mm </div> <div> SHORT LiPo BRASS WEIGHT YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> </div> <div> BRASS WEIGHT FOR MOTOR MOUNT YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> </div> <div> DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm </div> <div> UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> </div> <div> STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> </div> <div> HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm </div>	<div> 2.5 TOE IN Left = Right </div> <div> SHIM 0 /mm </div> <div> UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> </div> <div> STEERING SHIM/mm <input checked="" type="checkbox"/> 8.0mm <input type="checkbox"/> 7.5mm STD. </div> <div> HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm </div>

FRONT BOTTOM VIEW	REAR
<div> STEER. LOCK 27 /deg. </div> <div> T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/> </div> <div> FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/> </div>	<div> CHASSIS GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU 1.5mm <input type="checkbox"/> </div> <div> REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/> </div>