

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	Pre setting for HKRCSA 2024 Rd 1				
TRACK	TRC				
NAME	Chan Ka Lok Joey		DATE	25/4/2024	
QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME	
		/sec	/		

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input checked="" type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL 5000 /cSt
PINION 38 /T	SPUR GEAR 91 /T	FINAL DRIVE RATIO 4.55

FRONT	SHOCKS	REAR
2.7	XRAY SPRINGS	2.7
400	OIL /cSt	400
25%	REBOUND %	25%
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH 8.5 /mm		SHOCK LENGTH 8.5 /mm	
1.2 THICKNESS/mm		1.2 THICKNESS/mm	

Sweep D40	TIRES	Sweep D40	
MG V3 Black	ADDITIVE	MG V3 Black	
10Mins	ADDITIVE TIMING	10Mins	
	WIPE OFF TIME		
Timing:	Temp.: 80C	Timing:	
FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT 1305 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
----------------------	----------------	------------	-----------

MOTOR Teampowers V5 13.5t	TIMING 30 Fixed
ESC Teampowers V4BT 140A	BATTERIES Coddar 6600mah
BODY Ghibli 2.0	WING Std

65mm /mm	Dimension from body post to window bottom line	BODY POSITION
	Dimension from body post to upper holder	WING SIDE PLATE
	Dimension from edge to surface	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>

1.6mm <input checked="" type="checkbox"/> 2.0mm <input checked="" type="checkbox"/> 1.6mm
2.0mm <input type="checkbox"/> 1.6mm
NONE <input type="checkbox"/> BEARING

Speedome-RC 2.25mm Graphite chassis

Speedome-RC Split topdeck (soft at front ,medium at rear).

3 screws mounting PowerHD S15X servo.

30g bass plate under battery.

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
Adjust with eccentric bushings	BUMP STEER 2 /mm	Adjust with eccentric bushings
5° 4° 3°	HEIGHT 20 /mm	0.5° 1.5° 2.5° 3.5° 4.5° 5.5°
1 /mm FF	SHIM /mm	TOE GAIN 2.5 /mm
5.2 /mm	SERVO SAVER	2.5 /mm RF
FR 2 /mm	SERVO HORN	5.4 /mm RR
RIDE HEIGHT		RIDE HEIGHT

FRONT	SHOCK HOLDERS	SHIM	FRONT HUB
2 /mm	SHIM 3 /mm	2 /mm	MEDIUM <input type="checkbox"/>
CAMBER 2 /deg.	SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	3 /mm	HARD <input type="checkbox"/>
Left = Right	DRIVE SHAFT 58mm 59mm BEARING BLADE		GRAPHITE <input checked="" type="checkbox"/>
	#107702 Chassis Droop Gauge Blocks		ALU <input type="checkbox"/>
	#107712 Chassis Droop Gauge		SHIM 0.5 /mm
			DOWNSTOP 5.8 /mm

REAR	SHOCK HOLDERS	SHIM	REAR HUB
1 /mm	SHIM 3 /mm	1 /mm	MEDIUM <input type="checkbox"/>
CAMBER 2 /deg.	SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	3 /mm	HARD <input type="checkbox"/>
Left = Right	DRIVE SHAFT 52mm 54mm BEARING BLADE		GRAPHITE <input checked="" type="checkbox"/>
	#107702 Chassis Droop Gauge Blocks		ALU <input type="checkbox"/>
	#107712 Chassis Droop Gauge		SHIM 0.5 /mm
			DOWNSTOP 4.8 /mm

FRONT TOP VIEW	REAR
1 TOE OUT	3 TOE IN
Left = Right	Left = Right
ACKERMANN SHIM 0 /mm	SHORT LiPo BRASS WEIGHT YES <input type="checkbox"/> NO <input type="checkbox"/>
DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm	BRASS WEIGHT FOR MOTOR MOUNT 40g
UPPER ARM SOFT MEDIUM <input checked="" type="checkbox"/>	SHIM /mm
STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	STEERING SHIM /mm
HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm	PLATE 7.5 8.0mm 7.5mm STD. <input checked="" type="checkbox"/>
	HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm 0.5

FRONT BOTTOM VIEW	REAR
STEER. LOCK 26 /deg.	T-BRACE ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/>
SERVO HOLDER	CHASSIS T-BRACE
MOTOR MOUNT	FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>
CHASSIS GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU 1.5mm	REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>