

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	Canadian On Road National				
TRACK	Welland Mall				
NAME	Keven Hebert		DATE	April 7th 24	
QUAL POSITION	1	FINAL POSITION	1	BEST LAPTIME	9.5 /sec
				LAPS	31 / 5:02

TRACK					
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT			
TRACK LAYOUT	<input checked="" type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED	<input type="checkbox"/> FAST		
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH		

FRONT		TRANSMISSION		REAR	
GEAR DIFF OIL	/cSt	<input checked="" type="checkbox"/> FRONT SOLID AXLE		GEAR DIFF OIL	7000 /cSt
PINION	29 /T	SPUR GEAR	110 /T	FINAL DRIVE RATIO	

FRONT		SHOCKS		REAR	
2.4/2.7		XRAY SPRINGS		2.7	
425		OIL /cSt		425	
10%		REBOUND %		10%	
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		FOAM INSERTS		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	
<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm		<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm		<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm	
<input checked="" type="checkbox"/> PSS		<input checked="" type="checkbox"/> PSS		<input checked="" type="checkbox"/> PSS	
2x0.8mm		2x0.8mm		2x0.8mm	
SHOCK LENGTH	8.5 /mm	SHOCK LENGTH		8.5 /mm	

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.3
Gravity Type C		TIRES	Gravity Type C	
SXT 3.0		ADDITIVE	SXT 3.0	
7min		ADDITIVE TIMING	7min	
2min		WIPE OFF TIME	2min	
Timing:	Temp.:	TIRE WARMERS	Timing:	Temp.:
FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT	1328 /g	WEIGHT BALANCE	FRONT 50 % REAR 50 %
--------------	---------	----------------	----------------------

MOTOR	Motiv 5.5	TIMING	27
ESC	HW XR10 G2S	BATTERIES	Motiv 4800
BODY	Twister .4	WING	speciale .5

67 /mm	Dimension from body post to window bottom line	BODY POSITION
8th	Dimension from body post to upper holder	WING SIDE PLATE
		YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
64 /mm	Dimension from edge to surface	

X4'23	1.6mm <input checked="" type="checkbox"/> 2.0mm <input type="checkbox"/> 1.6mm <input type="checkbox"/>	
X4'22	2.0mm <input type="checkbox"/> 2.0mm <input type="checkbox"/> 1.6mm <input type="checkbox"/>	
X4'22	2.0mm <input type="checkbox"/> 2.0mm <input type="checkbox"/> 1.6mm <input type="checkbox"/>	
	NONE <input type="checkbox"/> BEARING <input type="checkbox"/>	

6G front Heavy
Power HD setvo all 3 screws used

FRONT & REAR SUSPENSION	
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER	SHIM
2 /mm	3 /mm
HEIGHT	
19 /mm	
TOE GAIN	
1.5 /mm	
TOE IN	
2.5 /mm	
TOE OUT	
5.2 /mm	
SHOCK HOLDERS	
SHIM 6 /mm	
SUSPENSION FLEX	
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	
DRIVE SHAFT	
58mm 59mm BEARING BLADE	
FRONT HUB	
MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	
SHIM	
0.5 /mm	
SHOCK LENGTH	
8.5 /mm	

FRONT	
2 /mm	SHIM 2 /mm
CAMBER	
2 /deg. Left=Right	
BODY STOP	
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	
17 /mm	
SHOCK HOLDERS	
SHIM 6 /mm	
SUSPENSION FLEX	
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	
DRIVE SHAFT	
58mm 59mm BEARING BLADE	
FRONT HUB	
MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	
SHIM	
0.5 /mm	
SHOCK LENGTH	
8.5 /mm	

REAR	
1.5 /mm	SHIM 2 /mm
CAMBER	
2 /deg. Left=Right	
BODY POST	
VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>	
SHOCK HOLDERS	
FIXED <input checked="" type="checkbox"/> ACTIVE <input type="checkbox"/>	
SHIM 6 /mm	
SUSPENSION FLEX	
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	
DRIVE SHAFT	
52mm 54mm BEARING BLADE	
REAR HUB	
MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	
SHIM	
1.5 /mm	
SHOCK LENGTH	
8.5 /mm	

FRONT TOP VIEW		REAR	
1	TOE OUT	3	TOE IN
Left=Right		Left=Right	
ACKERMANN		SHORT LiPo BRASS WEIGHT	
SHIM 1 /mm		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	
DIFF POSITION		BRASS WEIGHT FOR MOTOR MOUNT	
<input type="checkbox"/> UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> +1mm		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	
UPPER ARM		SHIM	
SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>		/mm	
STEERING BRIDGE		STEERING	
YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>		SHIM/mm	
HUB OFFSET		PLATE	
STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm		7.5	
		8.0mm 7.5mm STD.	
		HUB OFFSET	
		STD. <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> +0.5mm SHIM/mm	

FRONT BOTTOM VIEW		REAR	
STEER. LOCK		T-BRACE	
27 /deg.		ALU <input type="checkbox"/> BRASS <input type="checkbox"/>	
SERVO HOLDER		CHASSIS T-BRACE	
FR RE			
MOTOR MOUNT			
CHASSIS			
GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU 1.5mm			
FRONT ARMS		REAR ARMS	
MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>		MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	