

SET-UP SHEET

X4F'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4F'24

RACE	ETS Apeldoorn		
TRACK	AMCA Apeldoorn		
NAME	Delisé Nicolas	DATE	

TRACK TEMP.	QUAL POS.	FINAL POS.	BEST LAPTIME	LAPS	TIME
	1	1	18.9 /sec	/	

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input checked="" type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
-------	--------------	------

GEAR DIFFERENTIAL - OIL	200k /cSt
-------------------------	-----------

PINION / T	SPUR GEAR / T	FINAL DRIVE RATIO
38	90	4.5

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.6
375	OIL /cSt	375
	REBOUND %	
<input type="checkbox"/> YES <input type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input type="checkbox"/> 1.2mm	<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH		8.5 /mm	SHOCK LENGTH		8.5 /mm	

1.1	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.8
-----	--------------	---------------	--------------	-----

Ride	TIRES	Ride
ETS	ADDITIVE	ETS
30*	ADDITIVE TIMING	

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT	1300 /g	WEIGHT BALANCE	FRONT %	REAR %
--------------	---------	----------------	---------	--------

MOTOR	HW ETS	TIMING	
ESC	HW ETS	BATTERIES	Nosram 4200
BODY	YRS	WING	

Dimension from body post to window bottom line	BODY POSITION
Dimension from body post to upper holder	WING SIDE PLATE YES <input type="checkbox"/> NO <input type="checkbox"/>
Dimension from edge to surface	

<input checked="" type="checkbox"/>	TOP DECK FLEX	TOP DECK CUTTING
-------------------------------------	---------------	------------------

Tires prep : 30min @75° without additive, then 2 times additive for 30 minutes

Front shims on upper clamp : 0.5 on new tires, 0.25 after 4 runs.

-1.5 upper clamp front and rear => Free up the car

Only 2 screws on rear upper deck

COMMENTS

FRONT CASTER		FRONT & REAR SUSPENSION		REAR CASTER	
<input checked="" type="checkbox"/> 5°	<input type="checkbox"/> 4°	<input checked="" type="checkbox"/> 1 /mm	<input type="checkbox"/> 2 /mm	<input checked="" type="checkbox"/> 0.5°	<input type="checkbox"/> 1.5°
Adjust with eccentric bushings		Adjust with eccentric bushings		Adjust with eccentric bushings	
BUMP STEER		HEIGHT		SHIM	
2 /mm		5 /mm		FR 2 /mm	
FF		FR		RR 2 /mm	
RIDE HEIGHT		SERVO SAVER		SERVO HORN	
2 /mm		2 /mm		2 /mm	
2 /mm		6 /mm		2 /mm	
2 /mm		2 /mm		2 /mm	

2 /deg.	CAMBER	Left = Right
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	BODY STOP	/mm
0.5° /mm	SHIM	3 /mm
FRONT SUSPENSION	FRONT BRACE	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
FRONT SHOCK POSITION	BULKHEAD SHIMS	YES <input type="checkbox"/> 3mm <input type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT	HUBDY	58mm 59mm BEARING BLADE
#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	5.6 /mm DOWNSTOP

1 /deg.	CAMBER	Left = Right
1 /mm	SHIM	2 /mm
REAR SUSPENSION	REAR SHOCK POSITION	REAR HUB
HARD <input checked="" type="checkbox"/>	GRAPHITE <input type="checkbox"/>	ALU <input type="checkbox"/>
SHIM	1.5 /mm	
#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	4 /mm DOWNSTOP

FRONT TOP VIEW		REAR	
1	TOE OUT	2	TOE IN
Left = Right	Left = Right		
DIFF POSITION	STEERING ARM & BRIDGE		
UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> DUAL STD. <input type="checkbox"/> BRIDGE		
SHIMS	Battery weight plate.		
UPPER ARM	ACKERMANN		
SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>	SHIM 1 /mm		
HUB OFFSET	STEERING PLATE		
STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm 0.5	8.0mm STD. <input type="checkbox"/> 7.5mm <input checked="" type="checkbox"/>		
HUB OFFSET	HUB OFFSET		
STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm 0.5	STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm 0.5		

FRONT BOTTOM VIEW		REAR	
WEIGHT LEFT & RIGHT	STEER. LOCK	T-BRACE	
#309825 YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	/deg.	ALU <input type="checkbox"/> BRASS <input type="checkbox"/>	
BUMPER WEIGHT	STEER. SHIM		
#309824 YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	SIZE /mm		
FRONT BRACE	MOTOR MOUNT		
YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	CHASSIS T-BRACE		
FRONT ARMS	CHASSIS		
MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	GRAPHITE <input checked="" type="checkbox"/>		
REAR ARMS			
MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>			