

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	EC Warmup				
TRACK	RCR Roeselare				
NAME	Delise Nicolas		DATE		
QUAL POSITION	11	FINAL POSITION	11	BEST LAPTIME	16.5 /sec
LAPS	/				

TRACK		
TRACK SURFACE	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM
	<input type="checkbox"/> FAST	<input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL
PINION	42 /T	SPUR GEAR
	90 /T	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7*
375	OIL /Cst	375
	REBOUND %	
<input type="checkbox"/> YES <input type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input type="checkbox"/> NO
<input checked="" type="checkbox"/> 4 HOLES	1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH	8.5 /mm	SHOCK LENGTH
	8.5 /mm	
1.1	THICKNESS/mm	1.2

Rush 36	TIRES	
Tristar		
25		
Timing:	Temp.:	
FRONT LEFT	FRONT RIGHT	
REAR LEFT	REAR RIGHT	

TOTAL WEIGHT	WEIGHT BALANCE	FRONT	REAR
MOTOR	HW G4R 13.5	TIMING	50
ESC	HW	BATTERIES	
BODY	Wolverine	WING	twister

64 /mm	Dimension from body post to window bottom line	BODY POSITION
WING SIDE PLATE	YES <input type="checkbox"/> NO <input type="checkbox"/>	
Dimension from body post to upper holder		
Dimension from edge to surface		
1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm
X4'23	<input checked="" type="checkbox"/>	
X4'22	<input type="checkbox"/>	
X4'22	<input type="checkbox"/>	
NONE	<input type="checkbox"/>	BEARING

Car had pace for better result, but I didn't make a single clear run in qualifications.

2.7 rear spring on new tires, 2.8 on used

Try softer hub next time to get bit more grip

FRONT & REAR	SUSPENSION
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER	HEIGHT
SHIM	SHIM
2.5 /mm	FR 2.5 /mm
TOE GAIN	3 /mm
1.5 /mm	RR 3 /mm
SERVO SAVER	SERVO HORN

FRONT	SHOCK HOLDERS	SHOCK FLEX	SHOCK LENGTH
2 /deg.	SHIM 2 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	8.5 /mm
CAMBER	SHOCK HOLDERS	SUSPENSION FLEX	SHOCK LENGTH
Left = Right	SHIM 2 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	8.5 /mm
DRIVE SHAFT	SHOCK FLEX	SUSPENSION FLEX	SHOCK LENGTH
58mm 59mm	SHIM 2 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	8.5 /mm
BEARING BLADE	SUSPENSION FLEX	SUSPENSION FLEX	SHOCK LENGTH
	SHIM 2 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	8.5 /mm
	SUSPENSION FLEX	SUSPENSION FLEX	SHOCK LENGTH
	SHIM 2 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	8.5 /mm

REAR	SHOCK HOLDERS	SHOCK FLEX	SHOCK LENGTH
1 /mm	SHIM 3 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	8.5 /mm
CAMBER	SHOCK HOLDERS	SUSPENSION FLEX	SHOCK LENGTH
Left = Right	SHIM 3 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	8.5 /mm
DRIVE SHAFT	SHOCK FLEX	SUSPENSION FLEX	SHOCK LENGTH
52mm 54mm	SHIM 3 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	8.5 /mm
BEARING BLADE	SUSPENSION FLEX	SUSPENSION FLEX	SHOCK LENGTH
	SHIM 3 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	8.5 /mm
	SUSPENSION FLEX	SUSPENSION FLEX	SHOCK LENGTH
	SHIM 3 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	8.5 /mm

FRONT TOP VIEW	REAR
TOE OUT	TOE IN
Left = Right	Left = Right
ACKERMANN	SHORT LiPo BRASS WEIGHT
SHIM 0.5 /mm	YES <input type="checkbox"/> NO <input type="checkbox"/>
DIFF POSITION	BRASS WEIGHT FOR MOTOR MOUNT
UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	40g
UPPER ARM	SHIM
SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/>	SHIM /mm
XS	STEERING BRIDGE
STEERING BRIDGE	STEERING
YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	SHIM /mm
HUB OFFSET	STEERING
STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm	SHIM /mm
SHIM /mm	STEERING
	SHIM /mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK	T-BRACE
26 /deg.	ALU BRASS
SERVO HOLDER	CHASSIS T-BRACE
FR RE	CHASSIS T-BRACE
FRONT ARMS	CHASSIS T-BRACE
MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	CHASSIS T-BRACE
CHASSIS	CHASSIS T-BRACE
GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU 1.5mm	CHASSIS T-BRACE
REAR ARMS	CHASSIS T-BRACE
MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	CHASSIS T-BRACE