

# SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

# XRAY X4'24

RACE	Trnava r4				
TRACK	Varianta 4				
NAME	Filip Bortoli		DATE		
QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME	
4	4	15.3 /sec		/	

TRACK		
TRACK SURFACE	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL
PINION	SPUR GEAR	FINAL DRIVE RATIO
38 /T	100 /T	7k /St

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
350	OIL /Cst	350
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH		SHOCK LENGTH	
8 /mm		8 /mm	

1.1	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

Hudy	TIRES
Hudy asphalt	ADDITIVE
15 min	ADDITIVE TIMING
1	WIPE OFF TIME
Timing: 15	TIRE WARMERS
Temp.: 60	Timing:
Temp.:	
FRONT LEFT	FRONT RIGHT
REAR LEFT	REAR RIGHT
TREATED AREA	

TOTAL WEIGHT	1300 /g	WEIGHT BALANCE	FRONT 49 %	REAR 51 %
--------------	---------	----------------	------------	-----------

MOTOR	Hw juststock 13,5	TIMING	Fix
ESC	Hw 160 a	BATTERIES	6100
BODY	Wolverine	WING	Std

64,5 /mm	Dimension from body post to window bottom line	BODY POSITION
6+oring	Dimension from body post to upper holder	WING SIDE PLATE
52 /mm	Dimension from edge to surface	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>

1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm
2.0mm	<input type="checkbox"/> 1.6mm	<input type="checkbox"/> NONE
2.0mm	<input type="checkbox"/> 1.6mm	<input type="checkbox"/> BEARING

Na nových kolech nahrivat 10 min

FRONT & REAR	SUSPENSION
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER	SHIM
2 /mm	7 /mm
HEIGHT	TOE GAIN
19 /mm	1,5 /mm
SHIM	3,5 /mm
3 /mm	5,2 /mm
FF	RF
5 /mm	RR
FR	3,5 /mm
3 /mm	3,5 /mm
FRIDE HEIGHT	RRIDE HEIGHT
<input checked="" type="checkbox"/> SERVO SAVER	<input checked="" type="checkbox"/> SERVO HORN

FRONT	SHOCK HOLDERS	SHOCK FLEX	SHIM	FRONT HUB
2 /mm	SHIM 2 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	2 /mm	MEDIUM <input type="checkbox"/>
3 /mm	SHIM 3 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	3 /mm	HARD <input type="checkbox"/>
SHOCK LENGTH	SHOCK LENGTH	SHOCK LENGTH	SHOCK LENGTH	SHOCK LENGTH
8 /mm	8 /mm	8 /mm	8 /mm	8 /mm
1.1	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2

FRONT	SHOCK HOLDERS	SHOCK FLEX	SHIM	FRONT HUB
2 /mm	SHIM 2 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	2 /mm	MEDIUM <input type="checkbox"/>
3 /mm	SHIM 3 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	3 /mm	HARD <input type="checkbox"/>
SHOCK LENGTH	SHOCK LENGTH	SHOCK LENGTH	SHOCK LENGTH	SHOCK LENGTH
8 /mm	8 /mm	8 /mm	8 /mm	8 /mm
1.1	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2

FRONT	TOP VIEW	REAR
TOE OUT	ACKERMANN	TOE IN
Left=Right	SHIM 0,5 /mm	Left=Right
DIFF POSITION	SHORT LiPo BRASS WEIGHT	DIFF POSITION
<input checked="" type="checkbox"/> UP	YES <input type="checkbox"/> NO <input type="checkbox"/>	<input checked="" type="checkbox"/> UP
<input type="checkbox"/> DOWN	YES <input type="checkbox"/> NO <input type="checkbox"/>	<input type="checkbox"/> DOWN
<input type="checkbox"/> +1mm	BRASS WEIGHT FOR MOTOR MOUNT	<input type="checkbox"/> +1mm
UPPER ARM	STEERING BRIDGE	UPPER ARM
SOFT	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	SOFT
MEDIUM	SHIM/mm	MEDIUM
X	SHIM/mm	X
HUB OFFSET	STEERING	HUB OFFSET
STD. <input type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm	SHIM/mm	STD. <input type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm
SHIM/mm	SHIM/mm	SHIM/mm

FRONT	BOTTOM VIEW	REAR
STEER. LOCK	T-BRACE	STEER. LOCK
26 /deg.	ALU BRASS	26 /deg.
FR	CHASSIS T-BRACE	FR
RE	CHASSIS T-BRACE	RE
SERVO HOLDER	CHASSIS	SERVO HOLDER
MOTOR MOUNT	GRAPHITE <input checked="" type="checkbox"/>	MOTOR MOUNT
FRONT ARMS	ALU <input type="checkbox"/>	FRONT ARMS
MEDIUM <input checked="" type="checkbox"/>	ALU 1.5mm <input type="checkbox"/>	MEDIUM <input checked="" type="checkbox"/>
HARD <input type="checkbox"/>	REAR ARMS	HARD <input type="checkbox"/>
REAR ARMS	MEDIUM <input checked="" type="checkbox"/>	REAR ARMS
MEDIUM <input checked="" type="checkbox"/>	HARD <input type="checkbox"/>	MEDIUM <input checked="" type="checkbox"/>
HARD <input type="checkbox"/>		HARD <input type="checkbox"/>