

SET-UP SHEET

X4F'25 SET-UP SHEET VER.1 ©XRAY

XRAY X4F'25

RACE	EC Warm Up		
TRACK	RCS Roeselare		
NAME	Jacques Libar	DATE	30.06.24

TRACK TEMP.	QUAL POS.	FINAL POS.	BEST LAPTIME	LAPS	TIME
/	3	3	19.4 /sec	/ /	/

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFFERENTIAL - OIL 200K /cSt		
PINION / T 38	SPUR GEAR / T 90	FINAL DRIVE RATIO 4.5

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.6
350	OIL /cSt	350
/	REBOUND %	/

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH 8.5 /mm		SHOCK LENGTH 8.5 /mm	

1.3 THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm 1.2
-------------------------	---------------	-------------------------

RIDE ETS		TIRES	
TriStar Blue		ADDITIVE	
15 min		ADDITIVE TIMING	
5 min		WIPE OFF TIME	
Timing: 20 min	Temp.: 65	TIRE WARMERS	Timing: Temp.:

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT	1254 /g	WEIGHT BALANCE	FRONT 64 % REAR 36 %
--------------	----------------	----------------	------------------------------------

MOTOR	21.5	TIMING	/
ESC	Team Zombie	BATTERIES	4200 Nosram
BODY	YRS	WING	std

Dimension from body post to window bottom line 55 /mm	
Dimension from body post to upper holder EFRA /mm	
WING SIDE PLATE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	
Dimension from edge to surface EFRA /mm	

TOP DECK CUTTING

COMMENTS	
----------	--

FRONT & REAR SUSPENSION	
FRONT CASTER <input checked="" type="checkbox"/> 5° <input type="checkbox"/> 4° <input type="checkbox"/> 3° Adjust with eccentric bushings	REAR CASTER <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> 1.5° <input type="checkbox"/> 2.5° <input type="checkbox"/> 3.5° <input type="checkbox"/> 4.5° <input type="checkbox"/> 5.5° Adjust with eccentric bushings
BUMP STEER 1 /mm HEIGHT 19 /mm SHIM 6 /mm	TOE GAIN 5 /mm
2 /mm FF 5.0 /mm FR 2 /mm RIDE HEIGHT	2 /mm RF 5.2 /mm RR 2 /mm RIDE HEIGHT
<input type="checkbox"/> SERVO SAVER <input type="checkbox"/> SERVO HORN	

2 /degr. CAMBER Left = Right	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> /mm	FRONT SUSPENSION SHOCK HOLDERS SHIM 2 /mm	FRONT HUB MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>
	SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SHIMS 4 /mm SHIM 0.5 /mm	SHIM 0.5 /mm
DRIVE SHAFT 58mm <input type="checkbox"/> 59mm <input type="checkbox"/> BEARING <input type="checkbox"/> BLADE <input type="checkbox"/>	#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5.6 /mm DOWNSTOP		

2 /degr. CAMBER Left = Right	REAR SUSPENSION SHOCK HOLDERS FIXED <input checked="" type="checkbox"/> ACTIVE <input type="checkbox"/> SHIM 2 /mm	REAR HUB MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>
	SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SHIMS 3 /mm SHIM 1.5 /mm
#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4.4 /mm DOWNSTOP		

FRONT TOP VIEW		REAR
1 TOE OUT Left = Right	3.0 TOE IN Left = Right	
DIFF POSITION UP <input type="checkbox"/> +1mm <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> STD. <input type="checkbox"/>	SHIMS 0 /mm Battery weight plate.	ARS LINKS SHIMS kit /mm
UPPER ARM COMPOSITE <input checked="" type="checkbox"/> EXTRA SOFT <input type="checkbox"/> SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/>	UPPER ARM COMPOSITE <input checked="" type="checkbox"/> EXTRA SOFT <input type="checkbox"/> SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/>	
HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm	HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm	

FRONT	BOTTOM VIEW	REAR
WEIGHT LEFT & RIGHT #309826 YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	STEER. LOCK 26 /degr.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
BUMPER WEIGHT YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	MOTOR MOUNT	CHASSIS T-BRACE
FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	CHASSIS GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>	REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>