

SET-UP SHEET

X4F'25 SET-UP SHEET VER.1 ©XRAY

XRAY X4F'25

RACE	Warm Up ETS Luxembourg				
TRACK	LMCC Mini circuit ville de Luxembourg				
NAME	Jacques Libar	DATE	07.07.24		

TRACK TEMP.	QUAL. POS.	FINAL POS.	BEST LAPTIME	LAPS	TIME
/	1	1	24.0 /sec	/	/

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFFERENTIAL - OIL 150K /cSt		
PINION / T 38	SPUR GEAR / T 90	FINAL DRIVE RATIO 4.5

FRONT	SHOCKS	REAR
2.6-2.9	XRAY SPRINGS	2.6
350	OIL /Cst	350
	REBOUND %	

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH	8.5 /mm	8.5 /mm	SHOCK LENGTH

1.4 THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm 1.6
-------------------------	----------------------	-------------------------

RIDE ETS	TIRES ADDITIVE ADDITIVE TIMING WIPE OFF TIME TIRE WARMERS
MR33 V3	
12 min	
/	
Timing: 12	Temp.: 70

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT	1261 /g	WEIGHT BALANCE	FRONT 66 %	REAR 34 %
--------------	----------------	----------------	-------------------	------------------

MOTOR	17.5 ETS	TIMING	RPM LIMIT 17.5K
ESC	HW ETS limiter	BATTERIES	4200 Nosram
BODY	YRS	WING	std

54 /mm	Dimension from body post to window bottom line	BODY POSITION
low /mm	Dimension from body post to upper holder	WING SIDE PLATE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
low /mm	Dimension from edge to surface	

<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
TOP DECK CUTTING							

COMMENTS	
----------	--

FRONT & REAR SUSPENSION	
FRONT CASTER <input checked="" type="checkbox"/> 5° <input type="checkbox"/> 4° <input type="checkbox"/> 3° Adjust with eccentric bushings BUMP STEER 2 /mm HEIGHT 19 /mm SHIM 4 /mm FRIDE HEIGHT 5.2 /mm FR 2.0 /mm <input checked="" type="checkbox"/> SERVO SAVER <input type="checkbox"/> SERVO HORN	REAR CASTER <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> 1.5° <input type="checkbox"/> 2.5° <input type="checkbox"/> 3.5° <input type="checkbox"/> 4.5° <input type="checkbox"/> 5.5° Adjust with eccentric bushings TOE GAIN /mm RRIDE HEIGHT 5.4 /mm RR 2.0 /mm <input checked="" type="checkbox"/> SERVO SAVER <input type="checkbox"/> SERVO HORN

2 /degr. CAMBER Left = Right SHOCK HOLDERS SHIM 2 /mm SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> DRIVE SHAFT <input checked="" type="checkbox"/> 58mm <input checked="" type="checkbox"/> 59mm <input checked="" type="checkbox"/> BEARING <input checked="" type="checkbox"/> BLADE #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5.6 /mm DOWNSTOP	FRONT HUB MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> SHIM 0.5 /mm
---	--

2 /degr. CAMBER Left = Right SHOCK HOLDERS FIXED <input checked="" type="checkbox"/> ACTIVE <input type="checkbox"/> SHIM 2 /mm SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4.6 /mm DOWNSTOP	REAR HUB MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> SHIM 1.0 /mm
---	---

FRONT TOP VIEW	REAR
1.0 TOE OUT Left = Right DIFF POSITION UP <input checked="" type="checkbox"/> +1mm <input type="checkbox"/> DOWN <input type="checkbox"/> STD. <input type="checkbox"/> SHIMS 0 /mm BATTERY WEIGHT PLATE UPPER ARM COMPOSITE <input checked="" type="checkbox"/> EXTRA SOFT <input type="checkbox"/> SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/> HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm	3.0 TOE IN Left = Right ARS LINKS SHIMS kit /mm UPPER ARM COMPOSITE <input checked="" type="checkbox"/> EXTRA SOFT <input type="checkbox"/> SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/> HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm

FRONT BOTTOM VIEW	REAR
WEIGHT LEFT & RIGHT #309826 YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> BUMPER WEIGHT YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/> CHASSIS GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>	STEER. LOCK 26 /degr. T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/> MOTOR MOUNT CHASSIS T-BRACE REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>