

SET-UP SHEET

X4F'25 SET-UP SHEET VER.1 ©XRAY

XRAY X4F'25

RACE	German nationals 1/10		
TRACK	Siersburg		
NAME	Jacques Libar	DATE	06/10/2024

TRACK TEMP.	QUAL POS.	FINAL POS.	BEST LAP TIME	LAPS	TIME
	3	4	10.9 /sec	/ /	/

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input checked="" type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFFERENTIAL - OIL 150K /cSt		
PINION / T 38	SPUR GEAR / T 100	FINAL DRIVE RATIO 5.0

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.6
350	OIL /cSt	350
/	REBOUND %	/

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH	8.5 /mm	8.5 /mm	SHOCK LENGTH

1.3 THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm 1.8
-------------------------	---------------	-------------------------

Rush 28	TIRES ADDITIVE ADDITIVE TIMING WIPE OFF TIME TIRE WARMERS	
CS-High Grip		
20 min		
5		
Timing:	Temp.:	

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT	1253 /g	WEIGHT BALANCE	FRONT / %	REAR / %
--------------	----------------	----------------	-----------	----------

MOTOR	HW 17.5	TIMING		RPM LIMIT	35000
ESC	HW G3S	BATTERIES	Nosram 4200		
BODY	Bitty CA 45	WING	std		

	Dimension from body post to window bottom line	BODY POSITION
high /mm		
	Dimension from body post to upper holder	WING SIDE PLATE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
	Dimension from edge to surface	high /mm

<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
TOP DECK CUTTING					

COMMENTS	
----------	--

FRONT & REAR SUSPENSION	
FRONT CASTER <input type="checkbox"/> 5° <input checked="" type="checkbox"/> 4° <input type="checkbox"/> 3° Adjust with eccentric bushings	REAR CASTER <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/> 1.5° <input type="checkbox"/> 2.5° <input type="checkbox"/> 3.5° <input type="checkbox"/> 4.5° <input type="checkbox"/> 5.5° Adjust with eccentric bushings
BUMP STEER 2 /mm HEIGHT 19 /mm SHIM 6 /mm	TOE GAIN 4 /mm
2.0 /mm FF 5.0 /mm FR 2.0 /mm RR RIDE HEIGHT <input checked="" type="checkbox"/> SERVO SAVER <input checked="" type="checkbox"/> SERVO HORN <input checked="" type="checkbox"/>	2.0 /mm RF 5.2 /mm RR 2.0 /mm RR RIDE HEIGHT <input checked="" type="checkbox"/>

2.0 /mm CAMBER Left = Right	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> 23 /mm	FRONT SUSPENSION SHOCK HOLDERS SHIM 2 /mm	FF /mm 2 FR /mm 2 SHIMS 3 /mm	FRONT HUB MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>
SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>				
DRIVE SHAFT 58mm <input checked="" type="checkbox"/> 59mm <input type="checkbox"/> BEARING <input checked="" type="checkbox"/> BLADE <input type="checkbox"/> #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5.8 /mm DOWNSTOP				

2.0 /mm CAMBER Left = Right	REAR SUSPENSION SHOCK HOLDERS FIXED <input checked="" type="checkbox"/> ACTIVE <input type="checkbox"/> SHIM 2 /mm	RF /mm 2 RR /mm 2 SHIMS 3 /mm	REAR HUB MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>
SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>			
#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4.4 /mm DOWNSTOP			

FRONT TOP VIEW		REAR	
0.5 TOE OUT Left = Right	2.0 TOE IN Left = Right	DIFF POSITION UP <input checked="" type="checkbox"/> +1mm <input type="checkbox"/> DOWN <input type="checkbox"/> STD. <input type="checkbox"/>	SHIMS 0 /mm Battery weight plate.
UPPER ARM COMPOSITE <input type="checkbox"/> EXTRA SOFT <input type="checkbox"/> SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/>	UPPER ARM COMPOSITE <input type="checkbox"/> EXTRA SOFT <input type="checkbox"/> SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/>	HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm	HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm

FRONT BOTTOM VIEW		REAR	
WEIGHT LEFT & RIGHT #309826 YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	STEER. LOCK 26 /deg.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>	CHASSIS T-BRACE
BUMPER WEIGHT YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	MOTOR MOUNT	FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>