

**XRAY GTX8'23 C-HUB**

**FRONT**

**STEERING BLOCK**  
COMPOSITE ☐  
ALU ☒

**C-HUB**  
COMPOSITE ☐  
ALU ☒  
**CASTER**  
16° ☐  
6° ☒  
2° ☐

**FRONT ARM**  
SOFT ☐  
MEDIUM ☐  
HARD ☐  
GRAPHITE ☒

**OFFSET**  
0 ☐ +1 ☒ +2 ☐

**CASTER BUSHINGS**  
+2° ☐  
+1° ☐  
0° ☒  
-1° ☐  
-2° ☐

**FRONT DROOP**  
28

MEASURE UNDER WHEEL AXLE #107717 GAUGE

**REAR**

**ANTI-ROLL BAR**  
1 2

**REAR ARMS**  
MEDIUM ☐  
HARD ☐  
X-HARD ☐  
GRAPHITE ☒

**LOWER ROLL CENTER**  
ALU ☒

**UPRIGHT**  
MEDIUM ☐  
HARD ☐  
GRAPHITE ☐

**OFFSET**  
STANDARD ☐  
+1 ☒ +2 ☐

**REAR DROOP**  
28

MEASURE UNDER WHEEL AXLE

**FRONT**

**BUMP STEER SHIM /mm**  
STEERING BLOCK 3  
STEERING PLATE 0  
SHIMS PLACE ALWAYS UNDER

**WHEELBASE SHIM POSITION**  
0 mm ☒ 2 mm ☐  
SHIMS BEHIND FRONT ARM

**FF** 1° ☒ 0.5° ☐  
**FR** 1° ☒ 0.5° ☐

**FRONT LOWER ROLL CENTER ECCENTRIC BUSHINGS**

**REAR**

**WING HIGH** /mm

**GRAPHITE BRACE**  
WITHOUT ☐  
1-PIECE ☐  
2-PIECES ☐

**REAR DIFFUSOR**  
YES ☐ NO ☒

**RR** 1° ☐ 0.5° ☒

**REAR LOWER ROLL CENTER ECCENTRIC BUSHINGS**

**FRONT TOE OUT** 1.5

**TIGHTEN SERVO SAVER MATERIAL**  
TIGHT ☒ MEDIUM ☐  
MEDIUM ☒ GRAPHITE ☐  
SOFT ☐

**ACKERMANN POSITION**  
3 2 1

**UPPER PLATE**  
COMPOSITE ☒  
GRAPHITE ☒

**WHEELBASE**  
0 mm ☐ 1 mm ☐ 2 mm ☒ 3 mm ☐ 4 mm ☐  
SHIMS IN FRONT OF UPRIGHT

**ENGINE MOUNT**  
STANDARD ☒  
MONOBLOCK ☐

**REAR TOE IN** 2.5

**FRONT CAMBER** 2/2.5

**LENGTH** mm

**RIDE HEIGHT** 9 /mm

**REAR DIFF HEIGHT**  
UP ☐  
DOWN ☐

**REAR CAMBER** 3/3.5

**LENGTH** mm

**RIDE HEIGHT** 10 /mm

**FRONT**

**REAR**