

# SET-UP SHEET

X4'25 SET-UP SHEET VER.1 ©XRAY

# XRAY X4'25

RACE	Rug Racers Round 2				
TRACK	Round 2				
NAME	Harley Eldridge		DATE	1/12/2024-	
QUAL POSITION	3	FINAL POSITION	3	BEST LAPTIME	9.5 /sec
LAPS	/				

TRACK		
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL
PINION	22 /T	SPUR GEAR
	84 /T	FINAL DRIVE RATIO
		7.2

FRONT	SHOCKS	REAR
2.4-2.7	XRAY SPRINGS	2.7
400	OIL /Cst	400
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
<input type="checkbox"/> 4 HOLES <input checked="" type="checkbox"/> PSS	1.1mm 1.2mm	<input type="checkbox"/> 4 HOLES <input checked="" type="checkbox"/> PSS
2x0.8		2x0.8
SHOCK LENGTH	7 /mm	SHOCK LENGTH
	7 /mm	
1.3	THICKNESS/mm	1.3

Rush 30	TIRES	
Mr33		
5-10mins		
2		
Timing:	Temp.:	
FRONT TIRES ADDITIVE AREA All /mm		

TOTAL WEIGHT	13.03 /g	WEIGHT BALANCE	FRONT 49 % REAR 51 %
MOTOR	5T	TIMING	32
ESC	HW G3	BATTERIES	4200
BODY	Twister UL	WING	Twister L

66 /mm	Dimension from body post to window bottom line	BODY POSITION
7 + oring	Dimension from body post to upper holder	
64 /mm	Dimension from edge to surface	

X4'23	GF 1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm	GF
	SCREWS	SHIMS		
Rear used in front	2.0mm	1.6mm		
X4'22	NONE	BEARING		

COMMENTS

FRONT CASTER	Upper links CASTER	FRONT & REAR SUSPENSION	REAR CASTER	Upper links CASTER
5° 4° 3°			0.5° 1.5° 2.5° 3.5° 4.5° 5.5°	
Adjust with eccentric bushings			Adjust with eccentric bushings	
2 /mm	5 /mm	FR 2 /mm	TOE GAIN 1 /mm	2.5 /mm
FF	FR	RR	2.5 /mm	5.2 /mm
<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT
<input checked="" type="checkbox"/> SERVO SAVER	<input checked="" type="checkbox"/> SERVO HORN			

FRONT
2 /deg. CAMBER
Left = Right
BODY STOP YES <input checked="" type="checkbox"/> NO
16 /mm
SHOCK HOLDERS SHIM 4 /mm
SHOCK TOWER SCREW YES <input checked="" type="checkbox"/> NO
YES <input checked="" type="checkbox"/> NO
DRIVE SHAFT 58mm 59mm BEARING BLADE
FF 1.75 /mm SHIM 2 /mm
FR 1.75 /mm
FRONT HUB MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
SHIM 0.5 /mm
DOWNSTOP 6.0 /mm
Set with shocks <input checked="" type="checkbox"/> Set without shocks

REAR
2 /deg. CAMBER
Left = Right
BODY POST VERTICAL <input checked="" type="checkbox"/> HORIZONTAL
SHOCK HOLDERS SHIM 4 /mm
SHOCK TOWER SCREW YES <input checked="" type="checkbox"/> NO
YES <input checked="" type="checkbox"/> NO
DRIVE SHAFT 52mm 54mm BEARING BLADE
RF 1.5 /mm SHIM 2 /mm
RR 1.5 /mm
REAR HUB MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
SHIM 1 /mm
DOWNSTOP 4.2 /mm
Set with shocks <input checked="" type="checkbox"/> Set without shocks

FRONT TOP VIEW	REAR
1 TOE OUT	2.5 TOE IN
Left = Right	Left = Right
ACKERMANN SHIM 0.5 /mm	
SHORT LiPo BRASS WEIGHT YES <input checked="" type="checkbox"/> NO	
BRASS WEIGHT FOR MOTOR MOUNT	
DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN	
FRONT UPPER ARM LINKS C <input checked="" type="checkbox"/> XS <input type="checkbox"/> S <input type="checkbox"/> M	
STEERING BRIDGE YES <input checked="" type="checkbox"/> NO	
SHIM /mm	
HUB OFFSET <input checked="" type="checkbox"/>	
STEERING SHIM /mm	
PLATE 7.5	
8.0mm 7.5mm STD.	
REAR UPPER ARM LINKS C <input checked="" type="checkbox"/> XS <input type="checkbox"/> S <input type="checkbox"/> M	
HUB OFFSET <input checked="" type="checkbox"/>	

FRONT BOTTOM VIEW	REAR
BUMPER 3D - KIT <input type="checkbox"/> FOAM <input checked="" type="checkbox"/>	
STEER. LOCK 26 /deg.	
T-BRACE ALU BRASS	
MOTOR MOUNT	
SERVO HOLDER	
CHASSIS T-BRACE	
FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	
CHASSIS GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU 1.5mm	
REAR ARMS MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	