

SET-UP SHEET

X4F'25 SET-UP SHEET VER.1 ©XRAY

XRAY X4F'25

RACE	EWS Internationa		
TRACK	EWS		
NAME	Matthew Lax	DATE	08.12.24

TRACK TEMP.	QUAL POS.	FINAL POS.	BEST LAPTIME	LAPS	TIME
	5	6	17.7 /sec	17 /	305

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFFERENTIAL - OIL 300 /cSt		
PINION / T 38	SPUR GEAR / T 100	FINAL DRIVE RATIO 5

FRONT	SHOCKS	REAR
2.8	XRAY SPRINGS	2.9
400	OIL /Cst	400
10	REBOUND %	10

<input checked="" type="checkbox"/> 4 HOLES	<input type="checkbox"/> 1.1mm	<input type="checkbox"/> 1.1mm	<input type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH 8.5 /mm		SHOCK LENGTH 8.5 /mm	

1.4 THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm 1.4
-------------------------	---------------	-------------------------

Ride Slick	TIRES		
MR33 V4			
15			
5			
Timing:	Temp.:	Timing:	Temp.:

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT	1288 /g	WEIGHT BALANCE	FRONT %	REAR %
--------------	----------------	----------------	---------	--------

MOTOR	HW	TIMING	RPM LIMIT	17.5
ESC	HW	BATTERIES	Fyework 6300	
BODY	Blitz YRS LW	WING	Std	

	Dimension from body post to window bottom line /mm	BODY POSITION
	Dimension from body post to upper holder /mm	WING SIDE PLATE YES <input type="checkbox"/> NO <input type="checkbox"/>
	Dimension from edge to surface /mm	

<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
TOP DECK CUTTING					
TOP DECK FLEX					

COMMENTS	
----------	--

FRONT CASTER		FRONT & REAR SUSPENSION		REAR CASTER	
<input checked="" type="checkbox"/> 5°	<input type="checkbox"/> 4°	<input checked="" type="checkbox"/> 1 /mm	<input type="checkbox"/> 19 /mm	<input checked="" type="checkbox"/> 0.5°	<input type="checkbox"/> 1.5°
Adjust with eccentric bushings		Adjust with eccentric bushings		Adjust with eccentric bushings	
0.5 /mm FF 5.2 /mm RIDE HEIGHT FR 0.5 /mm		SHIM 5 /mm SERVO SAVER <input type="checkbox"/> SERVO HORN <input checked="" type="checkbox"/>		TOE GAIN 4 /mm 2 /mm RF 5.4 /mm RIDE HEIGHT RR 2 /mm	

2 /degr. CAMBER	Left = Right	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> SHOCK HOLDERS SHIM 1 /mm	FRONT SUSPENSION FF /mm 1 FR /mm 1 SHIMS 3 /mm	FRONT HUB MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>
		SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> DRIVE SHAFT 58mm <input checked="" type="checkbox"/> 59mm <input type="checkbox"/> BEARING <input type="checkbox"/> BLADE <input type="checkbox"/>		SHIM 0.5 /mm #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5.6 /mm DOWNSTOP

2 /degr. CAMBER	Left = Right	SHOCK HOLDERS FIXED <input checked="" type="checkbox"/> ACTIVE <input type="checkbox"/> SHIM 1 /mm	REAR SUSPENSION RF /mm 0.5 RR /mm 0.5 SHIMS 3 /mm	REAR HUB MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>
		SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4.2 /mm DOWNSTOP		

FRONT TOP VIEW		REAR	
1 TOE OUT	Left = Right	0.5 TOE IN	Left = Right
DIFF POSITION UP <input type="checkbox"/> +1mm <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> STD. <input checked="" type="checkbox"/>		SHIMS 0 /mm Battery weight plate.	
UPPER ARM COMPOSITE <input checked="" type="checkbox"/> EXTRA SOFT <input type="checkbox"/> SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/>		UPPER ARM COMPOSITE <input checked="" type="checkbox"/> EXTRA SOFT <input type="checkbox"/> SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/>	
HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm 0.5		HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm 0.5	

FRONT BOTTOM VIEW		REAR	
WEIGHT LEFT & RIGHT #309826 YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	STEER. LOCK 28 /degr.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>	
BUMPER WEIGHT YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		MOTOR MOUNT	
FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>		CHASSIS GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>	
		REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	