

SET-UP SHEET

XB2'21 SET-UP SHEET VER. 1 ©XRAY 2020

XRAY XB2'21

| | | |
|-------|---------------------------|-----------------|
| RACE | Practise Grimstad Raceway | |
| TRACK | Grimstad Raceway | |
| NAME | Daniel Kobbevik | DATE 2021-03-27 |

| | | | |
|---------------------|--|----------------|----------|
| LAPS | | BEST LAP TIME | 14.5 sec |
| QUALIFYING POSITION | | FINAL POSITION | |

| TRACK | |
|-----------|---|
| SIZE | <input type="checkbox"/> OPEN <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> TIGHT |
| TRACTION | <input type="checkbox"/> VERY-LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> VERY-HIGH |
| SURFACE | <input checked="" type="checkbox"/> SMOOTH <input type="checkbox"/> MEDIUM <input type="checkbox"/> BUMPY |
| TYPE | <input type="checkbox"/> CLAY <input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASTRO |
| CONDITION | <input type="checkbox"/> BLUE GROOVE <input type="checkbox"/> HARD PACKED <input checked="" type="checkbox"/> DRY <input type="checkbox"/> DUSTY <input type="checkbox"/> LOAMY <input type="checkbox"/> WET |

| TRANSMISSION | |
|---|--|
| DIFFERENTIAL | |
| BALL DIFF <input checked="" type="checkbox"/> | GEAR DIFF <input type="checkbox"/> ACTIVE DIFF <input type="checkbox"/> |
| OIL <input type="text"/> cst 60° 90° 120° | |
| SATELLITE GEARS | COMPOSITE <input type="checkbox"/> STEEL <input type="checkbox"/> GEARS 2 <input type="checkbox"/> 4 |
| SLIPPER | 2 PAD <input type="checkbox"/> 3 PAD <input checked="" type="checkbox"/> <input type="text"/> mm |

| GEARING | |
|-----------|------|
| PINION | 23 T |
| SPUR GEAR | 78 T |

| GEAR BOX | |
|-----------|---|
| FRONT LCG | <input checked="" type="checkbox"/> REAR LCG <input type="checkbox"/> |

| FRONT | SHOCKS | REAR |
|---|--|--|
| 3dot | SPRINGS | 450 |
| cst 500 | OIL | cst |
| <input checked="" type="checkbox"/> 2 HOLES <input type="checkbox"/> 3 HOLES <input type="checkbox"/> 6 HOLES | PISTONS | <input type="checkbox"/> 2 HOLES <input type="checkbox"/> 3 HOLES <input type="checkbox"/> 6 HOLES |
| <input type="checkbox"/> HOLES | <input checked="" type="checkbox"/> ø1.6mm <input type="checkbox"/> ø1.7mm | <input type="checkbox"/> HOLES |
| DOWNSTOP SHIM | OTHER <input type="text"/> mm | DOWNSTOP SHIM |
| LENGTH 22 mm | | LENGTH 29.5 mm |
| UPSTOP SHIM | OTHER <input type="text"/> mm | UPSTOP SHIM |
| COLLAR STANDARD <input checked="" type="checkbox"/> -2mm | | COLLAR STANDARD <input checked="" type="checkbox"/> -2mm |
| OTHER <input type="text"/> | | OTHER <input type="text"/> |
| <input checked="" type="checkbox"/> KIT BALL JOINT | | <input checked="" type="checkbox"/> KIT |

| FRONT | SHOCK TOWER | REAR |
|--|-------------|--|
| ALU <input type="checkbox"/> GRAPHITE <input type="checkbox"/> | | GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> |

| FRONT | ANTI ROLL BAR | REAR |
|-------|-----------------------------------|------|
| | THICKNESS <input type="text"/> mm | |

| FRONT | TIRES | REAR |
|--------------|----------|---------------|
| inispice Sct | BRAND | aggrer cut sc |
| yellow | COMPOUND | yellow |
| Craig | INSERTS | no insert |
| schumacher | WHEELS | schumacher |

| ELECTRONICS | |
|--------------|--------------------------|
| MOTOR | Hobbywing 7 Hobbywing xi |
| MOTOR TIMING | standard Sunpadow 38 |
| SPEEDO | BATTERY |

| BODY | |
|-------------------|---|
| Gamma 2D (329711) | <input checked="" type="checkbox"/> LIGHT |

| COMMENT | |
|---------|--|
| | |

| FRONT | | APPLIED <input type="radio"/> <input checked="" type="checkbox"/> APPLIED | | REAR | |
|--|--|---|--|---|--|
| STEERING BLOCK | LONGER BUSHINGS | SHIM 1 /mm | | SHIM /mm | |
| MEDIUM <input type="checkbox"/> | UP <input type="checkbox"/> | | | <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU | |
| HARD <input type="checkbox"/> | DOWN <input checked="" type="checkbox"/> | | | | |
| GRAPHITE <input type="checkbox"/> | | | | | |
| CASTER BLOCK | FLAT ARM | SHIM 5 /mm | | SHIM 3 /mm | |
| MEDIUM <input type="checkbox"/> | | DRIVE SHAFT Length 77 /mm | | | |
| HARD <input type="checkbox"/> | | | | | |
| GRAPHITE <input checked="" type="checkbox"/> | | | | | |
| | LSM ARM | XB2D SUSP. ARM | | XB4 SUSP. ARM | |

| FRONT | | WING CUTTING LINE / SIDE LINE | | WING TYPE | |
|--|---|--|--|--|--|
| CASTER BUSHINGS | WING POSITION | SHOCK POSITION | | tec/kit | |
| <input type="checkbox"/> 0° <input checked="" type="checkbox"/> 2.5° <input type="checkbox"/> 5° | YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> | FRONT <input type="checkbox"/> REAR <input type="checkbox"/> | | CENTER FIN YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> | |
| KICK-UP ° | BUMP STEER SHIM 2 /mm | | | WING POSITION | |
| KIT 26° <input checked="" type="checkbox"/> | | | | UP <input checked="" type="checkbox"/> MIDDLE <input type="checkbox"/> DOWN <input type="checkbox"/> | |

| FRONT TOE | | EXTENSION | | REAR TOE | |
|---|------------------------|---|--|---|--|
| 0.5° | OUT | 0 SLOTS <input type="checkbox"/> 1 SLOT <input checked="" type="checkbox"/> 2 SLOTS <input type="checkbox"/> 3 SLOTS <input type="checkbox"/> | | IN | |
| OFFSET kit /slots | WHEELBASE SHIM 2 /mm | BATTERY PLACEMENT | | OFFSET 3 /slots | |
| | | LONG SIDE FRONT 1 2 3 LONG SIDE REAR 1 2 3 | | WHEELBASE SHIM 1 /mm | |
| ROLL CENTER | GUARD BRACE FLEX | BATTERY SIZE | | ROLL CENTER | |
| HARD <input type="checkbox"/> ALU <input checked="" type="checkbox"/> | | STD. SHORT <input type="checkbox"/> LOW SHORT <input checked="" type="checkbox"/> | | HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> | |
| | SERVO HORNS SHIM 2 /mm | UPPER BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> | | | |

| STEERING ARMS | | REAR ROLL CENTER HOLDERS | |
|---|--|---|--|
| HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> | CARPET <input checked="" type="checkbox"/> DIRT <input type="checkbox"/> | ECCENTRIC BUSHINGS | |
| STEERING PLATE | SHIMS 2 /mm | RF 0.5° <input checked="" type="checkbox"/> 1° <input type="checkbox"/> | |
| HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> | | RR 0.5° <input checked="" type="checkbox"/> 1° <input type="checkbox"/> | |

| FRONT CAMBER | | DIFF HEIGHT | | REAR CAMBER | |
|--|--------------------|--------------------|--|--|--|
| 1° | | 0.5° | | | |
| | | | | | |
| FRONT ARM | RIDE HEIGHT 18 /mm | RIDE HEIGHT 18 /mm | | REAR ARM | |
| MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> | #107721 GAUGE | | | MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> | |

| ARM MOUNT | | ECCENTRIC SHOCK BALL | | ARM SHIM | |
|---|---|---|--|--|--|
| COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/> | FRONT <input checked="" type="checkbox"/> REAR <input type="checkbox"/> | FRONT <input checked="" type="checkbox"/> REAR <input type="checkbox"/> | | /mm | |
| CHASSIS BRACE | SERVO POSITION | BALANCE 17 g | | CHASSIS | |
| MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> | | BALANCE 35 g | | SHORT <input type="checkbox"/> MID (KIT) <input checked="" type="checkbox"/> LONG <input type="checkbox"/> | |
| SERVO WEIGHT | | | | CHASSIS FLEX | |
| STANDARD <input type="checkbox"/> LOW PROFILE <input type="checkbox"/> | | | | SCREW USED <input checked="" type="checkbox"/> SCREW NOT USED <input type="checkbox"/> | |