

XRAY XB4'21

FRONT

APPLIED ☒ APPLIED ☒

STEERING BLOCK

MEDIUM ☐
HARD ☐
GRAPHITE ☒

LONGER BUSHINGS

UP ☐
DOWN ☒

SHIM

2 mm

DRIVE SHAFT

CVD ☐ ECS ☒
Length 83 /mm

REAR UPRIGHT

DRIVE SHAFT

Length 75 /mm

SHIM

4 mm

SHIMS

2 /mm

HARD ☐
GRAPHITE ☐
ALU ☒

#325341 ADJ. DRIVE AXLE

1 2 3 4

1° 0.5°

#107711 GAUGE

LOWER SHOCK POSITION

DOWNSTOP

mm

ROLL ENTER

DOWNSTOP

mm

#107711 GAUGE

FRONT

CASTER

6° ☐
9° ☒
12° ☐

CASTER BLOCK

MEDIUM ☐
HARD ☐
GRAPHITE ☒
ALU ☐

WING CUTTING LINE

1 2 3 4 5

OFFSET

Kit /slots

UPRIGHT WHEELBASE

SHIM 1 /mm
IN FRONT OF ARM

WING SIDE LINE

HIGHER ☐
LOWER ☒

WING POSITION

UP ☐
MIDDLE ☐
DOWN ☒

WING THICKNESS

0.75 ☐ 1 ☒ 1.5 ☐

TYPE Kit

FF

FR

RF

RR 2°

1° ☐ 0.5° ☒
1° ☒ 0.5° ☐
1° ☐ 0.5° ☒
1° ☒ 0.5° ☐

ROLL CENTER

ECCENTRIC BUSHINGS

UP ☒ DOWN ☐

FRONT TOE

OUT 1

STEER. PLATE

HARD ☒
GRAPHITE ☐
ALU ☐

BUMP STEER

SHIM 4 mm

Servo SAVER

SOFT ☐
MEDIUM ☐
TIGHT ☒

MATERIAL

STANDARD ☐
GRAPHITE ☐

ARM SHIM

2 mm

REAR TOE

IN

GRAPHITE FOR REAR BRACE

YES ☒
NO ☐

REAR BRACE

MEDIUM ☐
HARD ☒

ARM SHIM

2 mm

FRONT CAMBER

1.5

FRONT DIFF HEIGHT

DOWNSTOP SHIM mm
LENGTH mm
UPSTOP SHIM mm

COLLAR

STANDARD ☒ -2mm

RIDE HEIGHT

16 mm

REAR DIFF HEIGHT

DOWNSTOP SHIM mm
LENGTH mm
UPSTOP SHIM mm

COLLAR

STANDARD ☒ -2mm

RIDE HEIGHT

16 mm

REAR CAMBER

1.5

FRONT ARMS

LONG ☐
SHORT ☒
MEDIUM ☐
HARD ☐
GRAPHITE ☒

T-BRACE

CHASSIS

STANDARD ☒
2.5mm ☐

REAR ARMS

LONG ☐
SHORT ☒
MEDIUM ☐
HARD ☐
GRAPHITE ☒

CHASSIS FLEX

SCREW USED ☒
SCREW NOT USED ☐

SIDE GUARDS

MEDIUM ☐
HARD ☐
CF ☒

FRONT

REAR