

X12'22 SET-UP SHEET VER.1 ©XRAY

X12'22 SET-UP SHEET VER.1 ©XRAY


RACE			
TRACK			
NAME		DATE	2022/11/13

QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
		/sec	/	

TRACK

TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT	
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED	<input checked="" type="checkbox"/> FAST

TRACTION ☐ LOW ☒ MEDIUM ☐ HIGH

CENTER SHOCK ABSORBER		
	CENTER SHOCK OIL	600 /cSt
	CENTER SHOCK REBOUND	50 /%
	CENTER SHOCK SPRING	2.8 /C

SIDE DAMPING



OIL 30000 /cSt

FRONT	TIRES	REAR
BYMS	TIRES TYPE	BYMS
40.8	DIAMETER /mm	41.8
	ADDITIVE	
	ADDITIVE TIMING	

TRANSMISSION		
BALL DIFF <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> LOOSE MEDIUM TIGHT	GEAR DIFF <input type="checkbox"/> <input type="text"/> OIL <input type="text"/> /cSt	SOLID AXLE <input checked="" type="checkbox"/>

GEARING			
PINION / T	37	SPUR GEAR/T	80
FINAL DRIVE RATIO		ROLLOUT	

ELECTRONICS	
MOTOR	19XM
SPEEDO	R1 STOCK
SERVO	SANWA HR
BATTERIES	REEDY 3600

BODY	
TYPE	

COMMENTS

SHOCK Length 66.7mm SRF
Ride Height Spacer BODY 3mm

