

# SET-UP SHEET

X4'23 SET-UP SHEET VER.1 ©XRAY

# XRAY X4'23

RACE	EWS Round 4			
TRACK				
NAME	Kyle Branson	DATE		

QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
4	3	/sec	/	

TRACK			
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT	
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	<input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL 6000 /cSt
PINION 29 /T	SPUR GEAR 110 /T	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
2.4-2.7	XRAY SPRINGS	2.6
400	OIL /cSt	400
	REBOUND %	
<input type="checkbox"/> YES <input type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	1.1mm	1.1mm	4 HOLES	<input checked="" type="checkbox"/>
<input type="checkbox"/> PSS	<input checked="" type="checkbox"/> 1.2mm	1.2mm	<input checked="" type="checkbox"/> PSS	<input type="checkbox"/>
SHOCK LENGTH 8 /mm			SHOCK LENGTH 8 /mm	

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

Rush	TIRES	
MR33 v4	ADDITIVE	
	ADDITIVE TIMING	

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT 1302 /g	WEIGHT BALANCE	FRONT 49 %	REAR 51 %
----------------------	----------------	------------	-----------

MOTOR 5.0 HW	TIMING	
ESC HW G2S	BATTERIES	IP4400
BODY Twister	WING	Twister

67 /mm	Dimension from body post to window bottom line	BODY POSITION
7+oring /mm	Dimension from body post to upper holder	WING SIDE PLATE
		YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
63 /mm	Dimension from edge to surface	

X4'23	1.6mm	2.0mm	1.6mm
X4'22	2.0mm	2.0mm	2.0mm
X4'22	2.0mm	<input checked="" type="checkbox"/> 1.6mm	NONE <input checked="" type="checkbox"/> BEARING

COMMENTS

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
Adjust with eccentric bushings		Adjust with eccentric bushings
UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm		UPPER CLAMP STD. <input type="checkbox"/> -1.5mm
2 /mm FF	5.2 /mm FR	2 /mm RF
RIDE HEIGHT	RIDE HEIGHT	RIDE HEIGHT
	SERVO SAVER	
	SERVO HORN	

2 /deg. CAMBER	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	FRONT SUSPENSION	1.5 /mm SHIM 2 /mm	FRONT HUB
Left = Right	18 /mm			HARD <input checked="" type="checkbox"/>
		FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	FRONT SHOCK POSITION	GRAPHITE <input type="checkbox"/>
		BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm NO <input type="checkbox"/>		ALU <input type="checkbox"/>
		DRIVE SHAFT 58mm 59mm BEARING BLADE		SHIM 0.5 /mm
		#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	6.2 /mm DOWNSTOP

2 /deg. CAMBER	BODY POST VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>	REAR SUSPENSION	1 /mm SHIM 2 /mm	REAR HUB
Left = Right				HARD <input checked="" type="checkbox"/>
		REAR BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	REAR SHOCK POSITION	GRAPHITE <input type="checkbox"/>
		DRIVE SHAFT 52mm 54mm BEARING BLADE		ALU <input type="checkbox"/>
		#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	1.5 /mm SHIM
				4 /mm DOWNSTOP

FRONT TOP VIEW	REAR
1.2 TOE OUT	2.5 TOE IN
Left = Right	Left = Right
ACKERMANN SHIM 0.5 /mm	SHIM /mm
DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>
UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM STD. <input type="checkbox"/>	UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM STD. <input type="checkbox"/>
STEERING BRIDGE YES <input type="checkbox"/> NO <input type="checkbox"/>	STEERING PLATE 8.0mm <input checked="" type="checkbox"/> STD. <input type="checkbox"/> 7.5mm
HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm	HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK 26 /deg.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
STEER. SHIM SIZE 8 /mm	
FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	MOTOR MOUNT
SERVO HOLDER	CHASSIS T-BRACE
FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	CHASSIS GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input checked="" type="checkbox"/>
	REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>