

RACE	practise	
TRACK	RCRT Duisburg	
NAME	Jochen Müller	DATE 2.7.2023

LAPS		BEST LAP TIME	38,0 sec
QUALIFYING POSITION		FINAL POSITION	

TRACK			
SIZE	<input checked="" type="checkbox"/> OPEN	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT
TRACTION	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>		
	VERY-LOW	MEDIUM	VERY-HIGH
SURFACE	<input type="checkbox"/> SMOOTH	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY
TYPE	<input type="checkbox"/> CLAY	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASTRO
CONDITION	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> HARD PACKED	<input checked="" type="checkbox"/> DRY
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY	<input type="checkbox"/> WET

TRANSMISSION			
DIFFERENTIAL	BALL DIFF <input type="checkbox"/>	<input checked="" type="checkbox"/> GEAR DIFF	OIL 5000 cst
SATELLITE GEARS	COMPOSITE <input type="checkbox"/>	<input checked="" type="checkbox"/> STEEL	GEARS 2 <input type="checkbox"/> 4 <input checked="" type="checkbox"/>
SLIPPER	2 PAD <input type="checkbox"/>	<input checked="" type="checkbox"/> 3 PAD	<input type="checkbox"/> ELIMINATOR
			1 mm

GEARING			
PINION	20	SPUR GEAR	78

FRONT	SHOCKS	REAR
2d	SPRINGS	2s
cst 600	OIL	cst 425
<input checked="" type="checkbox"/> 2 HOLES	PISTONS	<input checked="" type="checkbox"/> 2 HOLES
<input type="checkbox"/> 3 HOLES	<input checked="" type="checkbox"/> ø1.6mm	<input type="checkbox"/> 3 HOLES
<input type="checkbox"/> 6 HOLES	<input type="checkbox"/> ø1.7mm	<input type="checkbox"/> 6 HOLES
HOLES		HOLES
DOWNSTOP SHIM		DOWNSTOP SHIM
mm		mm
LENGTH		LENGTH
mm		mm
UPSTOP SHIM		UPSTOP SHIM
3		0
mm		mm
COLLAR	STANDARD	STANDARD
-2mm		-2mm
OTHER	<input checked="" type="checkbox"/> KIT	OTHER
	BALL JOINT	
	<input checked="" type="checkbox"/> KIT	

FRONT	SHOCK TOWER	REAR
COMPOSITE <input checked="" type="checkbox"/>	GRAPHITE <input type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/>
		GRAPHITE <input type="checkbox"/>

ANTI ROLL BARS	
THICKNESS	mm

FRONT	TIRES	REAR
Swaggers	BRAND	Mini Pin
pink	COMPOUND	Y
AKA	INSERTS	Schu. SC
JC	WHEELS	JC

ELECTRONICS		
MOTOR	LRP 6,5t	LRP
MOTOR TIMING	Std	LRP 4600
		SPEEDO
		BATTERY

BODY	
Fusion	

COMMENT	
rear shocks in front of tower Anti-Roll-Bar Front: 2mm Rollcenterholder front: XB2, hole 4(out)	

FRONT	APPLIED <input type="radio"/>	APPLIED <input checked="" type="checkbox"/>	REAR
CASTER BLOCK MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>	UPPER SHOCK POSITION 3 2 1 LOWER SHOCK POSITION 3 2 1		SHIM 2 /mm HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU HIGH <input type="checkbox"/> ALU LOW <input type="checkbox"/>
LONGER BUSHINGS UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>	SHIM 4 mm DRIVE SHAFT Length /mm SHIM 4 mm LOWER SHOCK POSITION 1 2 3 0.5° 1°		1 2 3 4 #325341 ADJ. DRIVE AXLE
STEERING BLOCK MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>	SHIM 2 mm LOWER SHOCK POSITION 1 2 3		1 2 3 4 #325341 ADJ. DRIVE AXLE

FRONT	REAR
CASTER BUSHINGS 0° <input type="checkbox"/> 2.5° <input type="checkbox"/> 5° <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	STEERING ARMS COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
KICK-UP ANGLE 23° <input type="checkbox"/> KIT 26° <input checked="" type="checkbox"/> 29° <input type="checkbox"/>	ROLL CENTER ECCENTRIC BUSHINGS 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>
BUMP STEER SHIM 0 /mm	SHIMS /mm
STEERING PLATE COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	RF 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>
	RR 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>

FRONT	REAR
FRONT TOE 1 OUT 3 SLOTS	REAR TOE 3 IN 3 SLOTS
OFFSET 3 SLOTS	OFFSET 3 SLOTS
WHEELBASE SHIM 0mm <input type="checkbox"/> 1mm <input checked="" type="checkbox"/>	WHEELBASE SHIM 0 /mm IN REAR OF ARM
ROLL CENTER HOLDER HARD <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	COMPOSITE ROLL CENTER ALU <input type="checkbox"/>
SERVO BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	UPPER BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
BATTERY PLACEMENT LONG SIDE FRONT 1 2 3 LONG SIDE REAR 1 2 3	BATTERY SIZE STD. SHORT <input checked="" type="checkbox"/> LOW SHORT <input type="checkbox"/>
GUARD BRACE FLEX 1 2	WHEELPOST HOLDER 1 2 3 4 5

FRONT	REAR
FRONT CAMBER 2	REAR CAMBER 1
FRONT ARM MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>	REAR ARM MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>
DIFF HEIGHT 1 2 3 4 5 6 7 8	DIFF HEIGHT 1 2 3 4 5 6 7 8
FRONT SHOCK POSITION 1 2 3	REAR SHOCK POSITION 1 2 3
FRONT SHOCK POSITION 1 2 3	REAR SHOCK POSITION 1 2 3
FRONT SHOCK POSITION 1 2 3	REAR SHOCK POSITION 1 2 3

FRONT	REAR
ARM MOUNT COMPOSITE <input type="checkbox"/> ALU <input type="checkbox"/> BRASS <input checked="" type="checkbox"/>	ARM SHIM 0 /mm
CHASSIS BRACE MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	CHASSIS ALU <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
SERVO WEIGHT STANDARD <input checked="" type="checkbox"/> LOW PROFILE <input type="checkbox"/>	BALANCE 50 g
SERVO POSITION 1 2 3	BALANCE 50 g
SERVO POSITION 1 2 3	BALANCE 50 g