

XRAY XB4'23

FRONT

ALU C-HUB SHIM
UP ☒ 2 /mm
DOWN _____ /mm

LONGER BUSHINGS
UP ☐
DOWN ☐

DRIVE SHAFT
CVD ☐ ECS ☒
Length 83 /mm

SHIM mm

STEERING BLOCK
MEDIUM ☐
HARD ☐
GRAPHITE ☒

LOWER SHOCK POSITION

DOWNSTOP mm

#107711 GAUGE

APPLIED

REAR UPRIGHT

DRIVE SHAFT
Length 77 /mm

SHIM 2 mm

SHIMS 0 /mm

HARD ☐
GRAPHITE ☒
ALU HIGH ☒
ALU LOW ☐

#325341 ADJ. DRIVE AXLE

1° ☐ 0.5° ☐

#107711 GAUGE

WING CUTTING LINE

1 2 3 4 5

OFFSET 3 /slots

UPRIGHT WHEELBASE
SHIM 0 /mm

IN FRONT OF ARM

WING SIDE LINE

HIGHER ☐
LOWER ☒

WING POSITION
UP ☒
MIDDLE ☐
DOWN ☐

WING THICKNESSES
☐ 0.75 ☒ 1 ☐ 1.5

TYPE JC 6.5

CASTER
6° ☐
7° ☒
9° ☐
12° ☐

CASTER BLOCK
MEDIUM ☐
HARD ☐
GRAPHITE ☐
ALU ☒

BUMP STEER
SHIM 2 mm

OFFSET 2 /slots

ROLL CENTER
ECCENTRIC BUSHINGS
1° ☒ 0.5° ☐
1° ☒ 0.5° ☐

FF

RF

FR

RR2°

UP ☒ DOWN ☐

FRONT TOE
OUT 1 out

STEER. PLATE
HARD ☐
GRAPHITE ☒
ALU ☐

BUMP STEER
SHIM 2 mm
SHIM UNDER STEER. PLATE

Servo SAVER
SOFT ☐
MEDIUM ☐
TIGHT ☒

MATERIAL
STANDARD ☐
GRAPHITE ☒

ARM SHIM 0 mm

REAR TOE
IN 1

GRAPHITE FOR REAR BRACE
YES ☒
NO ☐

REAR BRACE
MEDIUM ☐
HARD ☒

ARM SHIM 2 mm

FRONT CAMBER -2 °

DOWNSTOP
SHIM 0 mm

LENGTH 22.5 mm

UPSTOP
SHIM 0 mm

COLLAR
STANDARD ☒ -2mm

FRONT DIFF HEIGHT
☒ ☐ ☐

RIDE HEIGHT 14 mm

#107720 GAUGE

REAR DIFF HEIGHT
☒ ☐ ☐ ☐ ☐

RIDE HEIGHT 15 mm

REAR CAMBER -2 °

DOWNSTOP
SHIM 0 mm

LENGTH 30 mm

UPSTOP
SHIM 3 mm

COLLAR
STANDARD ☐ -2mm

FRONT ARMS
LONG ☒
SHORT ☐
MEDIUM ☐
HARD ☐
GRAPHITE ☒

BALANCE g

MOTOR MOUNT
FRONT ☒ REAR ☐

T-BRACE

CHASSIS
ALU ☒
GRAPHITE ☐

SIDE GUARDS
HARD ☐
GRAPHITE ☒

BATTERY POSTS
FRONT BATTERY POST
REAR BATTERY POST

BALANCE g

REAR ARMS
LONG ☒
SHORT ☐
MEDIUM ☐
HARD ☐
GRAPHITE ☒

FRONT

REAR