

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	MSP Bohumin rnd.5				
TRACK	Bohumin				
NAME	Martin Hudy		DATE		
QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME	
1st	1st	/sec	/		

TRACK					
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT			
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	<input type="checkbox"/> FAST		
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH		

FRONT		TRANSMISSION		REAR	
GEAR DIFF OIL	/cSt	<input type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL	7k	/cSt
PINION	28	SPUR GEAR	110	FINAL DRIVE RATIO	

FRONT	SHOCKS	REAR
C2.5-2.8	XRAY SPRINGS	C2.7
425	OIL /cSt	425
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm	<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm	<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm
<input checked="" type="checkbox"/> PSS	<input checked="" type="checkbox"/> PSS	<input checked="" type="checkbox"/> PSS
2x0.8	2x0.8	2x0.8
SHOCK LENGTH	8.5 /mm	SHOCK LENGTH
1.3	THICKNESS/mm	1.3

Hudy C3	TIRES	Hudy C3
Hudy Red	ADDITIVE	Hudy Red
10 min	ADDITIVE TIMING	10 min
1 min	WIPE OFF TIME	1 min
Timing:	Temp.:	Timing:
FRONT LEFT	FRONT RIGHT	REAR LEFT
REAR RIGHT	TREATED AREA	

TOTAL WEIGHT	1300	WEIGHT BALANCE	FRONT 49 %	REAR 51 %
--------------	------	----------------	------------	-----------

MOTOR	TIMING
ESC	BATTERIES
BODY	WING
Twister UL	Speciale UL

66 /mm	Dimension from body post to window bottom line	BODY POSITION
7th hole + 2	Dimension from body post to upper holder	WING SIDE PLATE
64 /mm	Dimension from edge to surface	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>

X4'23	1.6mm <input checked="" type="checkbox"/> 2.0mm <input checked="" type="checkbox"/> 1.6mm
X4'22	2.0mm <input type="checkbox"/> 2.0mm <input type="checkbox"/> 1.6mm
X4'22	2.0mm <input type="checkbox"/> 1.6mm <input type="checkbox"/> NONE <input type="checkbox"/> BEARING

COMMENTS

FRONT & REAR SUSPENSION	
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER	SHIM
2 /mm	8 /mm
HEIGHT	SHIM
19 /mm	8 /mm
2.5 /mm	5 /mm
FR 2.5 /mm	RR 3 /mm
<input type="checkbox"/> SERVO SAVER	<input checked="" type="checkbox"/> SERVO HORN
TOE GAIN	TOE IN
1 /mm	3 /mm
SHIM	SHIM
1.5 /mm	2 /mm

FRONT	
2 /deg.	CAMBER
Left = Right	Left = Right
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SHOCK HOLDERS
17.6 /mm	SHIM 6 /mm
SHOCK LENGTH	SUSPENSION FLEX
8.5 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT	DRIVE SHAFT
58mm 59mm	BEARING BLADE
#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge
6.6 /mm	DOWNSTOP

REAR	
2 /deg.	CAMBER
Left = Right	Left = Right
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SHOCK HOLDERS
17.6 /mm	SHIM 6 /mm
SHOCK LENGTH	SUSPENSION FLEX
8.5 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT	DRIVE SHAFT
52mm 54mm	BEARING BLADE
#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge
4.2 /mm	DOWNSTOP

FRONT TOP VIEW		REAR	
1	TOE OUT	3	TOE IN
Left = Right	Left = Right	Left = Right	Left = Right
ACKERMANN	SHIM 0.5 /mm	SHORT LiPo BRASS WEIGHT	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
20	40g	BRASS WEIGHT FOR MOTOR MOUNT	12
40g	10	40g	10
DIFF POSITION	UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> +1mm	DIFF POSITION	UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> +1mm
UPPER ARM	SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>	UPPER ARM	SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>
STEERING BRIDGE	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	STEERING	SHIM /mm
HUB OFFSET	STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm	HUB OFFSET	STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm

FRONT BOTTOM VIEW		REAR	
26 /deg.	STEER. LOCK	T-BRACE	ALU BRASS
FR	RE	CHASSIS T-BRACE	
SERVO HOLDER	MOTOR MOUNT	FRONT ARMS	REAR ARMS
GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU 1.5mm <input checked="" type="checkbox"/>	GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU 1.5mm <input checked="" type="checkbox"/>	GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU 1.5mm <input checked="" type="checkbox"/>	GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU 1.5mm <input checked="" type="checkbox"/>