

# SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

# XRAY X4'24

RACE	test				
TRACK	soda city				
NAME	Cory Craig		DATE		
QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME	
		/sec	/		

TRACK			
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT	
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	<input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH

FRONT		TRANSMISSION		REAR	
GEAR DIFF OIL	/cSt	<input checked="" type="checkbox"/> FRONT SOLID AXLE		GEAR DIFF OIL	10 /cSt
PINION	/T	SPUR GEAR	/T	FINAL DRIVE RATIO	

FRONT	SHOCKS	REAR
2.4-2.7	XRAY SPRINGS	2.5
450	OIL /cSt	450
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm	<input checked="" type="checkbox"/> PSS <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm	<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm
2 x 0.8		2 x 0.8
SHOCK LENGTH 8.0 /mm		SHOCK LENGTH 8.0 /mm

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.3
Gravity USGT		TIRES	Gravity USGT	
sxt black		ADDITIVE	sxt black	
3 min		ADDITIVE TIMING	3 min	
Timing:		WIPE OFF TIME	Timing:	
Temp.:		TIRE WARMERS	Temp.:	
FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT	1355 /g	WEIGHT BALANCE	FRONT %	REAR %
MOTOR	Gravity USGT	TIMING	Locked	
ESC	Tekin	BATTERIES	Motiv Defy ULP	
BODY	Super Rad SR-30	WING	Super Rad	

BODY POSITION	
Dimension from body post to window bottom line	/mm
WING SIDE PLATE	
YES <input type="checkbox"/> NO <input type="checkbox"/>	
Dimension from body post to upper holder	/mm
Dimension from edge to surface	/mm

X4'23	1.6mm <input checked="" type="checkbox"/> 2.0mm <input checked="" type="checkbox"/> 1.6mm
X4'22	2.0mm <input type="checkbox"/> 2.0mm <input type="checkbox"/> 1.6mm
X4'22	2.0mm <input type="checkbox"/> 1.6mm <input type="checkbox"/> NONE <input type="checkbox"/> BEARING

COMMENTS
----------

FRONT & REAR SUSPENSION	
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER 2.5 /mm	HEIGHT 15 /mm
SHIM 6 /mm	
2.0 /mm FF	5.2 /mm FR
2.0 /mm	2.0 /mm
<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT
<input type="checkbox"/> SERVO SAVER	<input type="checkbox"/> SERVO HORN
TOE GAIN 1 /mm	2.5 /mm RF
	5.4 /mm RR
	2.5 /mm

FRONT	
-1 /deg. CAMBER	Left = Right
BODY STOP	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
SHOCK HOLDERS	SHIM 3 /mm
SUSPENSION FLEX	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT	58mm <input checked="" type="checkbox"/> 59mm <input type="checkbox"/> BEARING <input checked="" type="checkbox"/> BLADE <input type="checkbox"/>
#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge
3.5 /mm SHIM	3 /mm
FRONT HUB	MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>
SHIM 0.5 /mm	
DOWNSTOP	/mm

REAR	
-2 /deg. CAMBER	Left = Right
BODY POST	VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>
SHOCK HOLDERS	FIXED <input checked="" type="checkbox"/> ACTIVE <input type="checkbox"/>
SUSPENSION FLEX	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT	52mm <input checked="" type="checkbox"/> 54mm <input type="checkbox"/> BEARING <input checked="" type="checkbox"/> BLADE <input type="checkbox"/>
#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge
1 /mm SHIM	3 /mm
REAR HUB	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
SHIM 1 /mm	
DOWNSTOP	/mm

FRONT TOP VIEW		REAR	
TOE OUT	Left = Right	TOE IN	Left = Right
ACKERMANN	SHIM 0.5 /mm	SHORT LiPo BRASS WEIGHT	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DIFF POSITION	<input type="checkbox"/> UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> +1mm	BRASS WEIGHT FOR MOTOR MOUNT	12 40g
UPPER ARM	SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/>	SHIM	/mm
HUB OFFSET	STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm	STEERING	SHIM/mm
		STEERING BRIDGE	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
		PLATE	8.0mm <input checked="" type="checkbox"/> 7.5mm <input type="checkbox"/> STD.
		HUB OFFSET	STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm

FRONT BOTTOM VIEW		REAR	
STEER. LOCK	/deg.	T-BRACE	ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
MOTOR MOUNT	FR RE	CHASSIS T-BRACE	
SERVO HOLDER		FRONT ARMS	MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>
CHASSIS	GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU 1.5mm <input type="checkbox"/>	REAR ARMS	MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>