

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	practice				
TRACK	simara				
NAME	huanglaoxie		DATE		
QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME	
		17.7 /sec		/	

TRACK		
TRACK SURFACE	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT		TRANSMISSION		REAR	
GEAR DIFF OIL	/cSt	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL	9k	/cSt
PINION	36 /T	SPUR GEAR	100 /T	FINAL DRIVE RATIO	5.28

FRONT		SHOCKS		REAR	
2.5-2.8		XRAY SPRINGS		2.8	
400		OIL /cSt		400	
0		REBOUND %		0	
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO			

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm
SHOCK LENGTH		8.5 /mm	SHOCK LENGTH	
1.2		THICKNESS/mm	ANTI-ROLL BAR	
1.2		THICKNESS/mm		

rush 36x		TIRES		rush 36x	
simara alpha		ADDITIVE		simara alpha	
		ADDITIVE TIMING			
		WIPE OFF TIME			
Timing: 10		Temp.:		Timing: 10	
Temp.:				Temp.:	
FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT	TREATED AREA	

TOTAL WEIGHT	1320 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
--------------	---------	----------------	------------	-----------

MOTOR	g4 bandit	TIMING	43
ESC	xr10 g2s	BATTERIES	6100 lrp
BODY	twister UL	WING	twister L

66.5 /mm	Dimension from body post to window bottom line	BODY POSITION
WING SIDE PLATE	YES <input type="checkbox"/> NO <input type="checkbox"/>	
Dimension from body post to upper holder		
Dimension from edge to surface	/mm	

X4'23	1.6mm <input type="checkbox"/> 2.0mm <input type="checkbox"/> 1.6mm	
X4'22	2.0mm <input checked="" type="checkbox"/> 1.6mm	
X4'22	2.0mm <input type="checkbox"/> 1.6mm	
	NONE <input type="checkbox"/> BEARING <input type="checkbox"/>	

COMMENTS

FRONT & REAR SUSPENSION	
FRONT CASTER <input type="checkbox"/> 5° <input checked="" type="checkbox"/> 4° <input type="checkbox"/> 3° Adjust with eccentric bushings	REAR CASTER <input type="checkbox"/> 0.5° <input type="checkbox"/> 1.5° <input checked="" type="checkbox"/> 2.5° <input type="checkbox"/> 3.5° <input type="checkbox"/> 4.5° <input type="checkbox"/> 5.5° Adjust with eccentric bushings
BUMP STEER 2 /mm	HEIGHT 19 /mm
SHIM 7 /mm	
2.5 /mm FF 5 /mm RIDE HEIGHT FR 2.5 /mm	TOE GAIN 1.5 /mm 3 /mm RF 5.2 /mm RIDE HEIGHT RR 3 /mm
<input type="checkbox"/> SERVO SAVER <input checked="" type="checkbox"/> SERVO HORN	

FRONT	
2 /deg. CAMBER Left = Right	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> /mm
SHOCK HOLDERS SHIM 2 /mm	SHIM 1 /mm SHIM 2 /mm
SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	FRONT HUB MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>
DRIVE SHAFT <input checked="" type="checkbox"/> 58mm <input type="checkbox"/> 59mm <input checked="" type="checkbox"/> BEARING BLADE	SHIM 0.5 /mm
#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5.8 /mm DOWNSTOP	

REAR	
2 /deg. CAMBER Left = Right	BODY POST VERTICAL <input checked="" type="checkbox"/> HORIZONTAL <input type="checkbox"/>
SHOCK HOLDERS FIXED <input checked="" type="checkbox"/> ACTIVE <input type="checkbox"/> SHIM 2 /mm	SHIM 0.5 /mm SHIM 2 /mm
SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	REAR HUB MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>
DRIVE SHAFT <input type="checkbox"/> 52mm <input checked="" type="checkbox"/> 54mm <input checked="" type="checkbox"/> BEARING BLADE	SHIM 0.5 /mm
#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4.4 /mm DOWNSTOP	

FRONT TOP VIEW		REAR	
1 TOE OUT Left = Right	ACKERMANN SHIM 1 /mm	2.5 TOE IN Left = Right	SHORT LiPo BRASS WEIGHT YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm	BRASS WEIGHT FOR MOTOR MOUNT 40g	DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm	UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>
HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm	STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	STEERING SHIM/mm 0 SIZE <input checked="" type="checkbox"/> 8.0mm 7.5mm STD.	HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm

FRONT BOTTOM VIEW		REAR	
STEER. LOCK 26 /deg.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>	MOTOR MOUNT FR RE	SERVO HOLDER
FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	CHASSIS GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU 1.5mm <input type="checkbox"/>	REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	CHASSIS T-BRACE