

SET-UP SHEET

VER.01 ©XRAY

XRAY X4F'23

RACE	Dutch Nariional Round 2		
TRACK	RC HotWheels Deventer		
NAME	Patrick Jongenelis	DATE	26-05-2024

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAP/TIME	LAPS	TIME
20	1	1	19.665 /sec	21	7:02,612

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input checked="" type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH
FRONT	TRANSMISSION
GEAR DIFFERENTIAL - OIL	200K /cst

PINION / T	SPUR GEAR / T	FINAL DRIVE RATIO
38	90	4.50

FRONT	SHOCKS	REAR
2.8 / 3.0	XRAY SPRINGS	2.6
350	OIL /Cst	350
5%	REBOUND %	5%
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS	PISTONS 1.0mm <input type="checkbox"/> 1.1mm <input checked="" type="checkbox"/> 1.2mm <input type="checkbox"/>	<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS
SHOCK LENGTH FRONT		SHOCK LENGTH REAR
8,5 /mm		10 /mm

1,3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1,3
Ride (26082)	TIRES	Ride (26082)		
CS High	ADDITIVE	CS High		
30 min	ADDITIVE TIMING	30 min		

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT	1275 /g	WEIGHT BALANCE	FRONT 63 % REAR 37 %
--------------	---------	----------------	----------------------

MOTOR	17,5T HW ETS	TIMING
-------	--------------	--------

ESC	HW XR10 Justock	BATTERIES	LRP 3700
-----	-----------------	-----------	----------

BODY	Gorilla MAX	WING	std
------	-------------	------	-----

68 /mm	Dimension from body post to window bottom line	BODY POSITION
35 /mm	Dimension from body post to upper holder	WING SIDE PLATE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
61 /mm	Dimension from edge to surface	

COMMENTS
 Too Gain rear arms are the front steering arms from the X4-22.
 Front Caster is the 2 dot point too the front is 7 Deg.
 All oils HUDY

FRONT CASTER	BUMP STEER	HEIGHT	SHIM	FRONT & REAR SUSPENSION	REAR CASTER	TOE GAIN
Adjust with eccentric bushings	2 /mm	18,5 /mm	8,5 /mm		Adjust with eccentric bushings	4 /mm
0,5 /mm FF	5 /mm	FR 0,5 /mm	<input type="checkbox"/> SERVO SAVER		2 /mm RF	5,2 /mm
<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> SERVO HORN		<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT

FRONT CAMBER	FRONT SUSPENSION	FRONT HUB
1,75 /deg. Left=Right	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> BULKHEAD SHIMS YES <input type="checkbox"/> 3mm <input type="checkbox"/> NO <input type="checkbox"/> DRIVE SHAFT <input checked="" type="checkbox"/> 58mm <input type="checkbox"/> 59mm <input checked="" type="checkbox"/> STD. BEARING	SHIM 0,5 /mm COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
	#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5 /mm DOWNSTOP	

REAR CAMBER	REAR SUSPENSION	REAR HUB
2,5 /deg. Left=Right	SHIM 3 /mm REAR SHOCK POSITION #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 2 /mm DOWNSTOP	SHIM 2,5 /mm COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>

FRONT TOP VIEW	REAR TOP VIEW
0,5 TOE OUT Left=Right ACKERMANN SHIM 0 /mm DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> UPPER ARM STANDARD <input checked="" type="checkbox"/> OFFSET STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm TOP DECK <input checked="" type="checkbox"/> SPLITTED STEERING BRIDGE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	2,5 TOE IN Left=Right UPPER ARM STANDARD <input checked="" type="checkbox"/> OFFSET STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm TOP DECK CUTTING

FRONT BOTTOM VIEW	REAR BOTTOM VIEW
STEER. LOCK 25 /deg. STEER. SHIM SIZE std /mm FRONT BRACE YES <input type="checkbox"/> NO <input type="checkbox"/> FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/> MOTOR MOUNT CHASSIS T-BRACE REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>
STEER. PLATE STANDARD <input checked="" type="checkbox"/>	CHASSIS GRAPHITE <input checked="" type="checkbox"/>