

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	Jakarta State Rd.2				
TRACK	East RC				
NAME	Bowie	DATE	23/06/2024		
QUAL POSITION	1st	FINAL POSITION	1st	BEST LAPTIME	13.7 /sec
LAPS	/				

TRACK		
TRACK SURFACE	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL
PINION	SPUR GEAR	FINAL DRIVE RATIO
32 /T	110 /T	6.5

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
375	OIL /Cst	400
10	REBOUND %	10
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH		SHOCK LENGTH	
8.0 /mm		8.0 /mm	

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

TP ITC 2023	TIRES
MG Yellow	ADDITIVE
5 Mins	ADDITIVE TIMING
	WIPE OFF TIME
	TIRE WARMERS
Timing:	Temp.:
FRONT LEFT	FRONT RIGHT
REAR LEFT	REAR RIGHT
TREATED AREA	

TOTAL WEIGHT	1322 /g	WEIGHT BALANCE	FRONT 49 %	REAR 51 %
--------------	---------	----------------	------------	-----------

MOTOR	Insane 4 13.5	TIMING	46
ESC	Zombie TZ-01	BATTERIES	Zombie 6250
BODY	Twister L	WING	Twister L

66 /mm	Dimension from body post to window bottom line	BODY POSITION
7+oring	Dimension from body post to upper holder	WING SIDE PLATE
		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
65 /mm	Dimension from edge to surface	

X4'23	<input checked="" type="checkbox"/>	1.6mm	<input checked="" type="checkbox"/>	2.0mm	<input checked="" type="checkbox"/>	1.6mm
X4'22	<input type="checkbox"/>	2.0mm	<input type="checkbox"/>	2.0mm	<input type="checkbox"/>	1.6mm
X4'22	<input type="checkbox"/>	2.0mm	<input type="checkbox"/>	1.6mm	<input type="checkbox"/>	NONE
TOP DECK CUTTING						

COMMENTS

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
Adjust with eccentric bushings	BUMP STEER	Adjust with eccentric bushings
5° 4° 3°	HEIGHT	0.5° 1.5° 2.5° 3.5° 4.5° 5.5°
2 /mm	SHIM	
19 /mm	5 /mm	
2.0 /mm FF	FR 2.5 /mm	TOE GAIN
5.0 /mm	SHIM	2.5 /mm RF
FRIDE HEIGHT	SERVO SAVER	5.2 /mm RR
	SERVO HORN	2.5 /mm

FRONT	SHOCK HOLDERS	SHOCK FLEX	DRIVE SHAFT	FRONT HUB
2 /deg. CAMBER	SHIM	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	58mm 59mm	MEDIUM <input type="checkbox"/>
Left = Right	3 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	BEARING BLADE	HARD <input type="checkbox"/>
BODY STOP		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		GRAPHITE <input checked="" type="checkbox"/>
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		ALU <input type="checkbox"/>
				SHIM
				0.5 /mm

REAR	SHOCK HOLDERS	SHOCK FLEX	DRIVE SHAFT	REAR HUB
2 /deg. CAMBER	SHIM	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	52mm 54mm	MEDIUM <input type="checkbox"/>
Left = Right	3 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	BEARING BLADE	HARD <input type="checkbox"/>
BODY POST		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		GRAPHITE <input checked="" type="checkbox"/>
VERTICAL <input checked="" type="checkbox"/>		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		ALU <input type="checkbox"/>
HORIZONTAL <input type="checkbox"/>				SHIM
				0.5 /mm

FRONT TOP VIEW	REAR TOP VIEW
1.0 TOE OUT	2.5 TOE IN
Left = Right	Left = Right
ACKERMANN	SHORT LiPo BRASS WEIGHT
SHIM	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
40g	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
BRASS WEIGHT FOR MOTOR MOUNT	
40g	
DIFF POSITION	DIFF POSITION
<input checked="" type="checkbox"/> UP	<input checked="" type="checkbox"/> UP
<input type="checkbox"/> DOWN	<input type="checkbox"/> DOWN
<input type="checkbox"/> +1mm	<input type="checkbox"/> +1mm
UPPER ARM	UPPER ARM
SOFT <input checked="" type="checkbox"/>	SOFT <input checked="" type="checkbox"/>
MEDIUM <input type="checkbox"/>	MEDIUM <input type="checkbox"/>
STEERING BRIDGE	STEERING
YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	SHIM /mm
	PLATE
	8.0mm 7.5mm
HUB OFFSET	HUB OFFSET
STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm	STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm
SHIM /mm	SHIM /mm

FRONT BOTTOM VIEW	REAR BOTTOM VIEW
STEER. LOCK	T-BRACE
26 /deg.	ALU BRASS
FR RE	CHASSIS T-BRACE
SERVO HOLDER	
MOTOR MOUNT	
FRONT ARMS	REAR ARMS
MEDIUM <input checked="" type="checkbox"/>	MEDIUM <input checked="" type="checkbox"/>
HARD <input type="checkbox"/>	HARD <input type="checkbox"/>
CHASSIS	
GRAPHITE <input checked="" type="checkbox"/>	
ALU	
ALU 1.5mm	