

# SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

# XRAY X4'24

RACE	ACI Italian championship final				
TRACK	Road Race Riccione				
NAME	Orlando Fenili	DATE	21-22/09/24		
QUAL POSITION	5	FINAL POSITION	5	BEST LAPTIME	17.7 /sec
LAPS	17 / 5:12:0				

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input checked="" type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT		TRANSMISSION		REAR	
GEAR DIFF OIL	/cSt	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL	6000	/cSt
PINION	46 /T	SPUR GEAR	90 /T	FINAL DRIVE RATIO	3.71

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
375	OIL /cSt	375
REBOUND %		

<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm	<input type="checkbox"/> 1.1mm	<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm
<input type="checkbox"/> PSS <input checked="" type="checkbox"/> 1.2mm	<input checked="" type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS <input type="checkbox"/> 1.2mm

SHOCK LENGTH	8 /mm	SHOCK LENGTH	8 /mm
1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm
1.3			

Hot Race 36	TIRES	Hot Race 36	
Trinity Red Dot	ADDITIVE	Trinity Red Dot	
10 min	ADDITIVE TIMING	10 min	
2min	WIPE OFF TIME	2min	
Timing: 10	TEMP.: 80°C	Timing: 10	
Temp.: 80°C		Temp.: 80°C	
FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT	1304 /g	WEIGHT BALANCE	FRONT 50 % REAR 50 %
--------------	---------	----------------	----------------------

MOTOR	HW G4R 17.5	TIMING	58°
ESC	LRP FLOW X	BATTERIES	LRP 5100 G4.1
BODY	Speciale UL	WING	Twister UL

63 /mm	Dimension from body post to window bottom line	BODY POSITION
7+0+o-ring	Dimension from body post to upper holder	WING SIDE PLATE
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		
64 /mm	Dimension from edge to surface	

1.6mm <input checked="" type="checkbox"/> 2.0mm <input checked="" type="checkbox"/> 1.6mm
X4'23 <input checked="" type="checkbox"/> X4'22 <input type="checkbox"/> X4'22 <input type="checkbox"/>
2.0mm <input type="checkbox"/> 1.6mm <input type="checkbox"/>
NONE <input type="checkbox"/> BEARING <input type="checkbox"/>
TOP DECK CUTTING

10g in front of motor mount,  
T-Works adjustable servo horn

FRONT CASTER		FRONT & REAR SUSPENSION		REAR CASTER	
5° <input checked="" type="checkbox"/> 4° <input type="checkbox"/> 3° <input type="checkbox"/>	Adjust with eccentric bushings	BUMP STEER	HEIGHT	SHIM	Adjust with eccentric bushings
2 /mm	19 /mm	1 /mm			
1 /mm	5.4 /mm	FR 1 /mm	<input type="checkbox"/> SERVO SAVER	TOE GAIN	1.5 /mm
<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> SERVO HORN			3 /mm	

FRONT		SHOCK HOLDERS		FRONT HUB	
2 /deg.	CAMBER	SHIM	2 /mm	1.5 /mm	SHIM
Left = Right		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		3 /mm	
18.5 /mm					

FRONT		SHOCK HOLDERS		FRONT HUB	
2 /deg.	CAMBER	SHIM	2 /mm	0.5 /mm	SHIM
Left = Right		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		3 /mm	

FRONT TOP VIEW		REAR TOP VIEW	
1.5	TOE OUT	3	TOE IN
Left = Right		Left = Right	
ACKERMANN	SHIM 0.5 /mm	SHORT LiPo BRASS WEIGHT	YES <input type="checkbox"/> NO <input type="checkbox"/>

FRONT BOTTOM VIEW		REAR BOTTOM VIEW	
STEER. LOCK	25.5 /deg.	T-BRACE	ALU <input type="checkbox"/> BRASS <input type="checkbox"/>