

# SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

# XRAY X4'24

RACE	Indonesia Nats 2024				
TRACK	East RC				
NAME	Bowie	DATE	22/09/2024		
QUAL POSITION	1st	FINAL POSITION	1st	BEST LAPTIME	14.3 /sec
LAPS	/				

TRACK		
TRACK SURFACE	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL
PINION	33 /T	SPUR GEAR
	110 /T	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
2.7	XRAY SPRINGS	2.7
425	OIL /Cst	425
25	REBOUND %	25 - oring limit

<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
<input checked="" type="checkbox"/> 4 HOLES	1.1mm	1.1mm
<input type="checkbox"/> PSS	1.2mm	1.2mm

SHOCK LENGTH	8.5 /mm	SHOCK LENGTH	8.5 /mm
--------------	---------	--------------	---------

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

TP ITC 2023	TIRES
MG Yellow	ADDITIVE
5 mins	ADDITIVE TIMING
	WIPE OFF TIME
	TIRE WARMERS
Timing:	Temp.:
FRONT LEFT	FRONT RIGHT
REAR LEFT	REAR RIGHT
TREATED AREA	

TOTAL WEIGHT	1318 /g	WEIGHT BALANCE	FRONT 49 %	REAR 51 %
--------------	---------	----------------	------------	-----------

MOTOR	Zombie Insane IV	TIMING	46
ESC	XR10	BATTERIES	Zombie 6250
BODY	Speciale UL	WING	Twister L

65 /mm	Dimension from body post to window bottom line	BODY POSITION
7+2 oring	Dimension from body post to upper holder	WING SIDE PLATE
65 /mm	Dimension from edge to surface	

1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm
2.0mm	<input type="checkbox"/> 1.6mm	
NONE	<input type="checkbox"/> BEARING	

Rear Topdeck on Front (Cut bridge)  
Steering link used as rear brace

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
Adjust with eccentric bushings	BUMP STEER 2 /mm	Adjust with eccentric bushings
5° 4° 3°	HEIGHT 19 /mm	0.5° 1.5° 2.5° 3.5° 4.5° 5.5°
	SHIM 4 /mm	
1.5 /mm	FR 2 /mm	TOE GAIN 1.5 /mm
5.0 /mm	SERVO SAVER	2.5 /mm
FRIDE HEIGHT	SERVO HORN	5.4 /mm
		RR 2.5 /mm

FRONT	SHOCK HOLDERS	SHOCK FLEX	DRIVE SHAFT	FRONT HUB
1.25 /deg. CAMBER	SHIM 2.5 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	58mm 59mm	MEDIUM <input type="checkbox"/>
Left = Right		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	BEARING BLADE	HARD <input type="checkbox"/>
		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		GRAPHITE <input checked="" type="checkbox"/>
				ALU <input type="checkbox"/>
				SHIM 0.5 /mm

REAR	SHOCK HOLDERS	SHOCK FLEX	DRIVE SHAFT	REAR HUB
0.5 /mm	SHIM 2.5 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	52mm 54mm	MEDIUM <input type="checkbox"/>
		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	BEARING BLADE	HARD <input type="checkbox"/>
		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		GRAPHITE <input type="checkbox"/>
				ALU <input type="checkbox"/>
				SHIM 0.5 /mm

FRONT TOP VIEW	REAR TOP VIEW
1 /deg. CAMBER	2.75 /deg. CAMBER
Left = Right	Left = Right
TOE OUT	TOE IN
ACKERMANN	SHORT LiPo BRASS WEIGHT
SHIM 1 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DIFF POSITION	DIFF POSITION
<input checked="" type="checkbox"/> UP	<input checked="" type="checkbox"/> UP
<input type="checkbox"/> DOWN	<input type="checkbox"/> DOWN
<input type="checkbox"/> +1mm	<input type="checkbox"/> +1mm
UPPER ARM	UPPER ARM
SOFT <input checked="" type="checkbox"/>	SOFT <input checked="" type="checkbox"/>
MEDIUM <input type="checkbox"/>	MEDIUM <input type="checkbox"/>
STEERING BRIDGE	STEERING
YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	SHIM /mm
	8.0mm 7.5mm
HUB OFFSET	HUB OFFSET
STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm	STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm

FRONT BOTTOM VIEW	REAR BOTTOM VIEW
STEER. LOCK 25 /deg.	T-BRACE
	ALU <input type="checkbox"/>
	BRASS <input type="checkbox"/>
MOTOR MOUNT	CHASSIS T-BRACE
SERVO HOLDER	
FRONT ARMS	REAR ARMS
MEDIUM <input type="checkbox"/>	MEDIUM <input type="checkbox"/>
HARD <input type="checkbox"/>	HARD <input type="checkbox"/>
XG	XG