

# XRAY XB4'22

**FRONT**
APPLIED ☒ APPLIED ☒
**REAR**

---

**ALU C-HUB SHIM**

UP /mm  
DOWN **2** /mm

**STEERING BLOCK**

☒ ALU  
☐ MEDIUM  
☐ HARD  
☐ GRAPHITE

#107711 GAUGE

**LONGER BUSHINGS**

UP ☐  
DOWN ☐

**DRIVE SHAFT**

CVD ☐ ☒ ECS  
Lenght **83** /mm

**SHIM**

**1** mm

LOWER SHOCK POSITION

HUGOY #107701 SUPPORT BLOCKS

**DOWNSTOP**

mm

---

**CASTER**

6° ☐  
7° ☒  
9° ☐  
12° ☐

**CASTER BLOCK**

MEDIUM ☐  
HARD ☐  
GRAPHITE ☐  
ALU ☒

**BUMP STEER**

SHIM **0** mm

**OFFSET**

**2slot**

**WING CUTTING LINE**

☒ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5

**OFFSET**

**3slot** /slots

**UPRIGHT WHEELBASE**

SHIM **2** /mm  
IN FRONT OF ARM

---

**FF**

☒ 1°  
☐ 0.5°

**FR**

☒ 1°  
☐ 0.5°

**ROLL CENTER**

ECCENTRIC BUSHINGS

**RF**

☒ 1°  
☐ 0.5°

**RR 2°**

☐ UP ☐ DOWN

---

**FRONT TOE**

**1° Out**

**STEER. PLATE**

HARD ☐  
GRAPHITE ☒  
ALU ☐  
**BUMP STEER**
SHIM **2** mm  
SHIM UNDER STEER. PLATE

**SERVO SAVER**

SOFT ☐  
MEDIUM ☐  
TIGHT ☒

**MATERIAL**

STANDARD ☐  
GRAPHITE ☒

**ARM SHIM**

**2** mm

**REAR TOE**

**2**

**GRAPHITE FOR REAR BRACE**

YES ☒  
NO ☐

**REAR BRACE**

MEDIUM ☐  
HARD ☒

**ARM SHIM**

**2** mm

---

**FRONT CAMBER**

**-3**

**DOWNSTOP**

SHIM **0** mm

**LENGTH**

**22.5** mm

**UPSTOP**

SHIM **2** mm

**COLLAR**

STANDARD ☒ -2mm

**FRONT DIFF HEIGHT**

☒ ☐ ☐

**RIDE HEIGHT**

**12** mm

---

**REAR DIFF HEIGHT**

☒ ☐ ☐ ☐ ☐ ☐

**RIDE HEIGHT**

**12** mm

**REAR CAMBER**

**-3**

**DOWNSTOP**

SHIM **0** mm

**LENGTH**

**29** mm

**UPSTOP**

SHIM **1** mm

**COLLAR**

STANDARD ☐ ☒ -2mm

---

**FRONT ARMS**

LONG ☐  
SHORT ☒  
MEDIUM ☐  
HARD ☐  
GRAPHITE ☒

**BALANCE**

g

**T-BRACE**

☒ ☐ ☐ ☐

**FRONT BATTERY POST**

☒ 1 ☐ 2 ☐ 3

**BALANCE**

g

**SIDE GUARDS**

HARD ☐  
GRAPHITE ☒

**BALANCE**

g

**REAR BATTERY POST**

☒ 1 ☐ 2 ☐ 3 ☐ 4

**BALANCE**

g

---

**REAR ARMS**

LONG ☒  
SHORT ☐  
MEDIUM ☐  
HARD ☐  
GRAPHITE ☒

**CHASSIS FLEX**

☒ SCREW USED  
☐ SCREW NOT USED