

SET-UP SHEET

XT2'23 SET-UP SHEET VER. 1 ©XRAY 2022

XRAY XT2'23

RACE	Postal Railroad - Spring Explosion		
TRACK	Shaffer's Full Steam Ahead Hobby		
NAME	Don Corbett	DATE	2/4/23

LAPS	34	BEST LAP TIME	11.9 sec
QUALIFYING POSITION	1	FINAL POSITION	

TRACK			
SIZE	<input type="checkbox"/> OPEN	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> TIGHT
TRACTION	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>		
	VERY-LOW	MEDIUM	VERY-HIGH
SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY
TYPE	<input type="checkbox"/> CLAY	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASTRO
CONDITION	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> HARD PACKED	<input type="checkbox"/> DRY
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY	<input type="checkbox"/> WET

TRANSMISSION			
DIFFERENTIAL	BALL DIFF <input type="checkbox"/>	<input checked="" type="checkbox"/> GEAR DIFF	OIL 30k cst
SATELLITE GEARS	COMPOSITE <input checked="" type="checkbox"/>	STEEL <input type="checkbox"/>	GEARS 2 <input checked="" type="checkbox"/> 4 <input type="checkbox"/>
SLIPPER	2 PAD <input type="checkbox"/>	3 PAD <input type="checkbox"/>	ELIMINATOR <input checked="" type="checkbox"/>

GEARING			
PINION	25 T	SPUR GEAR	78 T

FRONT	SHOCKS	REAR
4 dot	SPRINGS	3 dot
cst 800	OIL	cst 500
<input checked="" type="checkbox"/> 2 HOLES <input type="checkbox"/> 3 HOLES <input type="checkbox"/> 6 HOLES <input type="checkbox"/> HOLES	PISTONS <input type="checkbox"/> ø1.2mm <input type="checkbox"/> ø1.3mm <input checked="" type="checkbox"/> ø1.4mm <input type="checkbox"/> ø1.6mm <input checked="" type="checkbox"/> ø1.7mm <input type="checkbox"/> ø mm ø mm	<input checked="" type="checkbox"/> 2 HOLES <input type="checkbox"/> 3 HOLES <input type="checkbox"/> 6 HOLES <input type="checkbox"/> HOLES
DOWNSTOP SHIM		DOWNSTOP SHIM
LENGTH 29 mm		LENGTH 36 mm
UPSTOP SHIM		UPSTOP SHIM
2 mm		3 mm
KIT <input checked="" type="checkbox"/>	BALL JOINT	KIT <input checked="" type="checkbox"/>

FRONT	ANTI ROLL BARS	REAR
1.8 mm	THICKNESS	1.1 mm

FRONT	TIRES	REAR
Swagger	BRAND	Pin Down
	COMPOUND	
	INSERTS	
	WHEELS	Xray

ELECTRONICS			
MOTOR	13.5 Reds	Reds	SPEEDO
MOTOR TIMING	Alot	LCG	BATTERY

BODY			
1mm <input checked="" type="checkbox"/>	<input type="checkbox"/> 0.75mm LIGHT	OTHER	

COMMENT	
Gray EOS Style Carpet	

FRONT		APPLIED <input type="checkbox"/> <input checked="" type="checkbox"/> APPLIED		REAR	
LONGER BUSHINGS	UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	8 7 6 5 4 3 2 1 GRAPHITE SHOCK TOWER POSITION 4 5 6 3 2 1	SHIM 2 /mm <input checked="" type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU HIGH <input type="checkbox"/> ALU LOW	DRIVE SHAFT <input checked="" type="checkbox"/> CVD <input type="checkbox"/> ECS Length 94 /mm	SHIM 0 mm <input type="checkbox"/> 0.5° <input type="checkbox"/> 1°
STEERING BLOCK	MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	CAMBER LINK LOCATION 3 2 1 LOWER SHOCK POSITION SHIM 2 mm	SHIM 4 mm LOWER SHOCK POSITION SHIM 2 mm	SHIM 0 mm LOWER SHOCK POSITION SHIM 2 mm	SHIM 0 mm LOWER SHOCK POSITION SHIM 2 mm

FRONT		REAR	
CASTER BUSHINGS	0° <input checked="" type="checkbox"/> 2.5° <input type="checkbox"/> 5° <input type="checkbox"/> OTHER <input type="checkbox"/>	STEERING ARMS <input checked="" type="checkbox"/> COMPOSITE <input type="checkbox"/> ALU	ROLL CENTER ECCENTRIC BUSHINGS 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>
KICK-UP ANGLE <input type="checkbox"/> 23° <input checked="" type="checkbox"/> KIT 26° <input type="checkbox"/> 29°	BUMP STEER SHIM 0 /mm	STEERING PLATE <input type="checkbox"/> COMPOSITE <input checked="" type="checkbox"/> ALU	SHIMS 0 /mm RF 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> RR 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>

FRONT		REAR	
FRONT TOE	0 OUT	REAR TOE	1 IN
OFFSET	2 SLOTS	OFFSET	5 SLOTS
WHEELBASE SHIM	0mm <input type="checkbox"/> 1mm <input checked="" type="checkbox"/>	WHEELBASE SHIM	2 /mm
ROLL CENTER HOLDER	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	BATTERY PLACEMENT LONG SIDE FRONT <input type="checkbox"/> LONG SIDE REAR <input checked="" type="checkbox"/>	
UPPER DECK	MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	BATTERY SIZE STD. SHORT <input checked="" type="checkbox"/> LOW SHORT <input type="checkbox"/>	
	GUARD BRACE FLEX 1 2 3 4 5 6 7 8	UPPER BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	

FRONT		REAR	
FRONT CAMBER	-1	REAR CAMBER	-2
FRONT ARM	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	DIFF HEIGHT <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	
RIDE HEIGHT	20 mm	RIDE HEIGHT	20 mm
	#10721 GAUGE		
		REAR ARM	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>

FRONT		REAR	
ARM MOUNT	COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/>	REAR ARM SHIMS 0 /mm	
CHASSIS BRACE	MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	WING HIGH <input checked="" type="checkbox"/> LOW <input type="checkbox"/> OTHER /mm	
SERVO WEIGHT	STANDARD <input type="checkbox"/> LOW PROFILE <input checked="" type="checkbox"/>	CHASSIS ALU <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	
	CHASSIS FLEX <input checked="" type="checkbox"/> SCREW USED <input type="checkbox"/> SCREW NOT USED		