

SET-UP SHEET

XRAY GTX8'23 SET-UP VER. 01 ©XRAY

XRAY GTX8'23 C-HUB

RACE	Rd1 Cat																									
TRACK	Cerdanyola																									
NAME	Borja Gutarra	DATE																								
TEMPERATURE AIR	8	TEMPERATURE TRACK																								
LAPS	FINAL POS.	BEST LAPTIME /sec																								
RACE LENGTH		/min																								
TRACKS																										
CONDITION	SMOOTH <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> BUMPY <input type="checkbox"/>																									
	TECHNICAL <input type="checkbox"/> MIXED <input checked="" type="checkbox"/> FAST <input type="checkbox"/>																									
TRACTION	LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH <input type="checkbox"/>																									
1ST GEARING 2ND																										
<table border="1"> <tr> <td>13T</td><td>14T</td><td>15T</td><td>16T</td><td>17T</td><td>18T</td> <td>PINION GEARS</td> <td>17T</td><td>18T</td><td>19T</td><td>20T</td><td>21T</td> </tr> <tr> <td><input checked="" type="checkbox"/></td><td><input type="checkbox"/></td><td><input type="checkbox"/></td><td><input type="checkbox"/></td><td><input type="checkbox"/></td><td><input type="checkbox"/></td> <td></td> <td><input checked="" type="checkbox"/></td><td><input type="checkbox"/></td><td><input type="checkbox"/></td><td><input type="checkbox"/></td><td><input type="checkbox"/></td> </tr> </table>			13T	14T	15T	16T	17T	18T	PINION GEARS	17T	18T	19T	20T	21T	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
13T	14T	15T	16T	17T	18T	PINION GEARS	17T	18T	19T	20T	21T															
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>															
SPUR GEARS																										
<table border="1"> <tr> <td>48T</td><td>49T</td><td>50T</td><td>STANDARD</td><td>GRAPHITE</td><td>45T</td><td>46T</td><td>47T</td> </tr> <tr> <td><input checked="" type="checkbox"/></td><td><input type="checkbox"/></td><td><input type="checkbox"/></td> <td><input type="checkbox"/></td><td><input type="checkbox"/></td> <td><input checked="" type="checkbox"/></td><td><input type="checkbox"/></td><td><input type="checkbox"/></td> </tr> </table>			48T	49T	50T	STANDARD	GRAPHITE	45T	46T	47T	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>								
48T	49T	50T	STANDARD	GRAPHITE	45T	46T	47T																			
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>																			
CLUTCH																										
CLUTCH STANDARD <input checked="" type="checkbox"/> OTHER <input type="checkbox"/> SPRINGS TIGHTEN 0.1																										
SHOE Std Std SPRING																										
DIFFERENTIAL																										
FRONT Gh 1M CASE MATERIAL Gh 50k OIL																										
SHOCKS																										
FRONT 1/3 800 Std 10 SPRINGS OIL 1/2 800 Std 10 MEMBRANE REBOUND PISTONS 1.1 mm 1.2 mm 1.3 mm 1.4 mm OTHER PISTONS																										
ANTI-ROLL BAR																										
FRONT 2.5 /mm THICKNESS 2.8 /mm																										
TIRES																										
TIRES TYPE: XM3 ← COMPOUND → XM2																										
ENGINE																										
TYPE Fx G501																										
MUFFLER Fx																										
MANIFOLD Fx																										
PLUG																										
FUEL Shot fuel																										
BODY TYPE		TOTAL WEIGHT																								
Gt6		/g																								
COMMENTS																										

FRONT		REAR	
STEERING BLOCK COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	C-HUB COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	FRONT ARM SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/>	REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> X-HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/>
OFFSET 0 <input checked="" type="checkbox"/> +1 <input type="checkbox"/> +2 <input type="checkbox"/>	CASTER 16° <input type="checkbox"/> 6° <input checked="" type="checkbox"/> 2° <input type="checkbox"/>	UPPER SHOCK POSITION 1 2 3 4 5 6	UPRIGHT ROLL CENTER 1 2 3 4 5 6
CAMBER LINK 1 2 3 4 5 6	REAR ROLL CENTER 1 2 3 4 5 6	REAR SHOCK PLATE POSITION IN <input checked="" type="checkbox"/> OUT <input type="checkbox"/>	LOWER ROLL CENTER 1 2 3 4 5 6
FRONT DROOP 22	MEASURE UNDER WHEEL AXLE #107717 GAUGE	REAR DROOP 23	MEASURE UNDER WHEEL AXLE #107717 HUDY GAUGE
FRONT		REAR	
BUMP STEER SHIM /mm STEERING BLOCK 0 STEERING PLATE 0 SHIMS PLACE ALWAYS UNDER		WING HIGH 34.7 /mm	
WHEELBASE SHIM POSITION 0 mm <input checked="" type="checkbox"/> 2 mm <input type="checkbox"/>		GRAPHITE BRACE WITHOUT <input checked="" type="checkbox"/> 1-PIECE <input type="checkbox"/> 2-PIECES <input type="checkbox"/>	
SHIMS BEHIND FRONT ARM FF 1° <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/> FR 1° <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/>		REAR DIFFUSOR YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	
SHIMS IN FRONT OF REAR ARM RF 1° <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/> RR 1° <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/>		LOWER ROLL CENTER ECCENTRIC BUSHINGS	
1.25 FRONT TOE OUT		3 REAR TOE IN	
TIGHTEN <input checked="" type="checkbox"/> SERVO SAVER MATERIAL TIGHT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> MEDIUM <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> SOFT <input type="checkbox"/>		UPPER PLATE COMPOSITE <input type="checkbox"/> GRAPHITE <input type="checkbox"/>	
ACKERMANN POSITION 3 2 1		WHEELBASE 0 mm <input type="checkbox"/> 1 mm <input checked="" type="checkbox"/> 2 mm <input type="checkbox"/> 3 mm <input type="checkbox"/> 4 mm <input type="checkbox"/> SHIMS IN FRONT OF UPRIGHT	
ENGINE MOUNT STANDARD <input type="checkbox"/> MONOBLOCK <input type="checkbox"/>			
2 FRONT CAMBER		REAR CAMBER 2.5	
REAR DIFF HEIGHT UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>			
LENGTH mm		LENGTH mm	
RIDE HEIGHT 7.5 /mm		RIDE HEIGHT 8.5 /mm	
FRONT		REAR	