

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	PYC X SPECIAL RC RD1				
TRACK	Hong Kong PYC circuit				
NAME	Kimi Yam	DATE	19-5-2024		
QUAL POSITION	TQ	FINAL POSITION	A1	BEST LAP TIME	12.658 /sec
				LAPS	24 / 5:11.115

TRACK		
TRACK SURFACE	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED
	<input type="checkbox"/> FAST	
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM
	<input type="checkbox"/> HIGH	

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL
PINION	28 /T	SPUR GEAR
	108 /T	FINAL DRIVE RATIO
		7.33

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
450	OIL /Cst	450
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH	8.5 /mm	SHOCK LENGTH	8.5 /mm

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

SA-04-3S	TIRES	SA-04-3S
V3 Yellow	ADDITIVE	V3 Yellow
6	ADDITIVE TIMING	6
5	WIPE OFF TIME	5
Timing: 5	TIRE WARMERS	Timing: 5
Temp.: 60		Temp.: 60
FRONT LEFT	FRONT RIGHT	REAR LEFT
	TREATED AREA	

TOTAL WEIGHT	1310 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
--------------	---------	----------------	------------	-----------

MOTOR	Team Powers V5 4.5T	TIMING	22
ESC	Team Powers V5BT	BATTERIES	Gens ace 2.0 6100mah
BODY	Xtreme Twister UL	WING	Speciale 0.5mm

66 /mm	Dimension from body post to window bottom line	BODY POSITION
7	Dimension from body post to upper holder	WING SIDE PLATE
		YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
	Dimension from edge to surface	

X4'23	<input checked="" type="checkbox"/>	1.6mm	<input checked="" type="checkbox"/>	2.0mm	<input checked="" type="checkbox"/>	1.6mm
X4'22	<input type="checkbox"/>	2.0mm	<input type="checkbox"/>	2.0mm	<input type="checkbox"/>	1.6mm
X4'22	<input type="checkbox"/>	2.0mm	<input type="checkbox"/>	1.6mm	<input type="checkbox"/>	
		NONE	<input type="checkbox"/>	BEARING	<input type="checkbox"/>	

COMMENTS

FRONT & REAR	SUSPENSION
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER	SHIM
1.5 /mm	19 /mm
HEIGHT	
2 /mm	TOE GAIN
5.2 /mm	2.5 /mm
FR 2 /mm	5.4 /mm
RR 2.5 /mm	
SERVO SAVER	
SERVO HORN	

FRONT
2 /deg. CAMBER
Left = Right
BODY STOP
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
17.5 /mm
SHOCK HOLDERS
SHIM 2 /mm
SUSPENSION FLEX
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT
58mm 59mm BEARING BLADE
#107702 Chassis Droop Gauge Blocks
#107712 Chassis Droop Gauge
5.6 /mm
DOWNSTOP

REAR
2 /deg. CAMBER
Left = Right
BODY POST
VERTICAL <input type="checkbox"/>
HORIZONTAL <input checked="" type="checkbox"/>
SHOCK HOLDERS
FIXED <input checked="" type="checkbox"/> ACTIVE <input type="checkbox"/>
SHIM 2 /mm
SUSPENSION FLEX
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT
52mm 54mm BEARING BLADE
#107702 Chassis Droop Gauge Blocks
#107712 Chassis Droop Gauge
4.4 /mm
DOWNSTOP

FRONT TOP VIEW	REAR
1 TOE OUT	3 TOE IN
Left = Right	Left = Right
ACKERMANN	SHORT LiPo BRASS WEIGHT
SHIM 1 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
40g	BRASS WEIGHT FOR MOTOR MOUNT
12	40g
15	
DIFF POSITION	DIFF POSITION
<input checked="" type="checkbox"/> UP	<input checked="" type="checkbox"/> UP
<input type="checkbox"/> DOWN	<input type="checkbox"/> DOWN
<input type="checkbox"/> +1mm	<input type="checkbox"/> +1mm
UPPER ARM	UPPER ARM
SOFT <input checked="" type="checkbox"/>	SOFT <input checked="" type="checkbox"/>
MEDIUM <input type="checkbox"/>	MEDIUM <input type="checkbox"/>
STEERING BRIDGE	STEERING
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SHIM /mm
HUB OFFSET	PLATE
STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm	7.5
	8.0mm 7.5mm
	STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK	T-BRACE
26 /deg.	ALU <input type="checkbox"/>
	BRASS <input type="checkbox"/>
SERVO HOLDER	CHASSIS T-BRACE
FR RE	
MOTOR MOUNT	
CHASSIS	
GRAPHITE <input checked="" type="checkbox"/>	
ALU <input type="checkbox"/>	
ALU 1.5mm <input type="checkbox"/>	
FRONT ARMS	REAR ARMS
MEDIUM <input type="checkbox"/>	MEDIUM <input type="checkbox"/>
HARD <input checked="" type="checkbox"/>	HARD <input checked="" type="checkbox"/>