

# SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

# XRAY X4'24

RACE	Montbrison CF#3			
TRACK	Montbrison			
NAME		DATE		
QUAL POSITION	10	FINAL POSITION	8	
BEST LAPTIME			LAPS	
				TIME
				/sec /

TRACK				
TRACK SURFACE	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT		
TRACK LAYOUT	<input checked="" type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED	<input type="checkbox"/> FAST	
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH	

FRONT		TRANSMISSION		REAR	
GEAR DIFF OIL	/cSt	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL	7k	/cSt
PINION	39	SPUR GEAR	96	FINAL DRIVE RATIO	4.67

FRONT		SHOCKS		REAR	
2.5-2.8		XRAY SPRINGS		2.6	
425		OIL /cSt		475	
0		REBOUND %		0	
<input type="checkbox"/> YES	<input checked="" type="checkbox"/> NO	FOAM INSERTS		<input type="checkbox"/> YES	<input checked="" type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input type="checkbox"/> 1.1mm	<input type="checkbox"/> 1.1mm	<input type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/>
<input type="checkbox"/> PSS	<input checked="" type="checkbox"/> 1.2mm	<input checked="" type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS	<input type="checkbox"/>
SHOCK LENGTH		8.5 /mm	SHOCK LENGTH	
1.1		THICKNESS/mm	1.2	

Rush 36x		TIRES	Rush 36x		
Phub Rose			Phub Rose		
50			50		
Timing:		Temp.:	Timing:		Temp.:
FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT	

TOTAL WEIGHT	1300	WEIGHT BALANCE	FRONT 51 %	REAR 49 %
--------------	------	----------------	------------	-----------

MOTOR	R1wurks 13.5 SS	TIMING	50
ESC	R1wurks Digital3	BATTERIES	gensAce 6500
BODY	Volverine	WING	

64 /mm	Dimension from body post to window bottom line	BODY POSITION
51 /mm	Dimension from edge to surface	WING SIDE PLATE
		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>

X4'23	<input checked="" type="checkbox"/>	1.6mm	<input checked="" type="checkbox"/>	2.0mm	<input checked="" type="checkbox"/>	1.6mm
X4'22	<input type="checkbox"/>	2.0mm	<input type="checkbox"/>	2.0mm	<input type="checkbox"/>	1.6mm
X4'22	<input type="checkbox"/>	2.0mm	<input type="checkbox"/>	1.6mm	<input type="checkbox"/>	NONE
TOP DECK CUTTING						

Droop Aerox AV 23.6 = 5.6 avec rondelle de 0.5mm  
 Droop Aerox AR 22.6 = 4.0 avec rondelle de 1mm  
 Support de carro Arrière RCMaker  
 PareChoc 3D ae-rc.fr

FRONT & REAR SUSPENSION	
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER	SHIM
1 /mm	6 /mm
HEIGHT	SHIM
19 /mm	6 /mm
TOE GAIN	SHIM
1.5 /mm	2.5 /mm
TOE LOSS	SHIM
5.2 /mm	2.5 /mm

FRONT	
CAMBER	BODY STOP
2 /deg.	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
Left = Right	14 /mm
SHOCK HOLDERS	SHIM
SHIM	2 /mm
SUSPENSION FLEX	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT	BEARING BLADE
58mm 59mm	BEARING BLADE
#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge
23.6 /mm	DOWNSTOP

REAR	
CAMBER	BODY POST
2 /deg.	VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>
Left = Right	SHOCK HOLDERS
SHIM	SHIM
2 /mm	4 /mm
SUSPENSION FLEX	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT	BEARING BLADE
52mm 54mm	BEARING BLADE
#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge
22.6 /mm	DOWNSTOP

FRONT TOP VIEW		REAR	
TOE OUT	ACKERMANN	TOE IN	SHORT LiPo BRASS WEIGHT
Left = Right	SHIM	Left = Right	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
1	0.5 /mm	2.75	40g
DIFF POSITION	UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> +1mm	DIFF POSITION	UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> +1mm
UPPER ARM	SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>	UPPER ARM	SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>
STEERING BRIDGE	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	STEERING	SHIM
HUB OFFSET	STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm	SHIM	1 /mm

FRONT BOTTOM VIEW		REAR	
STEER. LOCK	T-BRACE	ALU BRASS	CHASSIS T-BRACE
26 /deg.	FR RE	FR RE	FR RE
SERVO HOLDER	MOTOR MOUNT	CHASSIS	REAR ARMS
FRONT ARMS	GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU 1.5mm	REAR ARMS	MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>