

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	XRS Grand Final				
TRACK	Hudy Arena				
NAME	Stefan Schulz		DATE	14.-16.06.2024	
QUAL POSITION	3	FINAL POSITION		BEST LAPTIME	/sec
LAPS	/				

TRACK					
TRACK SURFACE	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT			
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED	<input type="checkbox"/> FAST		
TRACTION	<input type="checkbox"/> LOW	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH		

FRONT		TRANSMISSION		REAR	
GEAR DIFF OIL	/cSt	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL	8K	/cSt
PINION	44 /T	SPUR GEAR	92 /T	FINAL DRIVE RATIO	3.97

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
350	OIL /cSt	350
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH 8.5 /mm			
ANTI-ROLL BAR THICKNESS/mm 1.1			

Hudy A1		TIRES		Hudy A1	
Hudy Asphalt		ADDITIVE		Hudy Asphalt	
15		ADDITIVE TIMING		15	
0		WIPE OFF TIME		0	
Timing: 15	Temp.: 70	Timing: 15	Temp.: 70		
FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT	TREATED AREA	

TOTAL WEIGHT	1300 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
--------------	---------	----------------	------------	-----------

MOTOR	HW G4R	TIMING	46
ESC	HW XR10 Pro G2	BATTERIES	Gens Ace 8500
BODY	Wolverine 0.4	WING	0.5 Std

64 /mm	Dimension from body post to window bottom line	BODY POSITION
25	Dimension from body post to upper holder	WING SIDE PLATE
67 /mm	Dimension from edge to surface	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>

1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm
2.0mm	<input type="checkbox"/> 1.6mm	
NONE <input type="checkbox"/> BEARING <input type="checkbox"/>		

COMMENTS

FRONT & REAR SUSPENSION	
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER 1.5 /mm	HEIGHT 19 /mm
SHIM 6.5 /mm	
TOE GAIN 1.5 /mm	TOE IN 3.5 /mm
SHOCK HOLDERS SHIM 3 /mm	SUSPENSION FLEX YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
DRIVE SHAFT 58mm 59mm BEARING BLADE	SHOCK LENGTH 8.5 /mm

FRONT	
2 /deg. CAMBER	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
SHOCK HOLDERS SHIM 3 /mm	SUSPENSION FLEX YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
DRIVE SHAFT 58mm 59mm BEARING BLADE	SHOCK LENGTH 8.5 /mm
FRONT HUB MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	SHIM 0.5 /mm

REAR	
2 /deg. CAMBER	BODY POST VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>
SHOCK HOLDERS SHIM 3 /mm	SUSPENSION FLEX YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
DRIVE SHAFT 52mm 54mm BEARING BLADE	SHOCK LENGTH 8.5 /mm
REAR HUB MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	SHIM 1 /mm

FRONT TOP VIEW		REAR	
1 TOE OUT	ACKERMANN SHIM 0.5 /mm	3 TOE IN	SHORT LiPo BRASS WEIGHT
DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm	BRASS WEIGHT FOR MOTOR MOUNT	DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm	SHOCK HOLDERS SHIM 3 /mm
UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/>	STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/>	SUSPENSION FLEX YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm	STEERING SHIM/mm 7	HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm	SHOCK LENGTH 8.5 /mm

FRONT BOTTOM VIEW		REAR	
STEER. LOCK 26 /deg.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>	FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>
SERVO HOLDER	CHASSIS T-BRACE	CHASSIS GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU 1.5mm	